# EXCEPTIONAL MONO PRINTING MADE AFFORDABLE.

Efficiency meets productivity with the EcoTank Monochrome M15140 A3 printer. Powered by Epson PrecisionCore Heat-Free Technology, this printer delivers business quality prints at speeds of up to 25 ipm*. It allows prints of up to 7,500 pages while consuming less power so you can minimise and enjoy a low total cost of ownership in the long run. With the ability to handle different media types and produce sharp, durable prints using DURABrite ET Ink, the M15140 makes it efficient for businesses that require low cost, hassle-free and low maintenance printing.

UP TO 725 IPM — Print Speed

A3+ — Print up to A3+*

Duplex Printing

AUTO — Automatic Document Feeder

7500 — Ultra-High Page Yield

DIRECT — Wi-Fi Direct

Ethernet

Epson Connect

## IT'S IN THE DETAILS.

**ecotank**  PRECISIONCORE HEAT-FREE  4 YEARS OR 150,000 PAGES PRINTHEAD INCLUDED

### Built for Business
Maximise productivity with print speeds of up to 25 ipm*. Save cost from affordable pigment ink that deliver water-resistant laser-quality prints.

### Enhanced Reliability
Enjoy a peace of mind even when printing in large volumes with a warranty of 4 years**.

### Heat-Free Technology
Achieve high speed quality printing at low power consumption with Epson PrecisionCore Heat-Free Technology.

*For simplex only.  **2-year + 2-year extended warranty or 150,000 pages, whichever comes first, printhead included.

# SPECIFICATIONS

| Product Name | M15140 |
|---|---|
| Printer Type | Print, Scan, Copy with ADF |

**Printing**

| | |
|---|---|
| Printing Technology | PrecisonCore™ Printhead |
| Nozzle Configuration | 800 x 1 nozzles (Black) |
| Print Direction | Bi-directional printing |
| Maximum Resolution | 4800 x 2400 dpi |
| Minimum Ink Droplet Volume | 3.8 pl |
| Print Speed*1 | |
| Draft Text - Memo, A4 (Black#1) | Up to 32.0 ppm |
| ISO 24734, A4 (Black) | Simplex: Up to 25.0 ipm \| Duplex: Up to 16.0 ipm |
| ISO 24734, A3 (Black) | Simplex: Up to 13.5 ipm \| Duplex: Up to 10.0 ipm |
| First Page Out Time (Black), A4 | Simplex: Up to 5.5 sec \| Duplex: Up to 11.0 sec |
| Printer Language | ESC/P-R, ESC/P Raster |
| Automatic 2-sided printing | Yes (Up to A3) |

**Copying**

| | |
|---|---|
| Copy Speed | |
| ISO 29183, A4 (Black), Flatbed | Simplex: Up to 23.0 ipm |
| ISO 24735, A4 (Black), ADF | Simplex: Up to 22.5 ipm \| Duplex: Up to 15.5 ipm |
| Maximum Copies from Standalone | 999 copies |
| Reduction / Enlargement | 25 - 400% |
| Maximum Copy Resolution | 600 x 600 dpi |
| Maximum Copy Size | A3 / Ledger |

**Scanning**

| | |
|---|---|
| Scanner Type | Flatbed colour image scanner |
| Sensor Type | CIS |
| Optical Resolution | 1200 x 2400 dpi |
| Maximum Scan Area | 297 x 431.8 mm |
| Scanner Bit Depth | |
| Colour | 48-bit input, 24-bit output |
| Grayscale | 16-bit input, 8-bit output |
| Black & White | 16-bit input, 1-bit output |
| Scan Speed (Flatbed / ADF) | |
| Monochrome 200dpi | Flatbed: 5 sec \| ADF (Simplex / Duplex): Up to 26.0 ipm / 11.5 ipm |
| Colour 200dpi | Flatbed: 10 sec \| ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm |

**ADF Function**

| | |
|---|---|
| Support Paper Thickness | 64-95 g/m² |
| Paper Capacity | 50 sheets |

**Paper Handling**

| | |
|---|---|
| Paper Feed Method | Friction Feed |
| Number of Paper Trays | 3 (Front 2, Rear 1) |
| Paper Hold Capacity | |
| Input Capacity | Cassette 1: 250 sheets (80 g/m²)<br>Cassette 2: 250 sheets, (80 g/m²)<br>Rear Slot: 50 sheets (80 g/m²) |
| Output Capacity | 125 sheets (80 g/m²) |
| Paper Size | A3, Super B (13 x 19"), Indian Legal, Letter, A4, 16K (195 x 270 mm), 8K (270 x 390 mm), Executive (7.25 x 10.5"), B4, B5, A5, B6, A6, 8.5 x 13", Legal (8.5 x 14"), 8 x 10", Envelopes: #10, DL, C6, C4 |
| Maximum Paper Size | 329 x 6000 mm |
| Print Margin | 3mm top, left, right, bottom via custom settings in printer driver |

**Interface**

| | |
|---|---|
| USB | USB 2.0 |
| Network | Ethernet, Wi-Fi IEEE 802.11a/b/g/n/ac, Wi-Fi Direct |
| Network Protocol | TCP/IPv4, TCP/IPv6 |
| Network Management Protocols | SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD |

**Mobile and Cloud Printing**

| | |
|---|---|
| Epson Connect | Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud |
| Other Mobile Solutions | Apple AirPrint, Mopria Print Service |

**Control Panel**

| | |
|---|---|
| LCD Screen | 2.7" LCD Touch Screen |

**Printer Software**

| | |
|---|---|
| Software Support | Epson ScanSmart |
| Operating System Compatibility | Windows XP / Vista / 7 / 8 / 8.1 / 10<br>Windows Server 2003 / 2008 / 2012 / 2016 / 2019<br>Mac OS X 10.6.8 or later |

**Electrical Specifications**

| | |
|---|---|
| Rated Voltage | AC 220-240 V |
| Rated Frequency | 50-60 Hz |
| Power Consumption | |
| Operating | 19.0 W |
| Standby | 8.0 W |
| Sleep | 0.8 W |
| Power Off | 0.2 W |

**Noise Level**

| | |
|---|---|
| PC Printing / Plain Paper Default*2 | Sound Power 6.7 B(A),  Sound Pressure 52 dB(A) |

**Consumables**

| Consumables | Page Yield*3 | Order Code |
|---|---|---|
| Black Ink Bottle | 7,500 | 008 |
| Maintenance Box | | C12C934591 |

---

## Dimensions & Weight

**M15140**
**Weight:** 20.2 kg



350 mm
500 mm
515 mm

#1
Black Text

*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.

*2 Default mode in accordance with ISO7779 for MFPs.

*3 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and black-and-white graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. Ink is used for both printing and printhead maintenance.

Information correct as at February 2021