INKJET COLOUR LABEL PRINTER COLORWORKS CW-C8050

Renewal SERUM

EPSON

\$39.99

SWIFT PRECISION IN INDUSTRIAL LABELS.

Hydrocodone

Hydrocodo

Streamline Your Industrial Labeling for Maximum Efficiency and Quality.

Transform your industrial labeling process with unmatched efficiency and quality. Maximise efficiency in industrial label printing with Epson ColorWorks CW-C8050. Engineered for high-volume applications, it offers exceptional quality using PrecisionCore[®] Heat-Free technology and UltraChrome DL Pigment inks, producing sharp images and text at fast speeds. With high-yield ink capacity and remote management via Epson Cloud Solution PORT®, you will boost productivity while minimising maintenance and energy costs.

ENGINEERED FOR 9000

Batch High Speed High Capacity Printing Printing Inks



PRECISIONCOR

High-Quality Colour Label Printing

Create customised labels on demand, achieving exceptional speeds of up to 300mm per second with reliable performance.

Enhanced Performance Features

Improved performance with an ink pack capacity of up to 480ml and versatile media handling, including thick card printing.

EPSON

Streamlined Connectivity

Enhanced connectivity with multi-platform drivers and optional Ŵi-Fi for reliable printing from iOS and Android devices.


Robust Solutions for High-Volume Labeling

The ColorWorks CW-C8050 is a versatile inkjet label printer designed for high-volume enterprises, facilitating efficient in-house label production on-demand. It supports various media types and widths from 1 to 4 inches, delivering exceptional print quality and speed. Its user-friendly design ensures easy maintenance, while the unique paper path design, along with adjustable platen gaps and advanced sensors, enables seamless printing on diverse materials.



Superior Print Quality

The CW-C8050 printer offers an impressive resolution of 600x1200dpi, making it perfect for barcode scanning and fine text. High print consistency is achieved through the Epson PrecisionCore printhead and UltraChrome DL Pigment inks. With nozzle verification technology, you can maintain optimal print quality even if nozzles become clogged. Additionally, spot colour management and ICC profiling ensure precise colour matching for outstanding results.



The PrecisionCore line head enables sharp printing with fine gradation



Versatile Media Options

The CW-C8050 provides an adaptable selection of media and inks tailored to meet diverse customer needs. utilising high-durability inks for consistently exceptional results. It accommodates both matte and high gloss media, as well as films and synthetic materials. Thanks to its adjustable platen gap, you can effortlessly print on thicker media up to 0.6mm.



Washi-textured

High-Capacity Ink Pack System

EPSON ULTRACHROM

DL

The printer features 480ml ink pouches, the largest volume in its class. This capacity enables extended print runs without interruption, minimising downtime and maximising productivity.



Flexible Integration Options

This printer prioritises convenience with USB 3.0, high-speed Ethernet, optional Wi-Fi, and an I/O port for easy setup. It integrates smoothly with legacy systems using the ESC/Label command, ensuring compatibility. It also supports popular middleware and includes Device Type and ABAP drivers for straightforward SAP Direct Printing. Enjoy cloud printing flexibility without a PC, and benefit from simple maintenance with one-side access. The new CoverPlus option offers extra peace of mind for Industrial and High-Productivity Value customers.

Improved Remote Management and Serviceability

Epson Software Solutions

Epson Device Admin

Effortlessly manage a fleet of printers remotely, allowing for installation, configuration, monitoring, maintenance, and troubleshooting to enhance productivity and reduce costs.


Epson Cloud Solution PORT

Achieve next-level productivity with Epson Cloud Solution PORT, a revolutionary platform for easy PORT remote monitoring of your printer fleet. Designed EPSON for simplicity and security, it offers a live view of production, equipment utilisation, and service information, enabling you to enhance efficiency and optimise your Epson printing workflow.



Epson Remote Monitoring System

Monitor and manage your devices from location through the internet with a cloud-based system. Run billing programmes and provide accurate support by checking the current status of the devices installed in your customer's premises.



Third-Party Labeling Software

Loftware Cloud

Provides true cloud-enabled label printing for flexibility and efficiency.











Drivers and SDKs



SAP ABAP Drivers

Ensure interoperability and customisation while maintaining security and compatibility with SAP systems.





Cross-Platform Drivers

Available for Windows, Linux, and MacOS to offer versatile printing options.

Epson Support Portal

Helps users find the right drivers for various operating systems.



Others

Epson ESC Label

This command language offers programmable control, flexible text formatting, barcode printing, graphical elements inclusion, and seamless integration for precise label printing across multiple industries.

Web Config

Configure printers through any web browser, ensuring platform-independent access.

BarTender by Seagull Scientific

Offers comprehensive label design, printing, barcode printing, RFID encoding, and card printing.

Label software by TEKLYNX

Simplifies the creation of dynamic on-demand colour labels



SPECIFICATIONS

MODEL NUMBER Print Printhead Printing Technology Maximum Print Resolution Maximum Print Speed^{*1} Colour Adjustment Media Dispense Type Paper-Feeding Mechanism Life Ink Ink Type Ink Colours Ink Pack Configuration Ink Pack Capacity

Media Supported Media Types Supported Media Constructions

Die-Cut Label Gap Gap Sensor Position

Black Mark Sensor Position Black Mark Wdith Black Mark Length

Maximum Print Width Media Width (Min. - Max.) Internal Roll Media External Roll Media, Fanfold Media Length (Min. - Max.) Media Thickness (Min. - Max.) Internal Roll Media

Connectivity USB

Ethernet Wi-Fi General-Purpose I/O Port Print Utilities and Remote Management Tools

Direct Command-Based Printing

Display Supported Operating System

Environmental Conditions Temperature


Humidity Printer Dimensions (W x D x H) **Printer Weight** Packaging Dimensions (W x D x H **Packaging Weight Electrical Specifications** Rated Voltage Rated Frequency Power Consumption **Acoustic Noise** FMI **Eco Features**

ecisionCore Printhead, permanent	
ecisionCore Line Inkjet Technology	
00 x 1,200 dpi	
o to 300 mm per second (11.8"/sec)	
oson Preferred Colour, Epson Standard, Epson Vivid Colour	
uto Cutter (scissor type), up to 1.5 million cuts	
00 km	
traChrome DL SJIC52P Pigment Ink	
ack (Gloss or Matte Black Options), Cyan, Magenta, Yellow	
our (4) individual ink packs	
30 ml each pack ²	
e-Cut Label, Full-Page Label, Continuous Label, Tag	
ain Paper, Textured Paper, Matte Paper, Synthetic,	
lossy Paper, Glossy Film, High Glossy Paper	
mm – 6 mm (0.12" – 0.24")	
djustable; 3 mm – 56 mm (0.12" – 2.20")	
om left side; pitch: 1 mm (0.04")	
xed position; approximately 12.4 mm (0.49") from left	
mm (0.75") or more from paper edge	
mm – 25.4 mm (0.16" to 1.0") with 4 mm (0.16") or more	
white space around the black mark	
08 mm (4.25")	
$5.4 \text{ mm} = 112 \text{ mm} (1.0^{\circ} - 4.40^{\circ})$	
5.4 mm - 112 mm (1.0" - 4.40")	
) mm – 112 mm (1.97" – 4.40") mm – 1,016 mm (0.31" – 40")	
084 mm – 0.600 mm (3.30 mils – 23.62 mils)	
edia Core Inner Diameter: 76.2 mm (3.0")	
edia Maximum Outer Diameter: 203.2 mm (8.0")	
SB 3.0 (one port), USB 2.0 (one port)	
00Base-T/100Base-TX/10Base-T	
ptional Wi-Fi dongle available (OT-WL06)	
-Sub 25	
	۱,
osonNet SetupManager, EpsonNet Config SE, Epson Device Admir	
psonNet SetupManager, EpsonNet Config SE, Epson Device Admir pson Deployment Tool, PrinterSetting, Colour Tone Matching Assist	ant,
	ant,
oson Deployment Tool, PrinterSetting, Colour Tone Matching Assist	ant,
oson Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater,	ant,
oson Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, oson Cloud Solution PORT ³ Production Monitor, WebConfig	
Dison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, Dison Cloud Solution PORT ³ Production Monitor, WebConfig Debra® ZPL II® native language support, plus command extensions,	
Dison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, Dison Cloud Solution PORT ³ Production Monitor, WebConfig Debra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language	
Dison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, Dison Cloud Solution PORT ³ Production Monitor, WebConfig Dison® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing	je;
Dison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, Dison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing 7" Colour LCD	je; it),
boson Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, boson Cloud Solution PORT ³ Production Monitor, WebConfig ebra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-b	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig ebra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command languag AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit) indows Server® 2022, Windows Server 2019, Windows Server 2019	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig ebra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-b indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64)	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C,	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command language AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C, b to 120 H; Matte Black Ink: -10°C to 40°C	ge; it), 6,
 boson Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, boson Cloud Solution PORT³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command languag AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 2015 indows Server 2012, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C, boto 120 H; Matte Black Ink: -10°C to 40°C perating: 20% – 80% RH (No Condensation) 	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command languag AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C, to 120 H; Matte Black Ink: -10°C to 40°C perating: 20% – 80% RH (No Condensation) 20 x 392 x 420 mm / 24.4 x 15.4 x 16.5 inch	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command languag AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C, to to 120 H; Matte Black Ink: -10°C to 40°C perating: 20% – 80% RH (No Condensation) 20 x 392 x 420 mm / 24.4 x 15.4 x 16.5 inch poprox. 35 kg	ge; it), 6,
bison Deployment Tool, PrinterSetting, Colour Tone Matching Assist SB Printer Class Device Replacement, Epson Firmware Updater, bison Cloud Solution PORT ³ Production Monitor, WebConfig abra® ZPL II® native language support, plus command extensions, allow for colourisation of data; ESC/Label color command languag AP® Direct Printing 7" Colour LCD indows® 11, Windows 10 (32-bit/64-bit, Windows 8.1 (32-bit/64-bit indows Server® 2022, Windows Server 2019, Windows Server 201 indows Server 201, Windows Server 2012 R2, OS X® 10.9.5 or late acOS® 10.12 or later, CentOS® 7 (x86_64), Ubuntu 20.04 (x86_64) perating: 5°C to 35°C / Storage: -15°C to 40°C, to 120 H; Matte Black Ink: -10°C to 40°C perating: 20% – 80% RH (No Condensation) 20 x 392 x 420 mm / 24.4 x 15.4 x 16.5 inch	ge; it), 6,

Operating: Approx. 83.0 kW; Standby: Approx. 3.3 W; Power Off: Approx. 0.4 W

Reduces waste materials by using Replaceable Ink Pack System (RIPS)

Dimensions & Weight CW-C8050 Weight: 35 kg (79.4 lb)



Take-up Unit Weight: 4.25 kg (9.4 lb)



MAIN UNIT

CW-C8050 (BK) Colour Inkjet Printer CW-C8050 (MK) Colour Inkjet Printer C31CL02106E1 C31CL02106E2

WHAT'S INCLUDED

ColorWorks CW-C8050 Printer (Gloss or Matte) Four Ink Packs (CMYK) Maintenance Box AC Power Adapter and Cord Sample Label Roll Startup Guide

OPTIONS Take-up Unit

CONSUMABLES (INK PACKS)

Glossy Black	
Cyan Ink Pack	
Magenta Ink Pack	
Yellow Ink Pack	
Matte Black	

C13T55S100 C13T55S200 C13T55S300 C13T55S400 C13T55S500

C32C882501

©2024 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is a registered trademark of Seiko Epson Corporation.

All other product and company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

This product uses only genuine Epson-brand ink packs. Other brands of ink packs and ink supplies are not compatible and, even if described as compatible, may not function properly or at all.

50 Hz – 60 Hz

Approx. 57 db

*1: *2:

FCC Class A, ICES-003 Class A

Printing in the Source as companies, may not function property of at all. Printing in full 600x1,200 resolution. Part of the ink from the first ink packs are used for initialising the printer. Ink usage will vary based on images printed, print settings, paper type, frequency of use, temperature and humidity. Variance may be more pronounced when printing infrequently or predominantly with one ink colour. Ink is used for printing and printer maintenance, and all colours must be available for printing. For print quality, a variable amount of ink remains after the "replace ink" indicator comes on. All features of this system require an active Internet connection and the use of a supported browser. *Q.

RoHS compliant, Actively uses recycled plastic parts

Information correct at time of printing. Printed November 2024