



The Epson All-in-One EcoTank L3550 and L5590 are designed to maximise your print productivity and convenience at the office. The upgraded PrecisionCore Printhead enables even faster printing speeds and replaceable maintenance box reduces repair downtime, improving efficiency. Both printers come with a full suite of connectivity features, including wireless connectivity and enabling direct printing from smart devices. Download Epson Smart Panel app to your mobile device and turn it into an intuitive control centre that enables you to power On/Off*, set up, monitor your printer and ink level effortlessly. Experience this high-speed all-in-one printing solution today.













 \Box Epson

Epson Smart Panel

Replaceable Maintenance







Productivity Meets Durability

With PrecisionCore Printhead enabled, L3550 and L5590 has faster printing speed at 15/8 ipm. Improved mechanical design on parts that support paper feed-out contributes to longer product life -2 years or 50,000 pages^{$^{^{\circ}}$}.

Sustainability in Mind

Reduce power consumption through Heat-Free Technology. With hardware made from 30% recycled plastic¹, utilising 84% less consumables compared to ink cartridge models² and over 80% recycled cardboard packaging, carbon footprint is minimised.

Simplify User Interface"

New concept of Flip UI simplifies user operation. Preset your frequently used functions as different cards, reducing the hassle of going through numerous setting parameters.

Applicable to EcoTank L3550 only. ** Available only on L5590. ^ 2-year warranty or 50,000 pages, whichever comes first, printhead included.

Virgin plastic savings equivalent to approximately 250 plastic spoons, calculated as 3g of High Impact Polystyrene (IIPS) plastic spoon. Ratio of the amount of recycled plastic weight to overall plastic component weight of the hardware. The amount of recycled contents and recycled material varies depending on the model, manufacturing time and site.
 Material weight comparison of consumables (including packaging) between Epson ink cartridges of WF2630 series and Epson ink bottles of L5590/3550 series.

SPECIFICATIONS

Product Name	L3550	L5590	
Printer Type	Print, Scan and Copy	Print, Scan, Copy, Fax with ADF	
Printing	Draginian Cara Drinthand		
rinting Technology lozzle Configuration	PrecisionCore Printhead 400 x 1 nozzles Black, 128 x 1 nozzles per Colour (Cyan, Magenta, Yellow)		
rint Direction	Bi-directional printing		
faximum Resolution		4800 x 1200 dpi (with Variable-Sized Droplet Technology)	
finimum Ink Droplet Volume	3.3 pl		
rint Speed*1	Ha to 00 man (00 man)		
Draft Text - Memo, A4 (Black*1/ Colour*2) ISO 24734, A4 (Black / Colour)	Up to 33 ppm / 20 ppm Simplex: Up to 15 ipm / 8 ipm		
First Page Out Time (Black / Colour)	Approx. 10 sec / 16 sec		
Photo Default - 10 x 15 cm / 4 x 6"*2 #3	Approx. 69 sec / 90 sec		
(Border / Borderless)			
rinter Language	ESC/P-R No		
utomatic 2-sided printing	INO		
opy Speed			
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 10.8 ipm / 5.5 ipm		
ISO 29183, A4 (Black / Colour), ADF		Approx. 60 sec / 82 sec	
opy Quality	Standard	Standard / High	
aximum Copies from Standalone aximum Copy Resolution	30 copies 600 x 600 dpi	99 copies	
aximum Copy Resolution aximum Copy Size	A4, LTR	Legal	
canning	7 (4, 2111	Logui	
canner Type	Flatbed colour image scanner		
ensor Type	CIS		
ptical Resolution	1200 x 2400 dpi		
aximum Scan Area	216 x 297 mm (8.5 x 11.7")		
canner Bit Depth Colour	48-bit input, 24-bit output		
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		
can Speed (Flatbed / ADF (Simplex))			
Monochrome 200 dpi	11 sec	12 sec / 5.0 ipm	
Colour 200 dpi	28 sec	29 sec / 5.0 ipm	
vpe of Fax	Walk-up Black-and-White and Colour Fax Ca	anghility.	
eceive Memory / Page Memory	1.1 MB, Page memory up to 100 pages		
rror Correction Mode	ITU-T T.30		
ax Speed (Data Transfer Rate)	Up to 33.6 kbps, Approx. 3 sec / page		
ax Resolution	Up to 200 x 200 dpi		
ransmission Paper Size	Latter A4		
Flatbed ADF	Letter, A4 A4, LTR, 8.5 x 13", Legal, Oficio 9, Mexico-Oficio, Indian-Legal		
eceiving Paper Size	Letter, A4, Legal		
peed Dial / Group Dial	Up to 100 numbers, 99 groups		
ax Features	PC Fax (Transmission / Receive), Automatic Redial, Address book, Broadcast Fax (Mono		
ADF Function (L5590 only)	Only), Transmit Reservation, Polling Reception	n	
Support Paper Thickness	64 - 95 g/m²		
Paper Capacity	30 sheets		
aper Handling			
aper Feed Method	Friction feed		
lumber of Paper Trays aper Hold Capacity	1		
Input Capacity	100 sheets of Plain Paper (80 g/m²), 20 she	ets of Premium Glossy Photo Paper	
Output Capacity	30 sheets of Plain Paper (80 g/m²), 20 sheets of Premium Glossy Photo Paper		
Paper Size	A4, A5, A6, B5, B6, Letter, Legal, Indian-Legal, 100 x 148 mm, 3.5 x 5", 4 x 6", 5 x 7",		
4	5 x 8", 8 x 10", 8.5 x 13", 16:9 Wide, 16K, E	Envelopes: #10, DL, C6	
Maximum Paper Size Supported Paper Weight	215.9 x 1200 mm (8.5 x 47.24")		
Plain Paper	64 - 90 g/m ²		
Premium Glossy Photo Paper	102 - 300 g/m ²		
rint Margin	0 mm top, left, right, bottom via custom set	tings in printer driver" ³	
terface			
SB	USB 2.0	Ethornot Wi EUEE 000 445 /- /- Wi EUE	
etwork etwork Protocol	Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6	Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Dir	
etwork Printing Protocol	LPD, IPP (L5590 Only), PORT9100, WSD		
etwork Management Protocols		, APIPA, PING, DDNS, mDNS, SLP, WSD, LL	
lobile/Software and Cloud Printing			
Epson Connect Other Mobile Solutions	Epson iPrint, Epson Email Print, Remote Print	nt Driver	
ontrol Panel	Apple AirPrint, Mopria Print Service, Epson	oman Fallel	
	N/A	1.44" Colour LCD Panel	
JD Screen			
rinter Software oftware Support	Epson Photo+		
rinter Software oftware Support perating System Compatibility			
rinter Software oftware Support	Windows XP SP3 / XP Professional x64 SP2	2 / Vista / 7 / 8 / 8.1 / 10 / 11	
rinter Software oftware Support perating System Compatibility		/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS	Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications	Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency	Windows XP SP3 / XP Professional x64 SP2 Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage atted Frequency ower Consumption	Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or later Chrome OS ver. 89 or later	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz	/ 2019 / 2022	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W	r	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off loise Level	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W	// 2019 / 2022 r	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off oise Level C Printing / Premium Glossy Photo Paper	Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A),	/ 2019 / 2022 r 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A),	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage atted Frequency ower Consumption Operating Standby Sleep Power Off oise Level C Printing / Premium Glossy Photo Paper est Photo	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 41 / 41 dB(A)	/ 2019 / 2022 r 0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 40 / 40 dB(/	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage atted Frequency ower Consumption Operating Standby Sleep Power Off oise Level C Printing / Premium Glossy Photo Paper est Photo	Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A),	0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 40 / 40 dB(/) Sound Power (Black / Colour) 6.7 / 6.0 B(A)	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off Oise Level C Printing / Premium Glossy Photo Paper est Photo C Printing / Plain Paper Default'4	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 6.8 / 6.0 B(A), Sound Power (Black / Colour) 6.8 / 6.0 B(A),	0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Sound Power (Black / Colour) 6.7 / 6.0 B(A),	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off Oise Level C Printing / Premium Glossy Photo Paper est Photo C Printing / Plain Paper Default'4 pson Consumable lack Ink Bottle	Windows XP SP3 / XP Professional x64 SP/ Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 41 / 41 dB(A), Sound Pressure (Black / Colour) 55 / 47 dB(A), Sound Pressure (Black / Colour) 55 / 47 dB(A),	0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A) Sound Pressure (Black / Colour) 6.7 / 6.0 B(A) Sound Pressure (Black / Colour) 5.4 / 47 d(B), Sound Pressur	
rinter Software oftware Support perating System Compatibility Windows Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off olise Level C Printing / Premium Glossy Photo Paper est Photo C Printing / Plain Paper Default*4 pson Consumable lack Ink Bottle yan Ink Bottle	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 41 / 41 dB(A) Sound Pressure (Black / Colour) 55 / 47 dB(A) Page Yield* 4,300 pages	0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 40 / 40 dB(# Sound Pressure (Black / Colour) 5.7 (6.0 B(A), Sound Pressure (Black / Colour) 54 / 47 dB(# Order Code 003	
Mac Chrome OS lectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep	Windows XP SP3 / XP Professional x64 SP; Windows Server 2003 / 2008 / 2012 / 2016 Mac OS X 10.9.5 or later, macOS 11 or late Chrome OS ver. 89 or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 6.8 / 6.0 B(A), Sound Pressure (Black / Colour) 5.5 / 47 dB(A), Page Yield*	0.9 W Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 40 / 40 dB(A) Sound Power (Black / Colour) 6.7 / 6.0 B(A), Sound Pressure (Black / Colour) 5.4 / 47 dB(A) Order Code	

Dimensions & Weight

L3550 Weight: 4.1 kg





*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode. 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



- *2 When printed on Epson Premium Glossy Photo Paper.
- *3 Otherwise 3 mm top, left, right, bottom
- *4 Default mode in accordance with ISO7779 for MFPs.
- *5 Quoted yields are extrapolated based on Epson original Guoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of fink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower.

© 2023 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is a registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing

Printed August 2023