### **POINT-OF-SALE PRINTERS** TM-T88VI/T88VI-iHub





# **EMPOWER SERVICE WITH ADVANCED CONNECTIVITY.**

Epson's TM-T88VI offers fast print speeds and flexible connectivity that is vital in demanding environments. Equipped with state-of-the-art technology, the TM-T88VI allows you to enjoy the benefits of web and POS services while maintaining compatibility with existing applications or set-ups. Through connectivity features including cloud service and Near-Field Communication (NFC), efficiency is enhanced for excellent customer service. Experience greater cost-savings with low power consumption and advanced paper saving capabilities. In addition, the TM-T88VI's intelligent counterpart, TM-T88VI-iHub, offers peripheral support and control on top of similar wireless connectivity. Designed with details, grow your business with this series.







## IT'S IN THE DETAILS.

### **Cloud Accessibility**

Retrieve information and print directly from cloud without a separate connection platform.

#### **Flexible Connectivity**

Customise your set-up with versatile communication, \*triple interfaces and \*\*peripheral support. Pair your device instantly using NFC, QR code or iBeacon.

### **Eco-Efficient Business Operations**

Encourage a pro-environmental business setting with its industry-leading low power consumption capabilities and advanced paper-saving function.

Applicable for TM-T88VI only.
 \*Applicable for TM-T88VI-iHub only.
 Peripheral connection support applicable for TM-T88VI-iHub only.

### **SPECIFICATIONS** TM-T88VI/T88VI-iHub



Pint Kend      Troma Importing      Dimensions & Weight        Pint Fort      0.17/12 9:44      The Pint Fort        Colum Capacity      00.412 / 22 9:44      The Pint Fort        Columa Capacity      00.42 / 22 9:44      The Pint Fort        Consider Service Viel (1)      0.02 / 22 4:17 9:24      The Pint Fort        Consider Service Viel (1)      0.02 / 22 4:17 9:24      The Pint Fort        Consider Service Viel (1)      0.02 / 22 4:17 9:24      The Pint Fort        Data Buffer      Data USE (0) / 20 / 47 0:24      The Pint Fort        Data Buffer      Consider (2) / 20 / 27 / 20 / 20 / 27 / 20 / 20 / 27 / 20 / 20	MODEL NUMBER	TM-T88VI	TM-T88VI-iHub	
Prest      Turn Target      Turn Target <th< td=""><td></td><td></td><td></td><td>Dimensions &amp; Weight</td></th<>				Dimensions & Weight
Find  9.17/21/2 24  Wagner Argen: 1.03 (0.05 P)  Wagner Argen: 1.03 (0.05 P)    Chancic Se (0/ X/P)  D38 / 24 mm / 141 × 33 mm  Set (3/ 20 mm / 24 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34    Chancic Se (0/ X/P)  D38 / 24 mm / 141 × 33 mm  Set (3/ 20 mm / 24 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34    Defined Set (0/ X/P)  D41 / 124 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34    Defined Set (0/ X/P)  D41 / 104 × 104 mm / 24 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34  Set (3/ 20 mm / 24 × 1/7 x 34    Defined Set (0/ X/P)  D41 / 104 × 103 mm / 24 × 1/3 mm  Set (3/ 20 mm / 24 × 1/3 mm / 24				
Colum Copanity  Bd/ 2 calumning  The TBR VI-Hab  The TBR VI-Hab    Convarter Ser W1  DB/s 2 damma  Bd/statuments  The TBR VI-Hab    Convarter Ser W1  DB/s 2 damma  DB/s 2 damma  The TBR VI-Hab    Convarter Ser W1  DB/s 2 damma  DB/s 2 damma  DB/s    Convarter Ser W1  DB/s 2 damma  DB/s  DB/s  DB/s    Data Date  DB/s 2 damma  DB/s  DB/s  DB/s  DB/s    Data Date  DB/s		9 × 17 / 12 × 24		Weight: Approx. 1.6 kg (3.53 lb)
Owner Step (W x Hp)      Upg 1 2 4 mm (1 H = 3.30 mm)      Weight Appair 1.6 xg (5.5 H)        Consorts KM      B Achhurumet, L. J & xd (3 mg/b)ca      Immit a Mark (1000 mm)				TM-T88VI-iHub
Caracter Sincke    106 Aptimumere. 18 mem torum, 126 x 40 Graphes      Caracter Sincke    2 2 4/1 9 1 7 1 9 2 8/1      Interface    Bullen USB ()typ A for O'MUL22 (DM20)      Deb 10 ()    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Deta buller    Bullen USB ()typ A for O'MUL22 (DM20)      Work Organization    Bullen USB ()typ A for O'MUL22 (DM20)      Parte Backet    Byras or I KB, selectable      Work Organization    Bullen USB ()typ A for O'MUL22 (DM20)      Parte Backet    Bullen USB ()typ A for O'MUL22 (DM20)      Parte Backet    Bullen USB ()typ A for O'MUL22 (DM20)      Parte Machanization    Bullen USB ()typ A for O'MUL22 (DM20)      Parter Machanization    Bullen USB ()typ A for O'MUL22 (DM20)      Parter Machanization    Bord (BD2 + BUL)      Parter Machanization L/B    Brann 0 Ab      MUSP    Bord Backet      Parter Machanization L/B    Brann 0 Ab				Weight: Approx. 1.6 kg (3.53 lb)
Caracteris      12.8.24 / 9.17.7.8.24        Interface      Ballet USB (0) report (0.04 for DM-100) (M.0110 or other PCB Propriessile ) = MURIE (DBM-10.SBR HURIE STREM) = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE (DBM-10.SBR HURIE STREM) = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE (DBM-10.SBR HURIE STREM) = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE (DBM-10.SBR HURIE STREM) = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or Other PCB Propriessile ) = MURIE STREM = Source (CBM-100) (M.0110 or MURIE STREM = Source (CBM-100) (M.0110 or MURIE STREM = So				
Interface  Built 108 (Figs Akr of W102 or M0 007) DND 110 4 subter OF Type A kr of W102 or M0 007 DND 110 4 subter OF Septembal + Built- ND 007 (Figs R) + Built-in Ethernet + UB Serie All Set UB (Figs R) + Built-in Ethernet + Senie All Set UB (Figs R) + Built-in Ethernet + Senie All Set UB (Figs R) + Built-in Ethernet + Senie All Set UB (Figs R) + Built-in Ethernet + Senie All Set DS Perginal) + USB Charging Port (D SA 2:14)  If all mm    Data Buffer Receive User-Saferad  45 bytes or 4 KB, selectable User-Saferad  45 bytes or 4 KB, selectable User-Saferad				
DM 0110 + Buin IUSR (Dipp B) + Buih = Ehmerning Link (DS Driphonski) + USB inter (DS Briphonski)			Ruitt in LISE (2 * Type A for OT W/LO2 DM D20 /	
Receive    45 bytes of 4 KB, selectable    19 mm    19 mm    14 mm      Macro    2 KB    10 mm    10 mm <t< td=""><td>Interface</td><td>DM-D110) + Built-in USB (Type B) + Built-in Ethernet</td><td>DM-D110 or other POS Peripherals) + Built-in USB (Type B) + Built-in Ethernet + Serial (POS Peripheral)</td><td>148 mm</td></t<>	Interface	DM-D110) + Built-in USB (Type B) + Built-in Ethernet	DM-D110 or other POS Peripherals) + Built-in USB (Type B) + Built-in Ethernet + Serial (POS Peripheral)	148 mm
User-defined  12 kB    Macro  2 kB    Macro  2 kB    Worphics  384 kB    NV User  1 kB    Print Speed  Max: 850 mm/vsoc.    Dot Density  180 x 180 dpir    Paper	Data Buffer		·	
User-defined    12.48      Workprise    32.48      WOrkprise    33.41/8      WUrkprise    14.8      Print Speed    Max 500 mm/see.      Dat Density    18.01.60 d/r      Paper	Receive	45 bytes or 4 KB, selectable		
NV Graphica  364 KB    NV User  1 KB    NV User  1 KB    NV User  1 KB    Phint Speed  Mix. s30 mr/sec.    Dot Density  190 x 180 dpl'    Paper	User-defined	12 KB		145 mm
NV Liser  1 KB    Print Speed  Max. 358 0m/lisee.    Dot Density  180 x 180 dpr <sup>2</sup> Paper	Macro	2 KB		
Print Speed  Max. 350 mm/sec.  150 × 180 dp²    Paper  79 ± 0.5 mm × 88.0 / 57.5 ± 0.5 × 83.0 mm  148 mm    Widh x Diameter  79.5 ± 0.5 mm × 88.0 / 57.5 ± 0.5 × 83.0 mm  195 mm    Prince Maximum  0.048 mm to 0.08 mm  195 mm    Supply Vidinga  DC +24 V ± 7%  Power Saving    Power Supply  P5-180  Approx. 27.4 W    Power Supply  P5-180  Adapter V    Reliability  Printer Mechanism Life  20 million lines    Auto Cutret Life  3 million cuts  350,000 hours    MC2F  70 million lines  20 million lines    Colour  Back (EBCK), White (EN48.5)  Elstex (EBCK)    Overall Diamesions (W x D x H)  L45 x 196 x 148 mm  400 cutret Life    Mass  Approx. 16 kg  EM    Mass  Approx. 16 kg  EM    Minder Diagon 10 (cutret Life)  OT-WL02 (ELPAP110)    Cuterend Diagon  Printer Software    Device Contol Software  ESO/POS, ePOS-Print XML, ePOS-SOK    Web Sarwar  Bigttpd/a/phybis@lta3    Printer Software	NV Graphics	384 KB		(
Print Speed  Mex. 350 mm/sec.  148 nm    Dat Density  160 x 180 dp*    Paper  79 ± 0.5 mm x 88.0 / 57.5 ± 0.5 x 83.0 mm    Trickness  0.048 mm to 0.08 mm    Power Saving  0.244 V ± 7%    Power Supply  P5 ± 10.5 mm x 88.0 / 57.5 ± 0.5 x 83.0 mm    Power Supply  P5 ± 10.5 mm x 88.0 / 57.5 ± 0.5 x 83.0 mm    Power Supply  P5 ± 10.0 mm x 80.0 / 57.5 ± 0.5 x 83.0 mm    Power Supply  P5 ± 10.0 mm x 80.0 / 57.5 ± 0.5 x 83.0 mm    Power Supply  P5 ± 10.0 mm x 80.0 / 57.5 ± 0.5 x 83.0 mm    Printer Mechanism Life  20 million lines    Auto Cutre Life  3 million cuts    MTBF  300.000 hours    Golar  Black (EBCK), White (ENN8.5)    Deard Black (EBCK), White (ENN8.5)  Black (EBCK)    Overall Dimensione (W x D x H)  H4 5 mm    Mass  Approx.16 kg    EMI  F0 - 10.5 A (222 N 0.00050-1)    Option  Ottal 200 - 10.5 A (222 N 0.00050-1)    Printer Mardware  CPU    CPU  APM Contex-AS 384 MHz    Web Source I black and ther DOR, Wrindows Diver (APD), OPOS, POS, POS, NET, JavaPOS (Windows), JavaPOS (Linux), More and are to town and or the stream and or the market on	NV User	1 KB		· · · · · · · · · · · · · · · · · · ·
Paper    79.5 ± 0.5 mm × 83.0 / 57.5 ± 0.5 × 83.0 mm      Width X Diameter    79.5 ± 0.5 mm × 83.0 / 57.5 ± 0.5 × 83.0 mm      Thickness    0.048 mm to 0.08 mm      Power Saving    DC + 24 V ± 7%.      Power Consumption    Approx. 27.6 W      Power Supply    PG-180      Reliability    Printer Mechanism Life      Printer Mechanism Life    20 million cats      Auto Cutter Life    3 million cats      MTBF    360,000 hours      Goldum    Black (EBCK), White (ENN8.5)      Black (EBCK)    Black (EBCK)      Overall Dimensions (W X D x H)    145 x 195 x 148 mm      Ass    Approx. 1.6 kg      EMI    CPC Class A, ICSE-003 Class A      Safety Standard    U.60650-1/CSA C2.2 No 60560-1      Option    Or FR220      Printer Medware    GPU      CPU    AIM Cortex-A5 384 MH2      Box Or Disolware    BSC/POS, ePOS-print XML, ePOS-SDK      Web Sorver    Bipttpd/php/agita3      Printer Differ    BOMB      Diver der Vinital Post Diver, UMS Diver (PPD), OPOS, OPOS.NETF, JavaPOS (Mindows), JavaPOS (Linux), mergater at the tadmarks or registered mergater at com as a multimorat register diverse and cot file coccording. Ep	Print Speed			148 mm
Width x Diameter      79.5 ± 0.5 m x 83.0 / 57.5 ± 0.5 x 83.0 mm        Trickness      0.048 mm to 0.08 mm        Power Saing      190 mm        Supply Voltage      DC + 24 V ± 7 %        Power Sonsumption      Approx. 27.6 W      Approx. 27.4 W        Power Sonsumption      Approx. 27.8 W      Approx. 27.6 W      Approx. 27.6 W        Reliability      Printer Mechanism Life      300.000 hours      350.000 hours      350.000 hours        Add Cutter Life      3 million cuts      300.000 hours      350.000 hours      350.000 hours        Order      Black (EBCK), White (ENN8.5)      Black (EBCK)      Black (EBCK)      Black (EBCK)        Order      Black (EBCK), White (ENN8.5)      Black (EBCK)      Black (EBCK)        Order      Black (EBCK), White (ENN8.5)      Black (EBCK)      Black (EBCK)        Order      Us0595 - ICSA C22.2 No.60550-1      Order      Black (EBCK)      Black (EBCK)        Writess LAN      OFW-L02 (ELPAP10)      Cuters      Cuters      Cuters      Black (EBCK)        Weide Gontrot Software      EGC/POS, ePOS Print XML, ePOS-SOK      Post and the viter post and	Dot Density	180 × 180 dpi*		
Thickness    0.048 mm to 0.08 mm    105 mm      Power Saving    C + 24 V ± 7%    115 mm    115 mm      Power Consumption    Approx. 27.8 W    Approx. 27.4 W    Approx. 27.4 W      Power Consumption    Approx. 27.8 W    Adapter V      Reliability    Printer Mechanism Life    20 million lines    4dapter V      Auto Cutter Life    3 million cuts    350,000 hours    350,000 hours      MCBF    70 million lines    20 million lines    4prox. 1.6 kg      Colour    Back (EBCK), White (ENNR.5.)    Black (EBCK)    4prox. 1.6 kg      EMI    FCC Class A, LOES-003 Class A    Safety Standard    5pros. 1.6 kg      EMI    FCC Class A, LOES-003 Class A    Safety Standard    2018 Epson Singapore Pet Lit.4 Rights Reserved.      Option    -    -    -    -    -      Phinter Hardware    OT-WL02 (ELPAP10)    -    -    -    -      Customer Display Unit    DM-D30, DM-D110    -    -    -    -      Printer Hardware    CP/OS, ePOS, ePOS, Print XML_ ePOS:SDK    rd Sek Epson Compation. A other products imms of Sek Epson. Singapore Pet Lit.4 Rights Reserved.    -      Meb	Paper			*
Power Saving      Item methods and the second secon	Width x Diameter	79.5 ± 0.5 mm × 83.0 / 57.5 ± 0.5 × 83.0 mm		p
Power Saving      C + 24 V ± 7%      115 mm        Supply Voltage      DC + 24 V ± 7%        115 mm      115 mm        Supply Voltage      DC + 24 V ± 7%         115 mm      11	Thickness	0.048 mm to 0.08 mm		195 mm
Power Consumption      Approx. 27.6 W      Approx. 27.4 W        Power Supply      PS-180      Adapter V        Reliability      Printer Mechanism Life      20 million lines        Auto Cutter Life      3 million cuts      Statument of the st	Power Saving			
Power Consumption      Approx. 27.6 W      Approx. 27.4 W        Power Supply      PS-180      Adapter V        Reliability      Printer Machanism Life      20 million lines        Auto Cutter Life      3 million outs      S00,000 hours        MTBF      360,000 hours      350,000 hours        MCBF      70 million lines      S00,000 hours        Colour      Black (EBCK), White (ENN8.5)      Black (EBCK)        Overall Dimensions (W x D x H)      145 x 195 x 148 mm        Mass      Pprox.15.6 kg        EM      FCC Class A, ICES-003 Class A        Safety Standard      UL060950-100 Class A        Option      Printer Software        OPL      Castomer Display Unit      DM-D30, DM-D110        Wall Hanging Unit      WH-10      _        EVel Control Memory      30 MB      100 MB        Printer Software      ESC/POS, ePOS-Print XML, ePOS-SDK      Partial Charge Pie Lid All Pghts Reserved. Printer Otiver        Web Sorter Memory      Bighttpd/php/sightleg83      POS-Print XML, ePOS-SDK      Printer Software endation in get or in whole, without the written permoses in the products names and of the respective or write. Printer Software endatenter or write write write write andaten area or writ	Supply Voltage	DC +24 V ± 7%		
Reliability      Printer Machanism Life    20 million lines      Auto Cutter Life    3 million cuts      MTBF    360,000 hours      MCBF    70 million lines      Colour    Black (EBCK)      Overall Dimensions (W x D x H)    145 x 195 x 148 mm      Mass    Approx. 1.6 kg      EMI    FCC Class A, ICES-003 Class A      Safety Standard    UL60900-1/CSA C22.2 No.60030-13      Option    Ul60900-1/CSA C22.2 No.60030-13      Wireless LAN    OT-WL02 (ELPAP10)      Customer Display Unit    DM-D30, DM-D110      Wirel Autor Market    OT-B220      Printer Hardware    OPL      CPU    AMC Cortex-A5 384 MHz      Web Control Maren    So MB      Printer Software    ESC/POS, ePOS-Print XML, ePOS-SDIK      Web Server    Ighttpd/iph/sglit63      Printer Oniver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS, NET, JavaPOS (Kindows), JavaPOS (Linux), Fits angles shown are aimlations ori, Specification and ard other production anares. Print angles othor area area. Third Print Assistant		Approx. 27.6 W	Approx. 27.4 W	
Reliability  Constraints  Constraints    Printer Machanism Life  20 million lines    Auto Cutter Life  3 million cuts    MTBF  360,000 hours    Sector  70 million lines    Colour  Black (EBCK)    Overall Dimensions (W x D x H)  145 x 195 x 148 mm    Mass  Approx. 1.6 kg    EMI  FCC Class A, ICES-003 Class A    Safety Standard  UL60950-11/CSA C22.2 No.60950-1    Option  Other Display Unit    Wireless LAN  OT-WL02 (ELPAP10)    Customer Display Unit  DM-D30, DM-D110    Wireless LAN  OT-WL02 (ELPAP10)    Customer Display Unit  DM-D30, DM-D110    Wireless LAN  OT-B320    Printer Hardware  CPU    QPU  APM Contex-A5 384 MHz    Web Content Memory  30 MB    Printer Software  ESC/POS, ePOS-Print XML, ePOS-SDK    Web Server  Ighttpd/iph/sglit83    Printer Driver  ePOS-Print XML, ePOS-SDK    Web Sorver  Ighttpd/iph/sglit83    Printer Driver  ePOS-Print XML, de DDS-Nerr, LlavaPOS (Windows), JavaPOS (Linux), TM Yrint Assistant    Utility  TM-Yrint Assistant	Power Supply	PS-180	Adapter V	
Printer Mechanism Life    20 million tuts      Auto Cuter Life    3 million cuts      MTBF    360,000 hours      MCBF    70 million lines      Colour    Black (EBCK), White (ENN8.5)    Black (EBCK)      Overall Dimensions (W x D x H)    145 x 195 x 149 mm      Mass    Approx. 1.6 kg      EMI    FCC Class A, ICES-003 Class A      Safety Standard    U.60950-1/CSA C22.2 No.60950-1      Orture    Class A      Vireless LAN    OT-WL02 (ELPAP10)      Customer Display Unit    MH-10      Vireless LAN    OT-WL02 (ELPAP10)      Customer Display Unit    MH-10      Vireless LAN    OT-WL02 (ELPAP10)      Vireless Control Software    OT-WL02 (ELPAP10)      Vireless Control Software    OT-WL02 (ELPAP10)      Vireless Control Software    Software      Printer Software    Software      Bevice Control Software    Softwa			·	
MTBF  360,000 hours  350,000 hours    MCBF  70 million lines    Colour  Black (EBCK), White (ENN8.5)  Black (EBCK)    Overall Dimensions (W x D x H)  145 x 195 x 148 mm    Mass  Approx. 1.6 kg    EMI  FCC Class A, ICES-003 Class A    Safety Standard  UL60950-17CSA C22.2 No.60950-1    Option  Wrieless LAN    OT-WL02 (ELPAP10)	Printer Mechanism Life	20 million lines		
MCBF  70 million lines    Colour  Black (EBCK), White (ENN8.5)  Black (EBCK)    Overall Dimensions (W x D x H)  145 x 195 x 148 mm    Mass  Approx. 1.6 kg    EMI  FOC Class A, ICES-003 Class A    Safety Standard  UL60950-1/CSA C22.2 No.60950-1    Option  UL60950-1/CSA C22.2 No.60950-1    Wireless LAN  OT-WL02 (ELPAP10)    Customer Display Unit  DM-D30, DM-D110    Wall Hanging Unit  WH-10    External Buzzer  OT-BZ20    Printer Hardware  CPU    Quice Control Software  ESC/POS, ePOS-Print XML, ePOS-SDK    Web Server  Ightpd/php/sglite3    Printer Diver  ESC/POS, ePOS-Print XML, ePOS-SDK    Web Server  Ightpd/php/sglite3    Printer Diver  ESC/POS, ePOS-Print XML, ePOS-SDK    Utility  TM-T88/U Utility, (TM Utility (OS/Android), EpsonNet Config, EpsonNet Config (Web version: for networks setting and and refor company neare subject to change without nearesinate for in definition puppose only, and all finits in those marks. Epson disclams any and all rights in those marks. Epson disclams any and all rights in those marks.	Auto Cutter Life	3 million cuts		
MCBF  70 million lines    Colour  Black (EBCK), White (ENN8.5)  Black (EBCK)    Overall Dimensions (W x D x H)  145 x 195 x 148 mm    Mass  Approx. 1.6 kg    EMI  FOC Class A, ICES-003 Class A    Safety Standard  UL60950-1/CSA C22.2 No.60950-1    Option  UL60950-1/CSA C22.2 No.60950-1    Wireless LAN  OT-WL02 (ELPAP10)    Customer Display Unit  DM-D30, DM-D110    Wall Hanging Unit  WH-10    External Buzzer  OT-BZ20    Printer Hardware  CPU    Quice Control Software  ESC/POS, ePOS-Print XML, ePOS-SDK    Web Server  Ightpd/php/sglite3    Printer Diver  ESC/POS, ePOS-Print XML, ePOS-SDK    Web Server  Ightpd/php/sglite3    Printer Diver  ESC/POS, ePOS-Print XML, ePOS-SDK    Utility  TM-T88/U Utility, (TM Utility (OS/Android), EpsonNet Config, EpsonNet Config (Web version: for networks setting and and refor company neare subject to change without nearesinate for in definition puppose only, and all finits in those marks. Epson disclams any and all rights in those marks. Epson disclams any and all rights in those marks.			350,000 hours	
Overall Dimensions (W x D x H)    145 x 195 x 148 mm      Mass    Approx. 1.6 kg      EMI    FCC Class A, ICES-003 Class A      Safety Standard    UL60950-1/CSA C22.2 No.60950-1      Option    Wrieless LAN      Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10      External Buzzer    OT-BZ20      Printer Hardware    CPU      QPU    AFM Cortex-A5 384 MHz      Web Content Memory    30 MB      Printer Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Device Control Software    ESC/POS, ePOS-Print XML, ePOS, SDK      Printer Driver    EOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      Utility    TM-7ra8VI Utility, TM Utility (IOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network stripting and and update striptinges check with out the secret check with coal Epse check	MCBF		· ·	
Overall Dimensions (W x D x H)    145 x 195 x 148 mm      Mass    Approx. 1.6 kg      EMI    FCC Class A, ICES-003 Class A      Safety Standard    UL60950-1/CSA C22.2 No.60950-1      Option    Wireless LAN      Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10      External Buzzer    OT-EZ20      Printer Hardware    CPU      QPU    AFM Cortex-A5 384 MHz      Web Content Memory    30 MB      Printer Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Device Control Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Velt Server    Ighttpd//ph/s/stilte3      Printer Driver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      Utility    TM-7ra8VI Utility, TM Utility (IOS/Android), EpsonNet Config. EpsonNet Config (Web version: for network stripting and and rule and and way between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please check without note and may any between countries. Please che	Colour	Black (EBCK), White (ENN8,5)	Black (EBCK)	
Mass    Approx. 1.6 kg      EMI    FCC Class A, ICES-003 Class A      Safety Standard    UL60950-1/CSA C22.2 No.60950-1      Option       Wireless LAN    OT-WL02 (ELPAP10)      Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10      External Buzzer    OT-BZ20      Printer Hardware    CPU      CPU    ARM Cortex-A5 384 MHz      Web Content Memory    30 MB      Printer Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Device Control Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Printer Driver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Utility, TM Utility (IOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting)      TM Print Assistant    TM Print Assistant	Overall Dimensions (W x D x H)			
EMI    FCC Class A, ICES-003 Class A      Safety Standard    UL60950-1/CSA C22.2 No.60950-1      Option				
Safety Standard    UL60950-1/CSA C22.2 No.60950-1      Option    OT-WL02 (ELPAP10)      Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10      External Buzzer    OT-BZ20      Printer Hardware    CPU      QPU    ARM Cortex-A5 384 MHz      Web Content Memory    30 MB      Povice Control Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Device Control Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Veb Server    Ighttpd/php/sqlite3      Printer Driver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Vritual Port Driver, CUPS Driver (Linux), Mac Driver      Utility    TM-Tra8VI Utility, TM Utility (IOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting)      TM Print Assistant    TM Printassistant	EMI			
Wireless LAN    OT-WL02 (ELPAP10)      Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10      External Buzzer    OT-BZ20      Printer Hardware    CPU      CPU    ARM Cortex-A5 384 MHz      Web Content Memory    30 MB      30 MB    100 MB      Printer Software    Sc/POS, ePOS-Print XML, ePOS-SDK      Device Control Software    ESC/POS, ePOS-Print XML, ePOS-SDK      Web Server    Ighttpd/php/sqlite3      Printer Driver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      Utility    TM-T88VI Utility, TM Utility (IOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting) TM Print Assistant	Safety Standard			
Customer Display Unit    DM-D30, DM-D110      Wall Hanging Unit    WH-10    -      External Buzzer    OT-BZ20      Printer Hardware    CPU    ARM Cortex-A5 384 MHz    © 2018 Epson Singapore Pte Ltd. All Rights Reserved.      Web Content Memory    30 MB    100 MB    Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Selko Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks or registered trademarks or registered trademarks or registered trademarks or registered trademarks of selko Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks or registered trademarks of selko Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks or registered trademarks of selko Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks or registered trademarks of selko Epson Corporation. All other products names and exception of the respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Option			
Wall Hanging Unit    WH-10    -      External Buzzer    OT-BZ20      Printer Hardware    CPU    ARM Cortex-A5 384 MHz    © 2018 Epson Singapore Pte Ltd. All Rights Reserved.      Web Content Memory    30 MB    100 MB    Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Selks Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks of selks Epson Corporation. All other products names and eXCEED YOUR VISION are registered trademarks of selks Epson Corporation. All other products names and excert endemarks or registered trademarks of selks Epson Corporation. All other products names and other company names used herein are for lidentification purposes only and are the trademarks of selks Epson Corporation. All other products names and other company names used herein are for lidentification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclams any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Wireless LAN	OT-WL02 (ELPAP10)		
External Buzzer    OT-BZ20      Printer Hardware    © 2018 Epson Singapore Pte Ltd. All Rights Reserved.      CPU    ARM Cortex-A5 384 MHz    © 2018 Epson Singapore Pte Ltd. All Rights Reserved.      Web Content Memory    30 MB    100 MB    Permission from Epson, is strictly prohibide. IPSON and EXCEED YOUR VISION are registered trademarks of Selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson discist of their respective owners. Epson discist of their respective owners. Epson discist on and and and and the trademarks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Customer Display Unit	DM-D30, DM-D110		
Printer Hardware      © 2018 Epson Singapore Pte Ltd. All Rights Reserved.        CPU      ARM Cortex-A5 384 MHz      © 2018 Epson Singapore Pte Ltd. All Rights Reserved.        Web Content Memory      30 MB      100 MB      Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED VOLIV VISION are registered trademarks of Selko Epson Corporation. All other products names and other company names used herein are for lidentification purposes only and are the trademarks or registered trademarks of their respective owners.        Web Server      Iighttpd/php/sqlite3      Iidentification purposes only and are the trademarks or registered trademarks of their respective owners.        Printer Driver      ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Wall Hanging Unit	WH-10	-	
CPU  ARM Cortex-A5 384 MHz  © 2018 Epson Singapore Pte Ltd. All Rights Reserved.    Web Content Memory  30 MB  100 MB  Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEPD YOUR VISION are registered trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION are registered trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION and are the trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION and are the trademarks of selice trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice trademarks of selice trademarks of selice trademarks of selice trademarks of their respective owners. Epson disclaims any and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Thirt samples Shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	External Buzzer	OT-BZ20		
CPU  ARM Cortex-A5 384 MHz  © 2018 Epson Singapore Pte Ltd. All Rights Reserved.    Web Content Memory  30 MB  100 MB  Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEPD YOUR VISION are registered trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION are registered trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION and are the trademarks of Selice Epson Corporation. All other products names and EXCEED YOUR VISION and are the trademarks of selice trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice Epson Corporation. All other products names and excert trademarks of selice trademarks of selice trademarks of selice trademarks of selice trademarks of their respective owners. Epson disclaims any and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Thirt samples Shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Printer Hardware			
Web Content Memory      30 MB      100 MB      permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Selko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks.        Printer Driver      ESC/POS, ePOS-Print XML, ePOS-SDK      and Other company names used herein are for identification purposes only and are the trademarks.        Printer Driver      ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      printer Software Senter structure and their company names used herein are for identification purposes only and are the trademarks.        Utility      TM-TR8VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting TM Print Assistant      Print amples shown are simulations only. Specifications and and product valiability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.		ARM Cortex-A5 384 MHz		
Printer Software  and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used harein are for identification purposes only and are the trademarks or registered trademarks of seiko Epson Corporation. All other products names and other company names used harein are for identification purposes only and are the trademarks or registered trademarks or	Web Content Memory	30 MB	100 MB	
Device Control Software      ESC/POS, ePOS-Print XML, ePOS-SDK      and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epon disclaims any and all rights in those marks.        Printer Driver      ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epon disclaims any and all rights in those marks.        Utility      TM-T88VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting) TM Print Assistant      and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all girbs in those marks.	Printer Software		·	
Web Server      lighttpd/php/sqlite3      and other company name to registered trademarks of their respective owners.        Printer Driver      ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver      or registered trademarks of their respective owners.        Utility      TM-T88VI Utility, (TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting) TM Print Assistant      or not information.	Device Control Software	ESC/POS, ePOS-Print XML, ePOS-SDK		
Printer Driver    ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Windows), JavaPOS (Linux),    or registered trademarks of their respective owners.      TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver    TM-788VI Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting)    or registered trademarks of their respective owners.      Utility    TM-788VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting)    and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices form ore information.				
TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver    Epson disclaims any and all rights in those marks.      Utility    TM-T88VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting TM Print Assistant    Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.	Printer Driver			or registered trademarks of their respective owners.
Utility    TM-788VI Utility, TM Utility (iOS/Android), EpsonNet Config, EpsonNet Config (Web version: for network setting)    and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.				
with local Epson offices for more information.	Utility			and product availability are subject to change without notice and may vary between countries. Please check
	Easy Setting	Easy pairing with NFC, QR Code, iBeacon**		with local Epson offices for more information.

\*dots per 25.4mm (dots per inch) \*\*specific iBeacon dongle is required (BT820)

Information correct at time of printing Printed August 2018

Dealer's Stamp

Sales Enquiries 800 120 5564



Epson Singapore Pte Ltd 1 Harbourfront Place, #03-02 HarbourFront Tower One, Singapore 098633. Tel: (65) 6586-5500 Fax: (65) 6271-9755 Epson Customer Care Centre 108, Pasir Panjang Road, #04-08 Golden Agri Plaza, Singapore 118535. Epson Helpdesk: 800 120 5564. Operating hours: Monday – Friday, 9am – 6pm, Saturday, 9am – 1pm. Closed on Sunday and Public Holiday.