



# Enhance Your Business Operations with a Versatile Multifunction POS Printing Solution.

The Epson TM-H6000VI multifunction POS printer excels in both receipt printing and check processing. With an upgraded printing speed of up to 500 mm/s\*, it delivers reliable performance, featuring a durable print head and an extended auto cutter life. It also supports multiple interfaces and connectivity options for seamless integration. The newly added support for UTF-8 font\* makes it easy to switch between and print multiple languages. Additionally, the printer offers up to 49%^ more paper savings compared to conventional receipt printer models.







Auto Cutter



Multiple Connectivity



Cost Effective



Multiple Languages Support



es Reliable Performance



# ENGINEERED FOR GOOD

### Improved Efficiency

The TM-H6000VI boosts productivity with printing speeds up to 500 mm/s\* and quick cheque processing with speed of up to 5.70 lps.

#### Reliable Performance

This reliable thermal printer is designed to minimise downtime, capable of printing up to 200 km of receipts and enduring over three million cuts with its durable auto-cutter\*.

#### Versatile Connectivity

Connect via USB, Ethernet, Serial, Parallel or optional Wi-Fi dongle, while maintaining compatibility with legacy POS systems.

#### **SPECIFICATIONS**

Print Method	MODEL NUMBER	TM-H6000VI
Slip   9-Pin Serial Impact Dot Matrix	Print Method	
Print Font Font ANK + Traditional Chinese (Big 5) + UTF-8 [receipt only] Character Set 95 Alphanumeric, 18 Set International, 128 x 12 Graphic Character Size (W x H) Receipt: 1.41 x 3.39 mm / 0.99 x 2.4 mm Slip: 1.56 x 3.11 mm / 1.24 x 3.11 mm Endorsement (Slip): 1.09 x 2.41 mm  Column Capacity (Slip) 45 cps / 60 cps Endorsement Print Yes (selected models only) Magnetic Ink Character Recognition Paper Copy Capacity (Slip) Original + 2 Copies  Print Sped Receipt 500 mm/s Slip 5.70 lps (40 columns, 17.80 cpi) Endorsement 4.0 lps Dot Density 180 dpi x 180 dpi Reliability Printer Head Life Auto Cutter Life 3 million cuts (Thermal receipt only) Feature Near Field Communication (NFC) Greyscale Printing Yes Paper Saving Function Yes Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle Power Consumption Operating Approx. 26.6 W	Receipt	Thermal Line Printing
Pont	Slip	9-Pin Serial Impact Dot Matrix
Character Set 95 Alphanumeric, 18 Set International, 128 x 12 Graphic Character Size (W x H) Receipt: 1.41 x 3.39 mm / 0.99 x 2.4 mm Slip: 1.56 x 3.11 mm / 1.24 x 3.11 mm Endorsement (Slip): 1.09 x 2.41 mm  Column Capacity (Slip) 45 cps / 60 cps Endorsement Print Yes (selected models only)  Magnetic Ink Character Recognition Paper Copy Capacity (Slip) Original + 2 Copies  Print Speed Receipt 500 mm/s Slip 5.70 lps (40 columns, 17.80 cpi) Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi Reliability  Printer Head Life 200 km Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature Near Field Communication (NFC) Yes Greyscale Printing Yes Paper Saving Function Yes Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Print Font	
Character Size (W x H) Receipt: 1.41 x 3.39 mm / 0.99 x 2.4 mm Slip: 1.56 x 3.11 mm / 1.24 x 3.11 mm Endorsement (Slip): 1.09 x 2.41 mm  Column Capacity (Slip) 45 cps / 60 cps Endorsement Print Ves (selected models only)  Magnetic Ink Character Recognition  Paper Copy Capacity (Slip) Original + 2 Copies  Print Speed Receipt 500 mm/s Slip 5.70 lps (40 columns, 17.80 cpi) Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi Reliability  Printer Head Life 200 km Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature Near Field Communication (NFC) Greyscale Printing Yes Paper Saving Function Yes Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle Power Consumption Operating Approx. 26.6 W	Font	ANK + Traditional Chinese (Big 5) + UTF-8 [receipt only]
Slip: 1.56 x 3.11 mm / 1.24 x 3.11 mm Endorsement (Slip): 1.09 x 2.41 mm  Column Capacity (Slip) 45 cps / 60 cps Endorsement Print Yes (selected models only)  Magnetic Ink Character Recognition  Paper Copy Capacity (Slip) Original + 2 Copies  Print Speed Receipt 500 mm/s Slip 5.70 lps (40 columns, 17.80 cpi) Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes Greyscale Printing Yes Paper Saving Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Character Set	95 Alphanumeric, 18 Set International, 128 x 12 Graphic
Endorsement (Slip): 1.09 x 2.41 mm  Column Capacity (Slip) 45 cps / 60 cps  Endorsement Print Yes (selected models only)  Magnetic Ink Character Recognition  Paper  Copy Capacity (Slip) Original + 2 Copies  Print Speed  Receipt 500 mm/s  Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Server Direct Print  Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating Approx. 26.6 W	Character Size (W x H)	Receipt: 1.41 x 3.39 mm / 0.99 x 2.4 mm
Column Capacity (Slip)  Endorsement Print Yes (selected models only)  Magnetic Ink Character Recognition  Paper  Copy Capacity (Slip) Original + 2 Copies  Print Speed  Receipt 500 mm/s  Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print Supported Application  Power Consumption Operating Approx. 26.6 W		Slip: 1.56 x 3.11 mm / 1.24 x 3.11 mm
Endorsement Print Yes (selected models only)  Magnetic Ink Character Recognition Yes (selected models only)  Paper  Copy Capacity (Slip) Original + 2 Copies  Print Speed  Receipt 500 mm/s  Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W		Endorsement (Slip): 1.09 x 2.41 mm
Magnetic Ink Character Recognition  Paper Copy Capacity (Slip) Original + 2 Copies  Print Speed Receipt So0 mm/s Slip 5.70 Ips (40 columns, 17.80 cpi) Endorsement 4.0 Ips Dot Density 180 dpi x 180 dpi Reliability Printer Head Life Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature Near Field Communication (NFC) Greyscale Printing Yes Paper Saving Function Supported Application EPOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Column Capacity (Slip)	45 cps / 60 cps
Paper Copy Capacity (Slip) Original + 2 Copies  Print Speed Receipt 500 mm/s Slip 5.70 lps (40 columns, 17.80 cpi) Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability Printer Head Life Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature Near Field Communication (NFC) Greyscale Printing Yes Paper Saving Function Supported Application Server Direct Print Supported Application Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Endorsement Print	Yes (selected models only)
Copy Capacity (Slip)  Print Speed  Receipt  500 mm/s  Slip  5.70 lps (40 columns, 17.80 cpi)  Endorsement  4.0 lps  Dot Density  Reliability  Printer Head Life Auto Cutter Life  3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC)  Greyscale Printing  Yes  Paper Saving Function  Built-in Cloud Function  Server Direct Print  Supported Application  Interface  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating  Approx. 26.6 W	Magnetic Ink Character Recognition	Yes (selected models only)
Print Speed  Receipt 500 mm/s  Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Paper	
Receipt 500 mm/s  Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print  Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating Approx. 26.6 W	Copy Capacity (Slip)	Original + 2 Copies
Slip 5.70 lps (40 columns, 17.80 cpi)  Endorsement 4.0 lps  Dot Density 180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print  Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating Approx. 26.6 W	Print Speed	
Endorsement  4.0 lps  180 dpi x 180 dpi  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Greyscale Printing Yes  Paper Saving Function Built-in Cloud Function Server Direct Print Supported Application Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Receipt	500 mm/s
Dot Density  Reliability  Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print  Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating Approx. 26.6 W	Slip	5.70 lps (40 columns, 17.80 cpi)
Reliability Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature Near Field Communication (NFC) Yes Greyscale Printing Yes Paper Saving Function Yes Built-in Cloud Function Server Direct Print Supported Application ePOS Print XML, ePOS SDK Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Endorsement	4.0 lps
Printer Head Life 200 km  Auto Cutter Life 3 million cuts (Thermal receipt only)  Feature  Near Field Communication (NFC) Yes  Greyscale Printing Yes  Paper Saving Function Yes  Built-in Cloud Function Server Direct Print  Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating Approx. 26.6 W	Dot Density	180 dpi x 180 dpi
Auto Cutter Life  Feature  Near Field Communication (NFC)  Greyscale Printing  Paper Saving Function  Built-in Cloud Function  Supported Application  Interface  Power Consumption  Operating  Amillion cuts (Thermal receipt only)  Yes  Yes  Server Direct Print  ePOS Print XML, ePOS SDK  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Approx. 26.6 W	Reliability	
Near Field Communication (NFC) Greyscale Printing Paper Saving Function Built-in Cloud Function Supported Application Interface Power Consumption Operating  Yes  Yes  Yes  Yes  Yes  Yes  Yes  Ye	Printer Head Life	200 km
Near Field Communication (NFC)  Greyscale Printing  Paper Saving Function  Built-in Cloud Function  Server Direct Print  ePOS Print XML, ePOS SDK  Interface  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating  Approx. 26.6 W	Auto Cutter Life	3 million cuts (Thermal receipt only)
Greyscale Printing  Yes  Paper Saving Function  Built-in Cloud Function  Server Direct Print  ePOS Print XML, ePOS SDK  Interface  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption  Operating  Approx. 26.6 W	Feature	
Paper Saving Function  Built-in Cloud Function  Supported Application  Interface  Power Consumption  Operating  Yes  Server Direct Print  ePOS Print XML, ePOS SDK  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Approx. 26.6 W	Near Field Communication (NFC)	Yes
Built-in Cloud Function Supported Application  Power Consumption Operating  Server Direct Print  ePOS Print XML, ePOS SDK  Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Approx. 26.6 W	Greyscale Printing	Yes
Supported Application ePOS Print XML, ePOS SDK  Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Paper Saving Function	Yes
Interface Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle  Power Consumption Operating Approx. 26.6 W	Built-in Cloud Function	Server Direct Print
Power Consumption Operating Approx. 26.6 W	Supported Application	ePOS Print XML, ePOS SDK
Operating Approx. 26.6 W	Interface	Built-in USB, Ethernet, Optional Serial, Parallel and Wi-Fi Dongle
	Power Consumption	
Standby Approx. 1.0 W	Operating	Approx. 26.6 W
	Standby	Approx. 1.0 W

Standby: 55 db (A)

#### **Dimensions & Weight**

Weight: Approx. 4.4kg Colour: Black



Weight: Approx. 4.4kg Colour: White



#### Legend

CPI: Characters Per Inch LPS: Lines Per Second

## What's In The Box

Setup Guide Roll Paper Connector Cover Power Switch Cover Power Supply PS-190

Epson ERC-(32B) Ribbon Cartridge, Black

# **Options and Consumables**

Item Customer Display Unit	Part Number A61CF26101
DM-D30 (White)	A010120101
Customer Display Unit	A61CF26111
DM-D30 (Black) Wi-Fi Dongle WL-06	C32C891328
Parallel Interface Card	C32C823891
UB-P02	0020020001
Serial Interface Card	C32C823361
UB-S01	
ERC-(32B) Ribbon Cartridge,	C43S015371
Black	

©2024 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON is a registered trademark of Seiko Epson Corporation.

All other product and company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks.
Projected images shown herein are simulations.
The actual product design and contents may vary.
Specifications are subject to change without notice and may vary between countries. Please check with local
Epson offices for more information.

Dealer's Stamp

Information correct at time of printing. Printed November 2024







**Noise Level**