

PROYEKTOR KARYA ANAK BANGSA.

TERBAIK KUALITASNYA
TERTINGGI TKDN-NYA*.



Dapatkan hasil yang terbaik untuk biaya yang anda keluarkan dengan Proyektor Epson. Proyektor ini merupakan Karya Anak Bangsa yang dirancang secara khusus untuk pengguna Indonesia dan diproduksi di Dalam Negeri. Proyektor ini dirancang menjadi pilihan terbaik pada penggunaan baik di dalam ruangan kelas sekolah maupun di ruang rapat perkantoran. Dengan mengutamakan kenyamanan, Anda dapat menampilkan dan memproyeksikan konten presentasi anda secara nirkabel** dari perangkat pintar dengan bantuan perangkat lunak iProjection. Sekarang anda dapat menampilkan konten anda dengan tajam dan jelas pada layar besar.



12,000 Hours
Lamp life in eco
mode



Split Screen



Auto Vertical
Keystone***



Horizontal
Keystone Slider



iProjection



Cost
Effective



Total Nilai
TKDN + BMP
55.70%

E600 untuk
Indonesia



Total Nilai
TKDN + BMP
55.02%

X600 untuk
Indonesia

ENGINEERED FOR good



SPEKIFIKASI

MODEL NUMBER		EB-E600	EB-X600
Projection Technology		RGB liquid crystal shutter projection system	
Specifications of Main Parts			
LCD	Size	0.55-inch(C2fine)	
	Native Resolution	XGA	
Lightsource	Type	210W UHE	
	Life (Normal / Eco)	6,000 / 12,000 hours	
Aspect Ratio		4:3	
Projection Lens	Type	No Optical Zoom / Focus (Manual)	Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.44	1.49-1.72
	Focal Length	16.7mm	16.9 mm-20.28 mm
	Zoom Ratio	1.0-1.35 (Digital Zoom)	1-1.2
	Throw Ratio	1.44-1.95 (Wide to Tele)	1.48-1.77 (Wide to Tele)
Screen Size (Projected Distance)			
Standard	Tele: 22" to 259" [0.87m to 10.34m]	Tele: 30" to 300" [1.07m to 10.95m]	
	Wide: 30" to 350" [0.87m to 10.34m]	Wide: 30" to 300" [0.89m to 9.12m]	
Brightness*1			
White Light Output (Normal / Extended)		3,400 lm	3,600 lm
Colour Light Output		3,400 lm	3,600 lm
Contrast Ratio		15,000:1	16,000:1
Geometric Correction			
Vertical / Horizontal Keystone		±30° / ±30°	±30° / ±30° (Auto Vertical Keystone only)
Quick Corner		Yes	
Split Screen		Yes	
Internal Speakers		Monaural: 5W x 1	
Connectivity			
Analog Input	D-Sub 15Pin	2	
	Composite	1 (RCA)	
Digital Input	DVI-D	NA	
	HDMI	1	
Output Terminal	HDBaseT	NA	
	D-Sub 15Pin	1	
Audio Input	HDMI	NA	
	2RCA (White & Red)	1	
Audio Output	Stereo Mini	2	
	Stereo Mini Jack	1	
Others	USB Type A	NA	1 (for Wireless LAN, Firmware Update, Copy OSD Settings)
	USB Type B	1 (for Firmware Update, Copy OSD Settings)	
Mic Input	Stereo Mini	NA	
Control I/O	RS-232C	1	
	Remote Control Input	NA	
Network	Wired LAN	NA	1
	Wireless	NA	1 (ELPAP11 (Optional))
Wireless Specification (Only for EB-X600)			
Supported Speed For Each Mode		IEEE 802.11b (2.4GHz): 11 Mbps ² / IEEE 802.11g (2.4GHz): 54 Mbps ² / IEEE 802.11n (2.4GHz): 72.2 Mbps ² / IEEE 802.11a (5GHz): 54 Mbps ² / IEEE 802.11n (5GHz): 150 Mbps ²	
Wireless LAN Security		Infrastructure: OPEN, WPA2/WPA3-PSK Access Point: OPEN, WPA2-PSK (AES)	
Operating Temperature			
Operating Altitude		Low Altitude: 5 – 40 °C <41 – 104 °F> High Altitude: 5 – 35 °C <41 – 95 °F> (20% – 80% Humidity, No Condensation)	
Direct Power On / Off		Yes	
Start-Up Period		Up to 6 seconds, Warm-up Period: 30 seconds	
Cool Down Period		Instant Off	
Air Filter			
Type		High Efficiency Filter	
Maintenance Cycle (Normal / Eco)		6,000 / 12,000 hours ³	
Power Supply Voltage		100 – 240 V AC ±10%, 50/60 Hz	
Power Consumption (220 - 240V)			
Lamp (Normal / Eco)		327W / 225W	
Standby (Network / Energy Saving)		NA / 0.3W	2.0W / 0.3W
Dimension Excluding Feet (D X W X H)		249 x 302 x 87 mm	
Weight (Including Standard Lens)		Approx. 2.7 kg	
Fan Noise (Normal / Quiet)		37dB / 28dB	

¹ Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

² Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

³ When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m³). Based on the Epson's in-house test results.

* Items may differ depending on your region.

EB-E600/X600

Supplied Accessories

Power Cable (1.8m)
Connection Cable (1.8m)
Remote control with 2AA Battery
Carry Case: ELPKS69 (Outside Box)
Quick Start Guide

Optional Accessories

Spare Lamp: ELPLP97
Air Filter: ELPAF32
Wireless LAN Card + Cover: ELPAP11 (only for EB-X600)
Ceiling Mount: ELPMB23



EB-E600



EB-X600

©2024 PT Epson Indonesia. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.
Printed October 2024