

Finger Touch Unit: 1

Password Protect Sticker

Optional Accessories

Remote Control Cable Set

Wall Mount for FTU: FI PMB63 Easy Interactive Pen 1 (Orange): ELPPN05A Easy Interactive Pen 2 (Blue): ELPPN05B

eless LAN unit: ELPAP11

Air Filter: ELPAF56

Lens Cap

Cable Cover

EB-1485Fi

Corner Marker for Automatic Geometry Adjustment: 4

ELPKC28 (10m x 2) (for synchronization of Interactive IR)

Replacement Hard Pen Tips: ELPPS03 (for ELPPN05) Replacement Soft Pen Tips: ELPPS04 (for ELPPN05)

HDBaseT Connection and Contol Box: FI PHD02

©2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole,

without the written permission from Epson.

All other product names and other company names used herein are for identification

purposes only and are the trademarks or registered trademarks of their respective owners

Epson disclaims any and all rights in those

marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to

Apple, iPad and iPhone are trademarks of Apple

Inc., registered in the U.S. and other countri App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct at time of printing. Printed December 2019

change without notice and may vary between countries. Please check with local Epson offices for more information.

EPSON and EXCEED YOUR VISION are

registered trademarks of Seiko Epson

is strictly prohibited

Corporation.

Dealer's Stamp

SPECIFICATIONS EB-1485Fi MODEL NUMBER EB-1485Fi Supplied Accessories Projection Technology Specifications of Main Parts RGB liquid crystal shutter projection system Power Cable: 1.8m x 1 HCB (HDBaseT Connection and Control Box) AC Cable for HCB: 1.8m x 1 Resolution USB Cable for HCB: 1.8m x 1 Type F-Number Remote Control with Battery Attached nteractive Pens: 2 pens with AA Battery Focal Length Pen Stand: 1 Setting Plate: ELPMB62 Light Source Pen Tip (Felt): 4 Pen Tip (Teflon): 2

2 (for USB Memory, Printer, USB Document Camera, Firmware Update, Copy OSD Settings) 2 (for USB Display, Mouse, K/B, Control, Firmware Update, Interactive, Copy OSD Settings) Stereo Mini x 1

Infrastructure: IEEE 802.11b (2.4GHz): 11Mbps⁻², IEEE 802.11g (2.4GHz): 54Mbps⁻² IEEE 802.11n (2.4GHz): 72Mbps⁻²,

Infrastructure: IEEE 802.11b (2.4GHz): 11Mbps², IEEE 802.11g (2.4GHz): 54Mbps², IEEE 802.11n (2.4GHz): 72Mbps², IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11n (5GHz): 54Mbps², IEEE 802.11a (5GHz): 325Mbps² Access Point: (Wifi Direct): IEEE 802.11g (2.4GHz): 54Mbps², IEEE 802.11n (2.4GHz): 72Mbps², IEEE 802.11n (2.4GHz):

Infrastructure: IEEE 802.11b (2.4GHz): 11Mbps⁻², IEEE 802.11g (2.4GHz): 54Mbps⁻², IEEE 802.11n (2.4GHz): 72Mbps⁻², IEEE 802.11a (5GHz): 54Mbps⁻², IEEE 802.11a (5GHz): 325Mbps⁻² Access Point: (Wifi Direct): IEEE 802.11g (2.4GHz): 54Mbps⁻², IEEE 802.11n (2.4GHz): 72Mbps⁻²

Access Point (Wi-Fi Direct): WPA2-PSK(AES

IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11n (5GHz): 150Mbps², IEEE 802.11ac (5GHz): 325Mbps² Access Point: (Wifi Direct): IEEE 802.11g (2.4GHz): 54Mbps², IEEE 802.11n (2.4GHz): 72Mbps², IEEE IEEE 802.11a (5GHz): 54Mbps¹², IEEE 802.11n (5GHz): 150Mbps¹², IEEE 802.11ac (5GHz): 325Mbps

Infrastructure, Access Point (Wifi Direct)
Infrastructure: OPEN, WPA2 / WPA3-PSK, WPA2 / WPA3-EA; Access Point (Wi-Fi Direct): WPA2-PSK (AE)

IEEE 802.11a (5GHz): 54Mbps⁻², IEEE 802.11n (5GHz): 150Mbps⁻², IEEE 802.11ac (5GHz): 325Mbps⁻¹ Infrastructure, Access Point (Wifi Direct)

IEEE 802.11a (5GHz): 54Mbps², IEEE 802.11n (5GHz): 150Mbps², IEEE 802.11ac (5GHz): 325Mbps

 $\begin{array}{l} 0\text{ - 2,286 m (0 - 7,500 ft): }0\text{ - 40 °C [41 - 104 °F] }; 20\% \text{ to }80\% \text{ Humidity, No Condensation} \\ \underline{\text{Over 2,286 - 3,048 m (7,500 - 10.000 ft): }0\text{ - }35 °C [41 - 95 °F] }; 20\% \text{ 80\% Humidity, No Condensation} \\ \underline{0\text{ - 2,286 m (0 - 7,500 ft): }0\text{ - }35 °C [41 - 95 °F] }; 20\% \text{ to }80\% \text{ Humidity, No Condensation} \\ \end{array}$

Supported EAP type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast; Access Point(Wi-Fi Direct): WPA2-PSK(AES)

ring or WLAN Switchable Usage) x 1 USB Type A (In common with Memory I/O) x 1 using Optional Wireless LAN Unit

Infrastructure: OPEN_WPA2/WPA3-PSK_WPA2/WPA3-EAP

Infrastructure: OPEN, WPA2 / WPA3-PSK, WPA2 / WPA3-EAP

Infrared
Digital Pen (Easy Interactive Pen A & B)

Hover, Right Click, Auto Adjust Pen Are

Yes (Up to 6 Fingers)
USB, Network
Pen: Auto / Manual (25 Points)

30g (Excluding a battery)

375 x 458 x 209.5 mm

65 x 422 x 40 mm

Supported EAP type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast

Over 2,286 - 3,048 m (7,500 - 10,000 ft): 0 - 30 °C [41 - 86 °F] ; 20% Over 1,500 m / 4,921 ft, with High Altitude Mode: 0 - 3,048 m (0 - 10,6

uype
Life (Normal / Eco / Extended)
Screen Size (Projected Distance
Brightness*1
White Light Output (Normal / Quiet)
Colour Light Output Colour Light Output

Contrast Ratio Internal Speaker(s) Sound Output 8W x 8W Stereo Geometric Correction Vertical / Horizontal Keystone ±3°/±3° Quick Corner Connectivity

Sub 9pin x 1

D-Sub 15Pin Composite Digital Input HDMI HDBaseT Analog Output Terminal D-Sub 15Pin (Black) (in common with Computer 2) Digital Output Terminal HDMI

Stereo Mini Jack Audio Output Stereo Mini Jack Others USB Type A USB Type B Mic I/O RS-232C Control I/O

Interactive Sync. Touch Unit Contro Network Wired LAN Wireless LAN - Built-in

Supported Mode Wireless LAN Security Miracast

Supported Speed For Each Mode

Supported Speed For Each Mode

Supported Mode
Screen Mirroring-Built-in Supported Speed For Each Mode

Wireless LAN Security: Supported Speed For Each Mode

Supported Speed For Each Mode Interactive Spe

Interactive Uni Technology Input Devices

Connection To Computer Functions Pen Unit

Weight Touch Unit Maximum Dimension (D x W x H) Weight Operating Temperature

Multi-projection Use

Operating Altitude
Direct Power On / Off
Start-Up Period
Cool Down Period
Air Filter Maintenance Cycle⁵ Power Supply Voltage Power Consumption (220 - 240V) Lamp On (Normal / Eco

imension Excluding Feet (D x W x H) Weight (with cable cover) Approx. 9.7 kg
Fan Noise (Normal / Extended / Quiet) 36dB / 36dB / 27dB

Pixel shifting technology achieves Full HD resolution on screen Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with ISO 21118.

Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

These modes and actual data throughputs depend on supported wireless mode of source devices and/or environmental conditions. When environmental temperature becomes high, the brightness becomes dark automatically

When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m3). Based on the Epson's in-house test results.

Sales Enquiries 800 120 5564

Epson Singapore Pte Ltd

Enson Customer Care Center



Closed on Saturday, Sunday and Public Holiday. Please refer to www.epson.com.sg/contact for updated opening hours














For latest specifications, visit www.epson.com.sg/projectors or call 800 120 5564.

438B Alexandra Road, #04-01/04 Block B, Alexandra TechnoPark, Singapore 119968. Tel: (65) 6586-5500 100G Pasir Paniang Road, #01-09 Interlocal Centre, Singapore 118523, Epson Helpdesk; 800 120 5564, Opening hours; Monday - Friday, 9am to 5pm

FULL HD ULTRA-SHORT THROW INTERACTIVE PROJECTOR

EB-1485Fi





Up your game and bring your presentations and learning experiences to life with Epson EB-1485Fi projector. Designed for meeting spaces and educational purposes, the ultra wide, super bright Full HD laser display allows image projection of up to 120" diagonal at the 16:6 ratio. A true PC-free digital whiteboard, the Epson EB-1485Fi projector allows you to draw, save, print, and even email without a computer.



Resolution





Touch



Throw 120"



Liaht Hours







EB-1485Fi









3LCD technology that delivers quality projected images and reliable performance.

Pixel shifting technology achieves Full HD resolution on screen

Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environments.

Color brightness(color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP® projectors based on NPD sales data for May 2017 – April 2018.

Intuitive

design that enables you the limitless possibilities in creativity.



The master of collaborative devices, the Epson EB-1485Fi integrates the functions of a projector, whiteboard, and interactive display, transforming any flat surface into an interactive virtual space. Without using an additional computer or software, the projector allows users to turn it on and start writing or presenting immediately.

Offering 5,000 lumens of equal colour and white brightness, the EB-1485Fi presents a choice of either 100-inch 16:9 display or the new ultra-wide 120-inch 16:6 display. Delivering bright, true-to-life images to impactful presentations, the EB-1485Fi works splendidly even in well-lit rooms.



Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

² Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environments.



Interactive

learning experience that stimulates inspirational knowledge exchange.



Imagine a classroom with a giant, interactive, and immersive digital drawing board instead of the traditional whiteboard. Operated by either a six-point multi-touch or two interactive pens, the Epson EB-1485Fi enhances the education experience by allowing end users the direct control of the education software that is projected on the screen. Users can now create immediate drawings, add on annotations, and share information onto other devices instantly.

When educators and students alike are given the opportunity to co-create and interact simultaneously on this large digital canvas, the lesson becomes enriching, stimulating, and fun.




Dual Screen Seamless Interactivity

Two projectors can be installed side by side to create an ultra-wide interactive panoramic screen of up to 180 inches diagonal.




Digital Whiteboard Capability

Enjoy up to 20 pages of digital whiteboard even with no PC connected.




Ultra Wide Display

The new 16:6 display allows maximization of the existing whiteboard, providing an ultra-wide display of 120 inches diagonal.



Seamless Edge Blending

Engage your audience in compelling and fascinating presentations on a larger seamless screen with two Epson EB-1485Fi projectors (with interactivity), or up to four (without interactivity) at any one time. With Epson EB-1485Fi's built-in edge blending function, you can now interact, control, and present immersive content seamlessly over one large panoramic screen.



Superior Image Quality

Enjoy a dynamic viewing experience with Full HD* resolution on screen with laser light source. Deliver vibrant and sharp high-resolution image displays from PCs, tablets and smartphones and watch your photos, 3D CAD, Blu-ray and online videos come to life in Full HD*. Data figures on spreadsheets and charts will also be displayed clearly for everyone to read accurately.

* Pixel shifting technology achieves Full HD resolution on screen.










No Reflection Glare On Projection

The projection screen is not glossy and does not cause glaring reflections of ambient light like florescent lamps and sunlight from windows.



Larger Images

With a wide projection screen size of up to 120 inches 16:6, you enjoy bigger image projection for greater visibility.



Ultra-short Throw Advantage

As light is not blocked by the presenter, less shadow is formed on the screen, allowing the audience to clearly see the information projected at all times.



Immersive

presentations through a collaborative enterprise-level secured network.



The Epson EB-1485Fi connects people with technology, providing platforms for creative ideas, knowledge exchange, and collaborations across a wide variety of sectors where long life, minimal maintenance, and low cost of operation hold significant importance.

In addition to an enterprise-level security via integrated wireless networking, users can save, print, and email content directly from the interactive laser display. Wirelessly sharing content simultaneously from multiple devices with Miracast is also part of Epson EB-1485Fi's charm.



Ease of Installation

60% reduction on installation time*

*compared against current Epson interactive display products



Microsoft Ink Support

Draw and write on Microsoft PowerPoint, Excel or Word documents using Microsoft Office Ink



Quick Info Sharing

Enjoy great flexibility of importing and sharing information



Multi Location Interactivity

Up to 4 interactive projectors in different location can share the interactivity of the projector screen**

**Applicable only when connected to the same network, for example via VPN.



Wireless Connectivity

Project from your laptop or mobile wirelessly using Epson iProjection or Miracast Screen Mirroring respectively


Easy Installation Guide

Epson EB-1485Fi's new wall mount design makes installation a breeze. A single LAN cable is all you need to connect to the HDBaseT Control Box. Calibrate the screen with a simple one-click Auto Adjustment feature and the new, slimmer Finger Touch Unit allows for better motion detection.



Screen adjustment

Minimise image adjustment setup timings as compared to current interactive models.



FTU adjustment

Minimise the installation time as compared to current interactive models.





Set marker.








Checking the performance by touch 4 points.

Step 4

New wall mount

3 axis adjustment part has changed to save the installation time and avoid the image vibration.




Lock dial to the image stability

Easy adjustment with free angle structure

HDBaseT solution

Simplified cabling to send both images and interactivity signals through just one LAN cable.



Longer Transmission Distance

HDBaseT solutions can transmit 1080p signals up to a distance of 60m*.

Greater Compatibility

Compatible with all HDMI formats and supports all key features.

Cost Savings

Eliminates the need to purchase different cables for different signal types.

Simple Installation

Reduces cable clutter and hence, simplifying the installation process.

^{*} For 1080p resolution using Cat6a/Cat7 cable.

Wide Range of Connectivity

Quick information sharing

With the rich input-output options provided by the smart interactive projector platform, you can enjoy great flexibility of importing information from various sources and sharing the meeting results in multiple ways, saving you precious time and increasing productivity.

Import



Project Documents, Photos, and More Wirelessly

Enjoy wireless projection via the Epson iProjection* app with your Chromebook or mobile devices. This powerful app allows you to share, manage, and annotate on displayed content from an easy-to-use, intuitive menu. iProjection* for Chromebooks supports fully mirrored display of all of your Chromebook content including Google Docs, Slides, Sheets, and the Chrome browser.


Using the iProjection App is easy:



Laser Light Technology

Revolutionary Laser Light Source

Blue light from the laser is projected through a beam splitter, which divides the light into two beams. One beam is reflected by a phosphor wheel, changing it into yellow, while the other beam remains blue. The two beams are then recombined into white light and separated into red, green and blue through dichroic mirrors. Each of the three colours passes through LCD panels, producing three individual images, which are transmitted through a prism and combined into the final full-colour image.



Inorganic LCD Panels and Phosphor Wheel for Outstanding Reliability

Made of inorganic material, Epson's newly developed phosphor wheel offers superior light and heat resistance to deliver excellent reliability. By combining this with our inorganic LCD panels, we create laser projectors that project bright, vibrant images for extremely long periods.

Organic vs. Inorganic

	Inorganic (Glass, iron, aluminum, etc.)	Organic (Paper, wood, plastic, etc.)
: Light-resistance	YES _	NO
✦ Heat-resistance	YES T	NO 🔰


Unlike organic substances, inorganic substances do not contain carbon.

of Maintenance-free Use

Longer Light Hours - Up to 20,000 Hours

Engineered with inorganic LCD panels and an inorganic phosphor wheel, this newly designed laser light source delivers 20,000 hours' of maintenancefree use. And with the advanced electrostatic filter having an equally long-lasting life. Cut down on the frequecny of lamp replacements, saving you time and money, and lowering the total cost of ownership.





- * Compared with other conventional lamp projector that has lamp life of 4000 hours.
- Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m3 of particulate matter. Time varies depending on usage conditions and environments

For more information on Epson's environmental programmes, visit http://global.epson.com/SR/environment.



Better Products for a Better Future™

 Unpainted plastic housing reduces the environment impact • The flame retardants used in the plastic housing do not contain chlorine or bromine

• Laser light technology* eliminates the need for lamp

Eco Features

• Uses just 0.3W of power in standby mode • Projector optics employ lead-free lenses

^{*} In iProjection mode, projector profile search, multi-screen display, distribution function, audio transfer, movie file transfer, and encryption data transfer capabilities are not supported.





FLEXIBLE DISPLAY SIZE

From small spaces to big areas, project visuals up to 100 inch.



VALUE FOR MONEY

Projectors give larger display at a lower cost per inch over flat panel displays.



FLEXIBLE PLACEMENT

Projector can be placed in multiple positions to fit any presentation setting.

BIG ON DETAILS, MAXIMISING BUSINESS ENGAGEMENTS.

In business, every minor detail matters. Ensure that everyone sees everything from every corner of the room, clearly. Epson projectors are developed to display images with exceptional clarity that will surely engage and captivate all audiences. Compact in size but big on projection. It's In The Details.
















With 3LCD panels, every projection gives you spectacular true colours.



PROJECTOR WISHES COME TRUE.

EPSON 3LCD PROJECTORS

1-CHIP PROJECTORS





COLOUR 3000 LUMENS







LIGHT



































gives you spectacular true colours.

Find out more at www.epson.com.sg/truecolours

Leading Epson business and education projectors vs. leading 1-chip DLP® projectors, selected according to NPD data as of July 2015. Based on U.S. research conducted by Radius Research.

These lumen statistic can be found at www.colorlightoutput.com.

Color brightness(color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP® projectors based on NPD sales data for May 2017 – April 2018.

Gamut volume in brightest mode, measured by a third-party lab in 3D in the CIE L*a*b* coordinate space. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP® projectors based on NPD sales data for May 2017 – April 2018.