

EXPERIENCE RUGGED RELIABILITY AND POWERFUL PERFORMANCE.



Discover a new way to print all business documents with Epson's FX-2190II, FX-2190IIN, FX-2175II and FX-2175IIN dot matrix printers. Designed to deliver absolute performance and reliability, these powerful printers offer blazing print speeds of up to 615cps and an MTBF (Mean Time Before Failure) of up to 25,000 POH (Power On Hours). With the built-in network connectivity* function, printing efficiently is achieved in the most convenient way.



- 
Print
- 
High Speed Printing
- 
Cost Effective
- 
Power Savings
- 
Ethernet



Epson genuine ribbons ensure greater yield, better quality and longer lifespan.

IT'S IN THE DETAILS.

Unparalleled Productivity

Boost productivity with fast print speeds of up to 615 cps (10 cpi) and 128 kb memory buffer.

Rugged Reliability

Enjoy cost savings, superior print quality and minimal downtime with a MTBF of up to 25,000 POH.

Superior Connectivity

Stay connected and experience fuss-free printing with built-in network connectivity* via Ethernet cable.

*FX-2190IIN and FX-2175IIN only.

SPECIFICATIONS

FX-2175II/2175IIN/2190II/2190IIN

MODEL NUMBER	FX-2175II	FX-2175IIN	FX-2190II	FX-2190IIN			
Printer Technology							
Printing Method	Impact dot matrix						
Number of Pins in Head	9 pins						
Print Direction	Bi-direction with logic seeking						
Control Code	ESC/P2, IBM PPDS						
Printer Speed							
Ultra Speed Draft	10 / 12cpi	496cps / 595cps	615cps / 738cps				
High Speed Draft	10 / 12cpi	496cps / 568cps	612cps / 694cps				
Draft	10 / 12cpi	372cps / 445cps	463cps / 555cps				
NLQ	10 / 12cpi	93cps / 111cps	115cps / 138cps				
Print Characteristics							
Character Table	1 Italic and 12 graphical character tables: Italic table, PC437 (US, Standard/Europe), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC865 (Nordic), PC863 (Canadian-French), Abicomp, BRAScii, Roman 8, ISO Latin 1, PC858, ISO 8859-15						
Bitmap Fonts	Epson Draft Epson Roman / Epson Sans Serif						
Barcode Fonts	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET						
Printable Columns							
Pitch	10cpi	136cpl					
Paper Handling							
Paper Path	Manual Insertion (front or rear in, top out), Push Factor (front or rear in, top out), Pull Tractor (front, rear or bottom in, top out)						
Paper / Media	Length Width Thickness Length Width Thickness						
Cut Sheet (Single Sheet)	Entry: Front						
	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	
	Entry: Rear						
	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.065 - 0.14 mm (0.0025 - 0.0055")	
Cut Sheet (Multi-part Sheet)	Entry: Front						
	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.39 mm (0.0047 - 0.015")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.46 mm (0.0047 - 0.018")	
	Entry: Rear						
	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.39 mm (0.0047 - 0.015")	100 - 420 mm (3.9 - 16.5")	100 - 420 mm (3.9 - 16.5")	0.12 - 0.46 mm (0.0047 - 0.018")	
Continuous Paper (Single Sheet / Multi-part)	Entry: Front / Rear / Bottom						
	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.065 - 0.39 mm (0.0025 - 0.015")	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.065 - 0.46 mm (0.0025 - 0.018")	
	Copies						
	Original + 4 copies			Original + 6 copies			
Envelope (No.6)	Entry: Rear	92 mm (3.6")	165 mm (6.5")	0.16 - 0.52 mm (0.0063 - 0.0205")	92 mm (3.6")	165 mm (6.5")	0.16 - 0.52 mm (0.0063 - 0.0205")
Envelope (No.10)	Entry: Rear	105 mm (4.1")	241 mm (9.5")	0.16 - 0.52 mm (0.0063 - 0.0205")	105 mm (4.1")	241 mm (9.5")	0.16 - 0.52 mm (0.0063 - 0.0205")
Label (Base Sheet)	Entry: Bottom	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.16 - 0.19 mm (0.0063 - 0.0075")	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 406.4 mm (4.0 - 16.0")	0.16 - 0.19 mm (0.0063 - 0.0075")
Card	Entry: Front / Rear	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")	0.22 mm (0.0087")	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")	0.22 mm (0.0087")
Roll Paper	Entry: Rear	Diameter 127mm (5")	Width 216 mm (8.5")	Thickness 0.07 - 0.09 mm (0.0028 - 0.035")	Diameter 127mm (5")	Width 216 mm (8.5")	Thickness 0.07 - 0.09 mm (0.0028 - 0.035")
Line Spacing	4.23mm (1/6") or programmable in increments of 0.059mm (1/432")						
Acoustic Noise	56 dB			55 dB			
Input Data Buffer	128KB						
Interface	USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported)		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported) Serial, 100base-Tx wired LAN	USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported)		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported) Serial, 100base-Tx wired LAN	
Ribbon Cartridge	Standard Ribbon Life	Fabric Ribbon Cartridge (Black) Approx. 12 million Characters ¹					
Reliability							
Mean Print Volume Between Failure (MVBFB)	30 million lines (except print head)			52 million lines (except print head)			
Mean Time Between Failure (MTBF)	15,000 Power On Hours (POH) (25% Duty)			25,000 Power On Hours (POH) (25% Duty)			
Print Head Life	200 million strokes/wire			400 million strokes / wire			
Control Panel	6 switches and 10 LEDs						
Environmental Conditions (Operating)							
Temperature ²	5 - 35 °C						
Humidity ²	10 - 80% RH						
Electrical Specification							
Rated Voltage	AC 220 - 240 V						
Rated Frequency	50 Hz - 60 Hz						
Power Consumption	Operating	54W					
	Sleep Mode	0.5W	0.8W	0.5W	0.8W		
	Power Off	0.1W in power off mode					
Supported Operating System							
Printer Driver	Microsoft Windows XP / Vista / 7 / 8 / 10						
Utility	Epson Status Monitor 3: Microsoft Windows XP / Vista / 7 / 8 / 10 Epson Setting Utility: Microsoft Windows XP / Vista / 7 / 8 / 10						

Dimensions & Weight

Weight: Approx. 9.4kg (20.8lbs)



Options and Consumables

Pull Tractor Unit	C12C933791
Ribbon Cartridge	C13S015584

Legend

- cpi Characters per inch
(Characters per 25.4mm)
- cps Characters per second
- cpl Character per line

¹ Actual print yield may vary depending on usage purpose and environment

² Without condensation

© 2020 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at March 2020