


**DOT MATRIX PRINTER**  
**9-PIN WIDE CARRIAGE**  
**DFX-9000**

**EPSON**  
EXCEED YOUR VISION



**FAST FORWARD YOUR  
BUSINESS EFFICIENCY.**

Amplify your productivity with the Epson DFX-9000 dot matrix printer. Featuring speeds of up to 1,550 cps and a MTBF rating of 20,000 power-on hours (POH), this 9-pin, wide format printer can perform high-volume printing with great efficiency and cost-savings. With a convenient LCD panel, versatile connectivity and advanced paper handling capabilities, the DFX-9000 is your reliable choice in a busy environment.



10-copies  
Printing    High Speed  
Printing    Power  
Saving    Cost  
Effective



Epson genuine ribbons ensure greater yield, better quality and longer lifespan.

**IT'S IN THE DETAILS.**

**Remarkable Performance**

Print speeds of up to 1,550 characters per second (10 cpi) and a user-friendly LCD panel to maximise your productivity.

**Efficient and Reliable**

Enjoy resilient and long-lasting operations with low cost printing that goes easy on your overheads.

**Flexibility and Versatility**

Prints up to 10-part forms and offers a wide range of connectivity and paper handling options.

**SPECIFICATIONS**  
**9-PIN WIDE CARRIAGE**  
**DFX-9000**



<b>Model Number</b>	<b>DFX-9000</b>		
<b>Printer Type</b>	Impact Dot Matrix		
Printing Method	36 pins (9 × 4 staggered)		
Number of Pins In Head	Bi-direction with logic seeking		
Print Direction	ESC/P®, IBM® PPDS emulation		
Control Code			
<b>Print Speed</b>			
High Speed Draft	10 / 12 cpi	1,550 / 1,450 cps	
Draft	10 / 12 cpi	1,320 / 1,320 cps	
NLQ	10 / 12 cpi	330 / 330 cps	
<b>Print Characteristics</b>	For Standard version: Italic table, PC437(US, Standard Europe), PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), PC861(Icelandic), BRASCII, Abicomp, Roman 8, ISO Latin 1, PC858, ISO 8859-15		
Character Table	13 International character sets:		
Bitmap Fonts	EPSON High Speed Draft: 10CPI, 12CPI, EPSON Draft 10CPI, 12CPI, Proportional, EPSON Roman: 10CPI, 12CPI, Proportional, EPSON Sans Serif: 10CPI, 12CPI, Proportional		
Bar Code	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET		
<b>Printable Columns</b>			
Pitch	10 / 12 / 15 / 17 / 20 cpi	136 / 163 / 204 / 233 / 272 cpi	
<b>Printable Handling</b>	Paper Path	Tractor (Front or Rear in, top out)	
<b>Paper / Media</b>			
<b>Continuous paper (Single Sheet)</b>	<b>Length</b>	<b>Width</b>	<b>Thickness</b>
	76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)	0.065 - 0.10 mm (0.0025 - 0.0039 inch)
<b>(Multi Part)</b>	76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)	
	<b>Rear Entry</b>	<b>Front Entry</b>	
Copies	1 original + 6 copies	1 original + 9 copies	
Thickness	0.12 - 0.53 mm (0.0047 - 0.021 inch)	0.12 - 0.79 mm (0.0047 - 0.031 inch)	
<b>Labels</b>	<b>Base Sheet Length</b>	<b>Base Sheet Width</b>	<b>Base Sheet Thickness</b>
	76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)	0.07 - 0.09 mm (0.0028 - 0.0035 inch)
			<b>Total Thickness</b>
			0.16 - 0.19 mm (0.0063 - 0.0075 inch)
<b>Continuous forms with labels</b>	<b>Base Sheet Length</b>	<b>Base Sheet Width</b>	<b>Total thickness (Rear Entry)</b>
	76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)	0.065 - 0.53 mm (0.0025 - 0.021 inch)
			<b>Total Thickness (Front Entry)</b>
			0.065 - 0.79 mm (0.0025 - 0.031 inch)
<b>Overlapping multi-part forms</b>	<b>Base Sheet Length</b>	<b>Base Sheet Width</b>	<b>Total thickness (Rear Entry)</b>
	76.2 - 558.8 mm (3.0 - 22.0 inch)	76.2 - 419.1 mm (3.0 - 16.5 inch)	0.13 - 0.53 mm (0.0051 - 0.021 inch)
			<b>Total Thickness (Front Entry)</b>
			0.13 - 0.79 mm (0.0051 - 0.031 inch)
Acoustic Noise	58 dB(A) (ISO7779 pattern)		
Line Spacing	4.23mm(1/6 inch) or programmable in increments of 0.059mm (1/432 inch)		
<b>Input Data Buffer</b>	128 KB		
<b>Interface</b>	Bi-directional parallel interface (IEEE-1284 nibble mode supported), Serial I/F, USB 2.0 (Full Speed) I/F, Optional Serial Interface Board (No Buffer Type-B)		
<b>Ribbon Cartridge</b>	Black		
Colour	Fabric		
Type	15 million characters (Draft 10cpi, 14 dots/character)		
Ribbon life			
<b>Reliability</b>	Mean print volume between failure (MVBF)		
	133 million lines (except print head)		
MTBF	20,000 POH (25% duty cycle)		
Print head life	200 million strokes/wire		
<b>Control Panel</b>	9 buttons, 6 LEDs and 1 LCD		
<b>Environmental Conditions (operating)</b>	Temperature		
	5 to 35 °C		
Humidity	10 to 80 % RH		
<b>Electrical Specification</b>	Rated Voltage		
	AC 100- 240 V		
Rated Frequency	50-60 Hz		
Power Consumption	Approx. 185 W (ISO/IEC10561 Letter pattern)		
	Approx. 7.5 W in sleep mode		
<b>Printer Driver / Utility</b>	OS		
	Microsoft® Windows® 95/98/2000/Me/XP and Windows® NT® operating system Version 4.0		
	Windows® 7 / 8 (32bit / 64bit) Ultimate / Enterprise / Professional / 10 (32/64bit)		
Utility	Epson Status Monitor ver. 4		
	Microsoft Windows 95/98/Me/NT 4.0/2000		
	Windows XP/7/8/8.1/10 (32/64 bit)		

**Dimensions & Weight**  
**Weight: 34kg**



**Consumables and Options**

Ribbon Cartridge (Black)	C13S015505
Pull Tractor unit	C12C800382
Serial Interface Board (No Buffer Type-B)	C12C824432
PS107-iPv6 Network Card	7108323

\*1 The recommended average print volume estimate for optimum device performance after factoring supplies replacement intervals and device life.

\*2 Complies with ISO-9296.

\*3 According to IEC/ISO 19798 yield measurements. Yield may vary depending on printing variables and conditions including toner and page coverage, continuous or intermittent.



© 2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at March 2019


**Epson (Thailand) Co.,Ltd.**

1 Empire Tower, 42<sup>nd</sup> Floor  
 South Sathorn Road, Yan Nawa, Sathon, Bangkok 10120

**Contact Us**

✉ : support@eth.epson.co.th  
 📞 : Epson Thailand  
 ☎ : 02-460-9699

**Follow Us**



**More Details**

