



The Epson All-in-One EcoTank L3550 and L5590 are designed to maximise your print productivity and convenience at the office. The upgraded PrecisionCore Printhead enables even faster printing speeds and replaceable maintenance box reduces repair downtime, improving efficiency. Both printers come with a full suite of connectivity features, including wireless connectivity and enabling direct printing from smart devices. Download Epson Smart Panel app to your mobile device and turn it into an intuitive control centre that enables you to power On/Off, set up, monitor your printer and ink level effortlessly. Experience this high-speed all-in-one printing solution today.









Ultra-High Page Yield (Colour)

Borderless Printing up to 4R

Wi-Fi

















Productivity Meets Durability

With PrecisionCore Printhead enabled, L3550 and L5590 has faster printing speed at 15/8 ipm. Improved mechanical design on parts that support paper feed-out contributes to longer product life - 2 years or 50,000 pages**.

Sustainability in Mind

Reduce power consumption through Heat-Free Technology. With hardware made from 30% recycled plastic¹, utilising 84% less consumables compared to ink cartridge models² and over 80% recycled cardboard packaging, carbon footprint is minimised.

Simplify User Interface

New concept of Flip UI simplifies user operation. Preset your frequently used functions as different cards, reducing the hassle of going through numerous setting parameters.

IT'S IN THE DETAILS.

Available only on L5590. ** 2-year warranty or 50,000 pages, whichever comes first, printhead included.

Twing in plastic savings equivalent to approximately 250 plastic spoons, calculated as 3g of High Impact Polystyrene (HIPS) plastic spoon. Ratio of the amount of recycled plastic weight to overall plastic component weight of the hardware. The amount of recycled contents and recycled material varies depending on the model, manufacturing time and site.

Material weight comparison of consumables (including packaging) between Epson ink cartridges of WF2630 series and Epson ink bottles of L5590/3550 series.

SPECIFICATIONS

	L3550	L5590	
Printer Type	Print, Scan and Copy	Print, Scan, Copy, Fax with ADF	
Printing		·	
Printing Technology	PrecisionCore Printhead		
Nozzle Configuration	400 x 1 nozzles Black, 128 x 1 nozzles	per Colour (Cyan, Magenta, Yellow)	
Print Direction	Bi-directional printing		
Maximum Resolution	4800 x 1200 dpi (with Variable-Sized Dr	roplet Technology)	
Minimum Ink Droplet Volume	3.3 pl		
Print Speed*1			
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 33.0 ppm / 20.0 ppm		
ISO 24734, A4 (Black / Colour)	Simplex: Up to 15.0 ipm / 8.0 ipm		
First Page Out Time (Black / Colour)	Approx. 10 sec / 16 sec		
Photo Default - 10 x 15 cm / 4 x 6"*2 #3	Approx. 69 sec / 90 sec		
(Border / Borderless)			
rinter Language	ESC/P-R, ESC/P Raster		
automatic 2-sided printing	No		
Copying			
Copy Speed			
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 10.8 ipm / 5.5 ipm		
ISO 29183, A4 (Black / Colour), ADF	<u>-</u>	Approx. 60 sec / 82 sec	
Copy Quality	Standard	Standard / High	
Maximum Copies from Standalone	30 copies	99 copies	
Maximum Copy Resolution	600 x 600 dpi		
Maximum Copy Size	A4, LTR	Legal	
canning			
Scanner Type	Flatbed color image scanner		
Sensor Type	CIS		
Optical Resolution	1200 x 2400 dpi		
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")		
Scanner Bit Depth			
Colour	48-bit input, 24-bit output		
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		
scan Speed (Flatbed / ADF (Simplex)	had a sadour		
Monochrome 200 dpi	11 sec	12 sec / 5.0 ipm	
Colour 200 dpi	28 sec	29 sec / 5.0 ipm	
ax Function (L5590 only)	20 000	1 20 000 / 0.0 ipiii	
vpe of FAX	Walk-up Black-and-White and Colour Fa	x Canability	
Receive Memory / Page Memory	1.1 MB, Page memory up to 100 pages		
rror Correction Mode	ITU-T T.30		
AX speed (data transfer rate)	Up to 33.6 kbps, Approx. 3 sec / page		
AX Resolution	Up to 200 x 200 dpi		
ransmission Paper Size	Op 10 200 x 200 dpi		
Flatbed	Letter, A4		
ADF	A4, LTR, 8.5 x 13", Legal, Oficio 9, Mexic	oo Oficia Indian Logal	
Receiving Paper Size	Letter, A4, Legal	co-Olicio, ilidian-Legal	
Speed Dial / Group Dial		Up to 100 numbers, 99 groups	
ax Features	PC Fax (Transmission / Receive), Automatic Redial, Address book, Broadcast Fax (Mono		
ax i cataros	Only), Transmit Reservation, Polling Rece		
		554611	
DE Function (L5590 only)	Only), Harismit rieservation, rolling riese		
Support Paper Thickness	64 - 95 gsm		
ADF Function (L5590 only) Support Paper Thickness Paper Handling			
Support Paper Thickness Paper Capacity Paper Handling	64 - 95 gsm 30 sheets		
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method	64 - 95 gsm 30 sheets Friction feed		
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Jumber of Paper Trays	64 - 95 gsm 30 sheets		
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Number of Paper Trays Paper Hold Capacity	64 - 95 gsm 30 sheets Friction feed	20 sheets of Bramium Cleany Dhoto Danar	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Number of Paper Trays Paper Hold Capacity Input Capacity	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/n	n°), 20 sheets of Premium Glossy Photo Paper	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Jumber of Paper Trays Paper Hold Capacity Input Capacity Output Capacity	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m	2), Up to 20 sheets of Premium Glossy Photo Paper	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Number of Paper Trays Paper Hold Capacity Input Capacity	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter,	
support Paper Thickness laper Capacity laper Handling laper Feed Method lumber of Paper Trays laper Hold Capacity Input Capacity Output Capacity laper Size	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6",), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter,	
Support Paper Thickness Paper Capacity Paper Handling Paper Head Method Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Size Maximum Paper Size	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24")	c), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Florid Capacity Paper Hold Capacity Paper Capacity Paper Size Print Margin	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6",	c), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Capacity Paper Size Maximum Paper Size Print Margin Interface	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom	c), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6	
Support Paper Thickness Paper Capacity Paper Handling Paper Hend Method Paper Hold Capacity Paper Hold Capacity Paper Hold Capacity Paper Capacity Paper Size Parint Margin Paper Size Parint Margin Paper Size Pass Size Parint Margin Paper Size Pass Size Pas	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0	c), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Fixes Paper Fold Capacity Paper Size Parint Margin Paper Size Paper Size Parint Margin Paper Size Parint Margin Paper Size Parint Margin Paper Size Parint Margin Paper Size P	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct	c), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Floid Capacity Paper Floid Capacity Input Capacity Output Capacity Paper Size Maximum Paper Size Print Margin Interface USB Vetwork Vetwork Protocol	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ³ Ethernet, Wi-Fi EEE 802.11b/g/n, Wi-Fi Direct	
support Paper Thickness super Capacity Paper Handling vaper Feed Method lumber of Paper Trays vaper Hold Capacity Input Capacity Output Capacity vaper Size Maximum Paper Size virint Margin nterface ISB letwork letwork Network letwork Management Protocols	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ³ Ethernet, Wi-Fi EEE 802.11b/g/n, Wi-Fi Direct	
Support Paper Thickness Paper Capacity Paper Handling Paper Handling Paper Head Method Paper Fred Method Paper Hold Capacity Paper Hold Capacity Paper Hold Capacity Paper Size Paper Size Paper Size Parint Margin Pater Face Pater Handling Paper Size Pater Size Pate	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct ONS, mDNS, SLP, WSD, LLTD	
upport Paper Thickness aper Capacity aper Handling aper Handling aper Feed Method umber of Paper Trays aper Hold Capacity Input Capacity Output Capacity Output Capacity aper Size alaximum Paper Size rint Margin atterface SB etwork etwork Protocol etwork Management Protocols Iobile/Software and Cloud Printing Epson Connect	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, , 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct PNS, mDNS, SLP, WSD, LLTD e Print Driver	
Support Paper Thickness Paper Capacity Paper Handling Paper Handling Paper Feed Method Paper Floid Capacity Paper Floid Capacity Paper Size Parent Maximum Paper Size Print Margin Pater Size Pater Size Print Margin Pater Size Pater Size Print Margin Pater Size Pater Size Pater Size Pater Size Pater Maximum Paper Size Pater Maximum Paper Size Pater Maximum Paper Size Pater	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, , 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct PNS, mDNS, SLP, WSD, LLTD e Print Driver	
support Paper Thickness super Capacity Paper Handling Paper Handling Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Hold Capacity Paper Size Paper Size Parint Margin Paper Size Paper	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, , 5 x 7", Envelopes #10, DL, C6 settings in printer driver ³ Ethernet, Wi-Fi EEE 802.11b/g/n, Wi-Fi Direct Ethernet, Wi-Fi EEE 802.11b/g/n, Wi-Fi Direct Print Driver Print Driver Ethernet Ethern	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Fixe Paper Fold Capacity Paper Size Parint Margin Paper Size Pa	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, , 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct PNS, mDNS, SLP, WSD, LLTD e Print Driver	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Pumber of Paper Trays Paper Hold Capacity Input Capacity Output Capacity Paper Size Print Margin Paper Size Print Margin Paper Size Print Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD e Print Driver son Smart Panel 1.44" Colour LCD Panel	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Hold Capacity Input Capacity Output Capacity Paper Size Print Margin Paper Size Print Margin Paper Size Print Management Protocols Aboile/Software and Cloud Printing Epson Connect Other Mobile Solutions Printer Software Printer Software Printer Software	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps	2), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, , 5 x 7", Envelopes #10, DL, C6 settings in printer driver ³ Ethernet, Wi-Fi EEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD e Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11	
support Paper Thickness super Capacity Paper Handling Paper Feed Method Jumber of Paper Trays Paper Hold Capacity Input Capacity Output Capacity Paper Size Parint Margin Paper Size	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
apport Paper Thickness aper Capacity aper Handling aper Feed Method lumber of Paper Trays aper Hold Capacity Input Capacity Output Capacity aper Size Maximum Paper Size rint Margin aterface SB letwork letwork Protocol letwork Management Protocols flobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rinter Software perating System Compatibility	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
apport Paper Thickness aper Capacity aper Handling aper Feed Method lumber of Paper Trays aper Hold Capacity Input Capacity Output Capacity aper Size Maximum Paper Size rint Margin aterface SB letwork letwork Protocol letwork Management Protocols flobile/Software and Cloud Printing Epson Connect Other Mobile Solutions control Panel CD Screen rinter Software perating System Compatibility	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
support Paper Thickness saper Capacity Paper Handling saper Feed Method sumber of Paper Trays saper Hold Capacity Input Capacity Output Capacity saper Size Maximum Paper Size Print Margin Interface SSB seletwork seletwork Protocol setwork Management Protocols Sobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Selectrical Specifications	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
upport Paper Thickness aper Capacity aper Handling aper Feed Method lumber of Paper Trays aper Hold Capacity Input Capacity Output Capacity Output Capacity aper Size flaximum Paper Size rint Margin riterface SB etwork letwork Protocol etwork Management Protocols Tobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen rinter Software pperating System Compatibility lectrical Specifications ated Voltage	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
Support Paper Thickness Paper Capacity Paper Handling Paper Handling Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Size Pare Maximum Paper Size Pare	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
Support Paper Thickness Paper Capacity Paper Handling Paper Handling Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Size Pare Maximum Paper Size Pare	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
support Paper Thickness super Capacity Paper Handling super Feed Method sumber of Paper Trays super Hold Capacity Input Capacity Output Capacity Super Size Maximum Paper Size Maximum Paper Size Frint Margin Interface Siss Substitute Size Size Size Size Size Maximum Paper Size Size Maximum Paper Size Maximum Paper Size Size Size Size Size Size Size Size	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
Support Paper Thickness Paper Capacity Paper Handling Paper Handling Paper Feed Method Paper Hold Capacity Paper Hold Capacity Paper Hold Capacity Paper Hold Capacity Paper Size Paper Size Parint Margin Paper Size Paper	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Size Parit Margin Paper Size	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W	P, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Pumber of Paper Trays Paper Hold Capacity Input Capacity Untput Capacity Paper Size Print Margin Interface USB Vetwork Protocol Vetwork Protocol Vetwork Management Protocols Vetwork Management Protocols Vetwork Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel Control Panel Control Panel Corporating System Compatibility Electrical Specifications Vetwork Consumption Operating Standby Sleep Standby Sleep	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Fize Print Margin Paper Size Paper Size Print Margin Paper Size Paper Size Paper Size Print Margin Paper Size Paper S	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W	Pi, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, 5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Pumber of Paper Trays Paper Floid Capacity Input Capacity Untput Capacity Paper Size Print Margin Interface USB Pater Metwork Vetwork Management Protocols Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power Off	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(Pi, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Pumber of Paper Trays Paper Hold Capacity Input Capacity Untput Capacity Paper Size Print Margin Interface USB Vetwork Vetwork Protocol Vetwork Management Protocols Vetwork Management Protocols Vetwork Mobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen Printer Software Departing System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power Off Volse Level Vet Protocol Vetwork Management Protocols Vetwork Managem	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Pressure (Black / Colour) 5.1 / 5.1 B/c Sound Pressure (Black / Colour) 5.1 / 5.1 B/c Sound Pressure (Black / Colour) 5.1 / 5.1 B/c	P), Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 1 settings in printer driver Ethernet, Wi-Fi EEEE 802.11b/g/n, Wi-Fi Direct Ethernet, Wi-Fi EEEE 802.11b/g/n, Wi-Fi Direct Ethernet, Wi-Fi EEEE 802.11b/g/n, Wi-Fi Direct Print Driver Print Driver 1.44" Colour LCD Panel 2.8P2 / Vista / 7 / 8 / 8.1 / 10 / 11 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 2.9016 / 2019 / 2022 3.9016 / 3.90	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Fize Paper Fize Parint Margin Paper Size Paper Protocol Paper Mobile Solutions Paper Control Paper Paper Software Pap	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B(Pi, Up to 20 sheets of Premium Glossy Photo Paper ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS 0.9 W 0.9 W A), Sound Power (Black / Colour) 5.3 / 5.3 B(A), Sound Pressure (Black / Colour) 38 / 39 dB(A) A), Sound Power (Black / Colour) 6.7 / 6.0 B(A), Sound Power (Black / Colour) 6.7 / 6.0 B(A),	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Size Parit Margin Paper Protocol Pathoric Mobile Solutions Paper Mobile Solutions Paper Pa	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Pressure (Black / Colour) 5.1 / 5.1 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 50 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Co	in-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct INS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS 0.9 W A), Sound Pressure (Black / Colour) 5.3 / 5.3 B(A), B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), B(A) Sound Pressure (Black / Colour) 54 / 47 dB(A) B(A) Sound Pressure (Black / Colour) 54 / 47 dB(A)	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Hold Capacity Input Capacity Paper Size Print Margin Paper Size Print Margin Pater Mobile Solutions Paper Protocol Pater Mobile Solutions Paper Mobile	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B6, Sound Pressure (Black / Colour) 6.8 / 6.0 B6, Sound Pressure (Black / Colour) 55 / 47 d Page Yield's	ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct Print Driver Print Driver 1.44" Colour LCD Panel 292 Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS 0.9 W A), Sound Pressure (Black / Colour) 5.3 / 5.3 B(A), B(A) Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Sound Pressure (Black / Colour) 5.4 / 47 dB(A) Order Code Open	
Support Paper Thickness Paper Capacity Paper Handling Paper Feed Method Paper Hold Capacity Input Capacity Paper Field Capacity Paper Size Print Margin Interface Pager Maximum Paper Size Print Margin Interface Pager Size Print Margin Pater Protocol Patetwork Protocol Patetwork Management Protocols Paper Mobile/Software and Cloud Printing Paper Mobile Solutions Paper Mobile Solutions Printer Software Paper Printer Software Paper Paper Paper Pater Paper Printer Software Paper Paper Printer Software Paper Paper Pater Paper Pa	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Pressure (Black / Colour) 5.1 / 5.1 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.8 / 6.0 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Colour) 5.5 / 50 B(Sound Pressure (Black / Colour) 5.5 / 47 B(Sound Pressure (Black / Co	in-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct INS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 e supported for Windows Server OS 0.9 W A), Sound Pressure (Black / Colour) 5.3 / 5.3 B(A), B(A), Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), B(A) Sound Pressure (Black / Colour) 54 / 47 dB(A) B(A) Sound Pressure (Black / Colour) 54 / 47 dB(A)	
support Paper Thickness super Capacity Paper Handling super Feed Method lumber of Paper Trays super Hold Capacity Input Capacity Untput Capacity Untput Capacity Super Size Maximum Paper Size Variet Margin Interface Uniter Margin Interface Uniter Mobile Solutions Super Mobile Solutions Super Mobile Solutions Super Mobile Solutions Superating System Compatibility Silectrical Specifications Stated Voltage Stated Frequency Sower Consumption Operating Standby Sleep Power Off Solicise Level Co Printing / Premium Glossy Photo Paper Stest Photo Co C Printing / Plain Paper Default* Spson Consumable	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14",3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DC Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9.x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Pressure (Black / Colour) 5.1 / 5.1 B(Sound Pressure (Black / Colour) 5.1 / 5.1 B(Sound Pressure (Black / Colour) 5.5 / 47 d Page Yield*5 4,300 pages	in-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver 3 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct Inc., .5 x 7", Envelopes #10, DL, C6 settings in printer driver 3 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct Inc., .5 x 7", Envelopes #10, DL, C6 Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 supported for Windows Server OS A), Sound Pressure (Black / Colour) 5.3 / 5.3 B(A), E(A) Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Sound Pressure (Black / Colour) 54 / 47 dB(A) Order Code 003	
upport Paper Thickness aper Capacity aper Handling aper Feed Method umber of Paper Trays aper Hold Capacity Input Capacity Output Capacity Output Capacity aper Size taximum Paper Size rint Margin terface SB etwork etwork Protocol tetwork Management Protocols Tobile/Software and Cloud Printing Epson Connect Other Mobile Solutions Control Panel CD Screen rinter Software perating System Compatibility Iectrical Specifications ated Voltage ated Frequency ower Consumption Operating Standby Sleep Power Off Toise Level C Printing / Premium Glossy Photo Paper est Photo C Printing / Plain Paper Default*4 pson Consumable lack tyan	64 - 95 gsm 30 sheets Friction feed 1 Up to 100 sheets of Plain Paper (80 g/m Up to 30 sheets of Plain Paper (80 g/m A4, A5, A6, B5, B6, 100 x 148 mm, Ind 8.5 x 13", Legal 8.5 x 14", 3 x 5", 4 x 6", 215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom USB 2.0 Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, APIPA, PING, DD Epson iPrint, Epson Email Print, Remote Apple AirPrint, Mopria Print Service, Eps N/A Windows XP SP3 / XP Professional x64 Windows Server 2003 / 2008 / 2012 / 2 Only printing and scanning functions are Mac OS X 10.9 x or later AC 220-240 V 50 - 60 Hz 12 W 7.1 W 0.8 W 0.2 W Sound Power (Black / Colour) 5.1 / 5.1 B6, Sound Pressure (Black / Colour) 6.8 / 6.0 B6, Sound Pressure (Black / Colour) 55 / 47 d Page Yield's	ian-Legal (215 x 345 mm), Letter, .5 x 7", Envelopes #10, DL, C6 settings in printer driver ⁻³ Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct DNS, mDNS, SLP, WSD, LLTD Print Driver Son Smart Panel 1.44" Colour LCD Panel SP2 / Vista / 7 / 8 / 8.1 / 10 / 11 2016 / 2019 / 2022 esupported for Windows Server OS 0.9 W A), Sound Pressure (Black / Colour) 5.3 / 5.3 B(A), B(A) Sound Pressure (Black / Colour) 6.7 / 6.0 B(A), Order Code Order Code	

ensions & Weight

ht: 4.1 kg





int speed (Pages Per Minute) is calculated when inted on A4 plain paper in the fastest mode, $x \downarrow 15$ cm photo print speed when printed on soon Premium Glossy Photo Paper. Print speed ay vary depending on system configuration, print odd, document complexity, software, type of oper used and connectivity. Print speed does not clude processing time on host computer.



- nen printed on Epson Premium Glossy Photo Paper.
- herwise 3 mm top, left, right, bottom.
- efault mode in accordance with ISO7779 for MFPs.
- accordance with ISO 24711/24712. Actual yields will a accordance with ISO 24711/24712. Actual yields will any considerably for reasons including images printed, rint settings, temperature and humidity. Yields may be wer when printing infrequently or predominantly with ne ink colour. A variable amount of ink remains in the artridges after the "replace cartridge" signal. Part of ie ink from the first cartridges is used for priming the rinter. Ink is used for both printing and print head laintenance. All inks are used for both black and plour printing.

22 PT Epson Indonesia. All Rights Reserved. oduction in part or in whole, without the written ssion from Epson, is strictly prohibited. EPSON XCEED YOUR VISION are registered trademarks iko Epson Corporation. All other products names other company names used herein are for fication purposes only and are the trademarks istered trademarks of their respective owners. disclaims any and all rights in those marks. samples shown are simulations only. Specifications roduct availability are subject to change without e and may vary between countries. Please check ocal Epson offices for more information.

, iPad and iPhone are trademarks of Apple Inc., ered in the U.S. and other countries. App Store is a e mark of Apple Inc.

oid is a trademark of Google Inc.

er's Stamp

nation correct at time of printing ed December 2022



















