INK TANK SYSTEM PRINTERS ECOTANK L6460/L6490

8 - 4

0



THE ULTIMATE PRINTER FOR YOUR BUSINESS

EPSON

Robust and reliable. These are the EcoTank L6460 and L6490. Compact in size, the printers fit into any given space in your office. Enjoy hassle-free, auto-duplex printing that lowers printing cost; and face down output for better security. DURABrite ET Ink uses pigment-based ink to deliver durable, water-resistant and extra-sharp print. You can also download the Epson Smart Panel app and transform your mobile devices into an intuitive control centre to set up, monitor and operate the printers. Improve business efficiency with enhanced print performance from this stylish printing solution today.







EPSON

0

EPSO

EPSON

Y

Versatility meets Productivity

Super compact printer which fits any business environment with fast print speed of up to 17.0 ipm (black) and 9.5 ipm (colour).

Save on Consumables

Enjoy remarkably low cost per print with high page yield of up to 7,500 pages for black and white and up to 6,000 pages for colour.

Care for Environment

With Epson Heat-free technology, less power is required to operate the EcoTank as compared to laser printer, reducing environmental impact.

SPECIFICATIONS

Product Name	L6460	L6490	
Printer Type	Print, Scan, Copy with ADF	Print, Scan, Copy, Fax with ADF	
Printing			
Printing Technology	PrecisionCore Printhead		
Nozzle Configuration		400 x 1 nozzles (Black), 128 x 1 nozzles per Colour (Cyan, Magenta, Yellow)	
Maximum Resolution	4800 x 1200 dpi		
Print Speed ^{*1}			
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 37.0 ppm / 23.0 ppm		
ISO 24734, A4 (Black / Colour)	Simplex: Up to 17.0 ipm / 9.5 ipm I Duplex: Up to 7.5 ipm / 5.0 ipm		
First Page Out Time (Black / Colour)	Simplex: Up to 7.0 sec / 11.0 sec		
Printer Language	ESC/P-R, ESC/P Raster		
Automatic 2-sided printing	Yes		
Copying			
Copy Speed			
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 12.0 ipm / 6.0 ipm		
ISO 24735, A4 (Black / Colour), ADF	Simplex: Up to 10.0 ipm / 4.5 ipm		
Maximum Copies from Standalone	99 copies		
Reduction / Enlargement	<u>25 - 400%</u>		
Maximum Copy Resolution	600 x 600 dpi		
Maximum Copy Size Scanning	Legal		
Scanner Type	Elathod colour image seeppor		
	Flatbed colour image scanner CIS		
Sensor Type Optical Resolution	1200 x 2400 dpi		
Vaximum Scan Area	216 x 297 mm		
Scanner Bit Depth			
Colour	48-bit input, 24-bit output		
Grayscale	48-bit input, 24-bit output 16-bit input, 8-bit output		
Black & White	16-bit input, 8-bit output		
Scan Speed (Flatbed / ADF (Simplex))	To Skinpar, T bit output		
Monochrome 200dpi	Flatbed: Up to 12 sec / ADF: Up t	o 6.0 ipm	
Colour 200dpi	Flatbed: Up to 27 sec / ADF: Up t		
Fax Function			
Type of Fax	N/A	Walk-up B/W and Colour Fax Capability	
Receive Memory / Page Memory	N/A	2MB, Page memory up to 180 pages	
Error Correction Mode	N/A	ITU-T T.30	
Fax Speed (Data Transfer Rate)	N/A	Up to 33.6 kbps, Approx. 3 sec/page	
Fax Resolution	N/A	Up to 200 x 200 dpi	
Transmission Paper Size			
Flatbed	N/A	Letter, A4	
ADF	N/A	Letter, A4, 8.5 x 13", Legal	
Receiving Paper Size	N/A	Letter, A4, Legal	
Speed Dial / Group Dial	N/A	Up to 100 numbers, 99 groups	
Fax Features	N/A	PC Fax (Transmission / Receive), Automa	
		Redial, Address book, Broadcast Fax	
		(Mono Only), Transmit Reservation, Polling	
		Reception, Fax Preview	
ADF Function			
Support Paper Thickness	64-95 g/m ²		
Paper Capacity	35 sheets (A4 Paper), 10 sheets (Legal)	
Paper Handling			
Number of Paper Trays	2 (Front 1, Rear 1)		
Paper Hold Capacity			
Input Capacity		Plain Paper (80 g/m ²), up to 20 sheets of Premium	
Output Capacity	Glossy Photo Paper. Rear Slot: 1 sheet (80 g/m ²)		
Output Capacity	Up to 30 sheets of Plain Paper (80 g/m²) Up to 20 sheets of Premium Glossy Photo Paper		
Paper Size	Legal, Indian Legal, Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6,		
	Legal, Indian Legal, Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm), 8.5 x 13", 5 x 7", 4 x 6", Legal (8.5 x 14")		
	Envelopes: #10, DL, C6	. , . ,	
Vaximum Paper Size	215.9 x 1200 mm		
Print Margin	3 mm top, left, right, bottom via c	ustom settings in printer driver	
Interface			
JSB	USB 2.0		
Network	Wireless IEEE 802.11b/g/n, Wi-Fi Direct, Ethernet		
Network Protocol	TCP/IPv4, TCP/IPv6		
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTE		
Mobile and Cloud Printing			
Epson Connect		lemote Print Driver, Scan to Cloud	
Other Mobile Solutions	Apple AirPrint, Mopria Print Servic	e, Epson Smart Panel	
Control Panel			
_CD Screen	2.4" Colour LCD Touch Screen		
Printer Software			
Software Support	Epson ScanSmart		
Operating System Compatibility	Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10		
	Windows Server 2003 / 2008 / 2012 / 2016		
	Mac OS X 10.6.8 or later		
Electrical Specifications			
Rated Voltage	AC 220-240 V		
Rated Frequency	50-60 Hz		
Power Consumption	12.0 W (Operating), 5.4 W (Stand		
Neise Level	0.9 W (Sleep), 0.2 W (Power Off)	0.9 W (Sleep), 0.2 W (Power Off)	
Noise Level	Sound Bower (Block / Onlaw) 0.4	(6.9 P(A) Sound Pressure (Plasty (Ostaw)	
PC Printing / Plain Paper Default ^{*2}	Sound Power (Black / Colour) 6.4 51 / 55 dB(A)	/ 6.8 B(A), Sound Pressure (Black / Colour)	
Consumables	Page Yield*3	Order Code	
Black Ink Bottle	7,500	008	
Black Ink Bottle Cyan Ink Bottle	<u>י,ססס י</u>	008	
Jyan IIK DULIG	0.000 (0.000 // 0.000 // 0.000	008	
Vagenta Ink Bottle			
	6,000 (Composite Yield)		
Magenta Ink Bottle Yellow Ink Bottle User Replaceable Maintenance Box	Source Steeled Yes	008 C13T04D100	

Dimensions & Weight L6460 Weight: 7.3 kg e y 346 mm EPSO <u>ه</u> 347 mm 375 mm L6490 Weight: 7.3 kg 346 mm EPSON 2 III 347 mm

375 mm

*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.

Maren and American Americ American American Am American American A	essa- contactoristen in inter toconec
#1	#2
Black Text	Colour

*2 Default mode in accordance with ISO7779 for MFPs.

*3 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2021 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at August 2021