



Robust and reliable. These are the EcoTank L6460 and L6490. Compact in size, the printers fit into any given space in your office, Enjoy hassle-free, auto-duplex printing that lowers printing cost; and face down output for better security. DURABrite ET Ink uses pigment-based ink to deliver durable, water-resistant and extra-sharp print. You can also download the Epson Smart Panel app and transform your mobile devices into an intuitive control centre to set up, monitor and operate the printers. Improve business efficiency with enhanced print performance from this stylish printing solution today.









U**l**tra-High Page Yield (Black)

Duplex Printing

Automatic Document Feeder









Epson Connect Si















## Versatility meets Productivity

Super compact printer which fits any business environment with fast print speed of up to 17.0 ipm (black) and 9.5 ipm (colour).

## Save on Consumables

Enjoy remarkably low cost per print with high page yield of up to 7,500 pages for black and white and up to 6,000 pages for colour.

## **Care for Environment**

With Epson Heat-free technology, less power is required to operate the EcoTank as compared to laser printer, reducing environmental impact.

## SPECIFICATIONS

Product Name	L6460	L6490
Printer Type	Print, Scan, Copy with ADF	Print, Scan, Copy, Fax with ADF
Printing	Time, Goari, Gopy Warrier	
Printing Technology	PrecisionCore Printhead	
Nozzle Configuration	400 x 1 nozzles (Black), 128 x 1 nozzle	s per Colour (Cyan, Magenta, Yellow)
Maximum Resolution	4800 x 1200 dpi	
Print Speed		
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 37.0 ppm / 23.0 ppm	
ISO 24734, A4 (Black / Colour)	Simplex: Up to 17.0 ipm / 9.5 ipm   Duplex: Up to 7.5 ipm / 5.0 ipm	
First Page Out Time (Black / Colour)	Simplex: Up to 7.0 sec / 11.0 sec	
Printer Language	ESC/P-R, ESC/P Raster	
Automatic 2-sided printing	Yes	
Copying		
Copy Speed		
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 12.0 ipm / 6.0 ipm	
ISO 24735, A4 (Black / Colour), ADF	Simplex: Up to 10.0 ipm / 4.5 ipm	
Maximum Copies from Standalone	99 copies	
Reduction / Enlargement	25 - 400%	
Maximum Copy Resolution	600 x 600 dpi	
Maximum Copy Size	Legal	
Scanning	Flattand adams in a second	
Scanner Type	Flatbed colour image scanner	
Sensor Type	CIS	
Optical Resolution	1200 x 2400 dpi	
Maximum Scan Area	216 x 297 mm	
Scanner Bit Depth	49 bit input 04 bit autout	
Colour	48-bit input, 24-bit output  16-bit input, 8-bit output	
Grayscale Black & White	16-bit input, 8-bit output 16-bit input, 1-bit output	
Black & White Scan Speed (Flatbed / ADF (Simplex))	ro-bit input, 1-bit output	
	Flathed: Up to 12 coo / ADE: Up to 0.0	inm
Monochrome 200dpi Colour 200dpi	Flatbed: Up to 12 sec / ADF: Up to 6.0 Flatbed: Up to 27 sec / ADF: Up to 5.0	
Fax Function	Flatbed. Op to 27 Sec / ADF. Op to 5.0	ірі і
Type of Fax	N/A	Walk-up B/W and Colour Fax Capability
Receive Memory / Page Memory	N/A	2MB, Page memory up to 180 pages
Error Correction Mode	N/A	TTU-T T.30
Fax Speed (Data Transfer Rate)	N/A	Up to 33.6 kbps, Approx. 3 sec/page
-ax Speed (Data Translet Mate)	N/A	Up to 200 x 200 dpi
Fransmission Paper Size	14/7	<del>Sp to 200 x 200 dpi</del>
Flatbed	N/A	Letter, A4
ADF	N/A	Letter, A4, 8.5 x 13", Legal
Receiving Paper Size	N/A	Letter, A4, Legal
Speed Dial / Group Dial	N/A	Up to 100 numbers, 99 groups
Fax Features	N/A	PC Fax (Transmission / Receive), Automa
		Redial, Address book, Broadcast Fax (Mono Only), Transmit Reservation, Polling
		Reception, Fax Preview
ADF Function		
Support Paper Thickness	64-95 g/m <sup>2</sup>	
Paper Capacity	35 sheets (A4 Paper), 10 sheets (Legal)	
Paper Handling	0/5 14 5 4)	
Number of Paper Trays	2 (Front 1, Rear 1)	
Paper Hold Capacity	0 " 1   1   050   1   (51   5	(00 / 2) D OL 1 1 1 (00 / 2)
Input Capacity	Cassette 1: Up to 250 sheets of Plain Paper (80 g/m²). Rear Slot: 1 sheet (80 g/m²)  Up to 30 sheets of Plain Paper (80 g/m²)	
Output Capacity		
Paper Size	Legal, Indian Legal, Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm), 8.5 x 13", 5 x 7", 4 x 6", Legal (8.5 x 14")	
	Надакі (100 x 148 mm), 8.5 x 13", 5 x 7", 4 x 6", Legal (8.5 x 14") Envelopes: #10, DL, C6	
Maximum Paper Size	215.9 x 1200 mm	
Print Margin	3 mm top, left, right, bottom via custon	settings in printer driver
nterface		O = 100 He con 201 ann 201
JSB	USB 2.0	
Network	Wireless IEEE 802.11b/g/n, Wi-Fi Direct, Ethernet	
Network Protocol	TCP/IPv4, TCP/IPv6	
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTE	
Mobile and Cloud Printing		, , , , , , , , , , , , , , , , , , , ,
Epson Connect	Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud	
Other Mobile Solutions	Apple AirPrint, Mopria Print Service, Epson Smart Panel	
Control Panel		
_CD Screen	2.4" Colour LCD Touch Screen	
Printer Software		
Software Support	Epson ScanSmart	
Operating System Compatibility	Windows XP / XP Professional / Vista /	
	Windows Server 2003 / 2008 / 2012 / :	2016
Florateinal Compatition of the c	Mac OS X 10.6.8 or later	
Electrical Specifications	AC 220 240 V	
Rated Voltage	AC 220-240 V	
Rated Frequency	50-60 Hz	12.0 W (Operating) 5.5 W (Ctandb)
Power Consumption	12.0 W (Operating), 5.4 W (Standby), 0.9 W (Sleep), 0.2 W (Power Off)	12.0 W (Operating), 5.5 W (Standby), 0.9 W (Sleep), 0.2 W (Power Off)
Noise Level	o.a vv (Gleep), o.z vv (Fower OII)	10.3 VV (Olech), U.Z VV (FOWER OII)
Noise Level PC Printing / Plain Paper Default*1	Sound Power (Black / Colour) 6.4 / 6.8	B(A) Sound Pressure (Black / Colour)
FO Filmling / Plain Paper Default	51 / 55 dB(A)	DICH, SOUTH FESSURE (DIACK / COTOUT)
Consumables	Page Yield*2	Order Code
Black Ink Bottle	7,500	008
	1	008
Ovan Ink Bottle		
	6.000 (Composite Yield)	008
Cyan Ink Bottle Magenta Ink Bottle Yellow Ink Bottle	6,000 (Composite Yield)	008 008

**Dimensions & Weight** 

L6460 Weight: 7.3 kg



L6490 Weight: 7.3 kg



- \*1 Default mode in accordance with ISO7779 for MFPs.
- \*2 Quoted vields are based on the ISO 24711/24712 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2021 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks.

Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing Printed December 2021



User Replaceable Maintenance Box

To find out more, visit www.epson.com.my/ecotank or call 1800-81-7349 (Toll-Free).





C13T04D100