INK TANK SYSTEM PRINTERS
ECOTANK L3110/L3150

EPSON
EXCEED YOUR VISION

SIZE DOWN YOUR PRINTING COST.

Save more with Epson's economical and multifunctional printing solutions for business—the EcoTank L3110 and L3150—built to bring down costs, and bring up productivity. The integrated ink tanks enable spill-free, error-free refilling with individual bottles that have designated nozzles. Other features include borderless 4R printing and an ultra-high yield of 7,500 coloured and 4,500 black-and-white pages. The EcoTank L3150 also delivers the convenience of wireless connectivity, allowing direct printing from smart devices.

L3110

L3150

Ultra-High Page Yield

Borderless Printing up to 4R

Wi-Fi*

Wi-Fi Direct*

Epson Connect*

2-Year Warranty

Each printer comes bundled with a starter kit of 4 bottles of Epson genuine inks.

ecotank

NO.1 INK TANK PRINTER VENDOR WORLDWIDE 9 YEARS RUNNING 2010 - 2018

IT'S IN THE DETAILS.

Low Cost, High Yield
Save as you print with affordable ink bottles and an ultra-high page yield of 7,500 pages for colour prints and 4,500 pages for black-and-white prints.

Wireless Connectivity*
Print wirelessly over networks or connect to other smart devices with the integrated Wi-Fi and Wi-Fi Direct functions.

Borderless Printing
Print high quality borderless photos up to 4R size.

* Available only on L3150. Supported Epson Connect features: Epson iPrint, Epson Email Print, Remote Print Driver.

EPSON
EXCEED YOUR VISION

MODEL NUMBER	L3110	L3150
Printer Type	Print, Scan, Copy	
Printing		
Printing Technology	On-demand inkjet (Piezoelectric)	
Nozzle Configuration	180 x 1 nozzles Black, 59 x 1 nozzles per colour (Cyan, Magenta, Yellow)	
Print Direction	Bi-directional printing	
Maximum Resolution	5760 x 1440 dpi (with Variable-Sized Droplet Technology)	
Minimum Ink Droplet Volume	3 pl	
Print Speed[*1]		
Draft Text - Memo, A4 (Black[#1] / Colour[#2])	Up to 33 ppm / 15 ppm	
ISO 24734, A4 (Black / Colour)	Simplex: Up to 10 ipm / 5.0 ipm	
First Page Out Time (Black / Colour)	Approx. 10 sec / 16 sec	
Photo Default - 10 x 15 cm / 4 x 6" [*2 #3]	Approx. 69 sec per photo (Border) / 90 sec per photo (Borderless)	
Printer Language	ESC / P-R	
Automatic 2-sided printing	No	
Copying		
Copy Speed		
ISO 29183, A4, Simplex (Black / Colour)	Up to 7.0 ipm / 1.7 ipm	Up to 7.7 ipm / 3.8 ipm
Copy Quality	Colour / Black-and-White; Draft / Standard	
Maximum Copies from Standalone	20 copies	
Maximum Copy Resolution	300 x 300 dpi	600 x 600 dpi
Maximum Copy Size	A4, Letter	
Scanning		
Scanner Type	Flatbed colour image scanner	
Sensor Type	CIS	
Optical Resolution	600 x 1200 dpi	1200 x 2400 dpi
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")	
Scanner Bit Depth		
Colour	48-bit input, 24-bit output	
Grayscale	16-bit input, 8-bit output	
Black & White	16-bit input, 1-bit output	
Scan Speed (Flatbed)		
Monochrome 200 dpi	11 sec	
Colour 200 dpi	32 sec	28 sec
Paper Handling		
Paper Feed Method	Friction feed	
Number of Paper Trays	1	
Paper Hold Capacity		
Input Capacity	Up to 100 sheets-A4 / Letter Plain paper (80 g/m²) Up to 20 sheets-Premium Glossy Photo Paper 10 sheets-Envelope, 30 sheets-Postcard	
Output Capacity	Up to 30 sheets, A4 plain paper 20 sheets, Premium Glossy Photo Paper	
Paper Size	Legal, Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm), 5 x 7", 4 x 6", Envelopes: #10, DL, C6	
Maximum Paper Size	215.9 x 1200 mm (8.5 x 47.24")	
Print Margin	0 mm top, left, right, bottom via custom settings in printer driver [*3]	
Interface		
USB	USB 2.0	
Network	-	Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
Network Protocol	-	TCP/IPv4, TCP/IPv6
Network Management Protocols	-	SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD
Mobile and Cloud Printing		
Epson Connect	-	Epson iPrint, Epson Email Print, Remote Print Driver
Other Mobile Solutions	-	Google Cloud Print
Printer Software		
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later	
Electrical Specifications		
Rated Voltage	AC 220 – 240 V	
Rated Frequency	50 – 60 Hz	
Power Consumption		
Operating	12 W	12 W
Standby	3.9 W	4.3 W
Sleep	0.4 W	0.7 W
Power off	0.3 W	0.3 W
Noise Level (PC Printing)		
Premium Glossy Photo Paper Best Photo	5.2 B(A), 38 dB (A)	
Plain Paper Default[*4]	6.5 B(A), 52 dB (A)	

Consumables	Page Yield[*5]	Order Code
Black Ink Bottle	4,500	003
Cyan Ink Bottle		003
Magenta Ink Bottle	7,500 (Composite Yield)	003
Yellow Ink Bottle		003

Dimensions & Weight

L3110/L3150
Weight: 3.9 kg / 8.6 lbs

179 mm (7.0")
375 mm (14.8")
347 mm (13.7")

#1 Black Text

#2 Black Text and graphics

#3 Photo 4R (4 x 6")

*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.

*2 When printed on Epson Premium Glossy Photo Paper.

*3 Borderless printing is supported up to 4R (4 x 6"), otherwise 3 mm top, left, right, bottom.

*4 Default mode in accordance with ISO7779.

*5 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

Information correct as at June 2019