



Efficiency meets productivity with the EcoTank monochrome M1140, M2140 and M3170 printers. Powered by PrecisionCore Heat-Free Technology, these compact printers deliver fast print speeds at 20 ipm with laser-quality text. Save 50% in paper cost with auto-duplex capabilities and bottles that provide an ultra-high page yield of up to 6,000 pages<sup>1</sup> each. What's more, enjoy a peace of mind with 4 years warranty coverage3.









Duplex Printing

Wi-Fi Direct2



ecotonk precisioncore



Ethernet<sup>2</sup>





# PrecisionCore Printhead Technology

Enjoy fast print speeds at 20 ipm, reliability from inkjet technology, and quality prints that rise to the standards of business printing with PrecisionCore Heat-Free Technology.

# **Enhanced Productivity**

With up to 4-in-1 (Print, Scan, Copy, Fax)<sup>2</sup> functionality, boost your productivity with costeffective printing and an ultra-high page yield of up to 6,000 pages<sup>1</sup>.

# **Better For The Environment**

Low power consumption and less replacement parts compared to laser printers mean less waste for a positive impact on the environment.

# **SPECIFICATIONS**

Product Name	M1140	M2140	M3170
Printer Type	Print	Print, Scan, Copy	Print, Scan, Copy, Fax with ADF
Printing	D	N D.:+h	
rinting Technology Nozzle Configuration	PrecisionCore <sup>3</sup>		
Nozzie Configuration	400 x 2 nozzles Black  Bi-directional printing		
Maximum Resolution	Bi-directional printing  1200 x 2400 dpi (with Variable-Sized Droplet Technology)		
Ainimum Ink Droplet Volume	2.8 pl		
Print Speed *1			
Draft Text - Memo, A4 (Black *1)	Up to 39 ppm		
ISO 24734, A4 (Black)	Simplex: Up to	20 ipm, Duplex: 9.0 ipm	
First Page Out Time (Black)	Approx. 6 sec (Simplex) / 13 sec (Duplex)		
Printer Language	ESC/P-R, ESC/P Raster		
utomatic 2-sided printing	Yes		
Copying			
Copy Speed ISO 29183, A4, Simplex (Black)		Up to 17 ipm	
Copy Quality	-	Standard / Best	1-
Maximum Copies from Standalone	_	99 copies	
Reduction / Enlargement	-	25-400% Auto Fit Func	tion
Maximum Copy Resolution	-	600 x 600 dpi	
Maximum Copy Size	=	A4, Letter	Legal (ADF)
Scanning			·
canner Type	-	Flatbed colour image s	canner
ensor Type		CIS	
Optical Resolution	-	1200 x 2400 dpi	711\
Maximum Scan Area Scanner Bit Depth	-	216 x 297 mm (8.5 x 11	./ ]
Colour	_	48-bit input, 24-bit out	out
Grayscale	_	16-bit input, 8-bit outp	
Black & White	-	16-bit input, 1-bit outp	
ican Speed (Flatbed)			
Monochrome 200 dpi	<u>-</u>	12 sec	12 sec / 7.0 ipm
Colour 200 dpi		27 sec	27 sec / 7.0 ipm
Fax Function		- · · <del> ·</del>	
Type of Fax	-		Walk-up black-and-white and colour fax capability
Receive Memory / Page Memory	-		2 MB, Page memory, Up to 180 pages (ITU-T No.1 chart
Error Correction Mode	-		ITU-T T.30
Fax Speed (Data Transfer Rate) Fax Resolution	-		Up to 33.6 kbps, Approx. 3 sec/page Up to 200 x 200 dpi
Transmission Paper Size			ор to 200 х 200 арг
Flatbed	-		Letter, A4
ADF	<u></u>		Letter, A4, 8.5 x 13", Legal
Receiving Paper Size	-		Letter, A4, Legal
Speed Dial / Group Dial	-		Up to 100 numbers, 99 groups
Fax Feature	-		PC Fax (Transmission/Receive), Automatic Redial,
			Address Book, Transmit Reservation, Broadcast Fax (Mono Only), Polling Reception, Fax Preview
ADF Function			Tax (wono only), Folling neception, Fax Freview
Support Paper Thickness	-		64 to 95 g/m <sup>2</sup>
Paper Capacity	-		35 sheets of A4 paper
Paper Handling			
Paper Feed Method	Friction Feed		
Number of Paper Trays	2		
Paper Hold Capacity	C 11 4 200Cl 1 14 / L 11 Dl 12 2 / 22 / 23 24 L - 1		
Input Capacity	Cassette 1: 250 Rear slot: 1 she	) Sheets-A4 / Letter Plain Paper Pet-A4 paper	r (80 g/m <sup>2</sup> ); 10-sheets-Envelope;
Output Capacity	Up to 100 shee		
Paper Size			Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6,
	Hagaki (100 x	148 mm), Envelopes: #10, DL, C	
Maximum Paper Size		nm (8.5 x 47.24")	
Print Margin	3 mm top, left	right, bottom via custom setti	ngs in printer driver
nterface	LICE 2.0		
JSB Vetwork	USB 2.0		Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
Network Network Protocol	-		TCP/IPv4, TCP/IPv6
Network Management Protocols	-		SNMP, HTTP, DHCP, APIPA, PING, DDNS,
			mDNS, SLP, WSD, LLTD
Mobile and Cloud Printing			
pson Connect	-		Epson iPrint, Email Print, Remote Print Driver,
Other Mobile Solutions			Scan to Cloud Apple AirPrint, Mopria Print Service
Control Panel	-		Apple All Fillit, Mopila Fillit Service
.CD Screen	-	1.44" LCD Screen	2.4" LCD Touch Screen
Printer Software		1 222 20.0011	
Operating System Compatibility		Vista / 7 / 8 / 8.1 / 10	
	Windows Serv	er 2003 / 2008 / 2012 / 2016 / 2	
	Only printing t Mac OS X 10.6	unction are supported for Win .8 or later	aows Server US
Electrical Specifications	ac 03 A 10.0		
Rated Voltage	AC 220 - 240 V		
Rated Frequency	50 - 60 Hz		
ower Consumption			
Operating	14 W	13 W	12 W
Standby	3.4 W	5.1 W	5.6 W
Sleep	0.6 W	0.7 W	0.9 W
Power Off	0.2 W	0.3 W	0.2 W
Noise Level (PC Printing)			
Plain Paper Default *2	6.9 B(A), 56 dB		
Consumables	Page Yield *3	Order Code	
tandard Black Ink Bottle	2,000	0055	
High Capacity Black Ink Bottle	6,000 005		
Maintenance Box	C13T04D100		

**Dimensions & Weight** M1140

Weight: 4.3 kg / 9.5 lbs



M2140 **Weight:** 6.2 kg / 13.7 lbs



M3170 Weight: 7.3 kg / 16.1 lbs



\*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



and graphics

- \*2 Default mode in accordance with ISO7779 for MFPs.
- 2 Detail mode in accordance with ISO/17 for MirPs.
  3 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and black-and-white graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower flow in those of replacement ink bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. Ink is used for both printing and printhead maintenance.

© 2020 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks.

Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at October 2020

# Epson (Thailand) Co.,Ltd.

Maintenance Box

1 Empire Tower, 42<sup>nd</sup> Floor South Sathorn Road, Yan Nawa, Sathon, Bangkok 10120

# **Contact Us**

support@eth.epson.co.th









