

EXPERIENCE SUPERB VERSATILITY WITH FLUORESCENT BRILLIANCE*.




Fabric Made Fabulous.


The SC-F530 series not only exhibits a high standard in printing with CMYK colours, but is economically ideal for small businesses with a lower print volume and is ergonomically designed to fit well in any small office space. In addition to that, the SC-F531 takes it a notch higher by also offering businesses the option of printing with fluorescent colours. The Epson Genuine fluorescent yellow and pink inks, bring brightness and vividity to the production of sportswear embellishments and novelty gifts.




*Fluorescent printing is only for SC-F531



SC-F530



SC-F531



IT'S IN THE DETAILS.

With Epson UltraChrome™ ink, the SureColor F-series printers redefine consistent, quality printing.

User-Friendly & Convenient

The SC-F530 series is developed with simple settings and features that enable easy operation and brings convenience to users in the SOHO environment.

Space Efficient

At just 24", the SC-F530 series is Epson's smallest dye-sublimation printer that only takes up a small footprint.

Fluorescent Brilliance

Using Epson's genuine fluorescent inks, SC-F531 can print in both fluorescent yellow and pink.



EPSON ULTRACHROME
DS INK

Epson Edge Print

SPECIFICATIONS

SureColor SC-F530 & SC-F531

EPSON

MODEL NUMBER	SC-F530	SC-F531
SKU Code	C11CJ17402	C11CJ58402
Printer Width	24"	
Printing Technology	PrecisionCore Inkjet Technology	
Technology 1	Variable-Sized Droplet Technology	
Technology 2	PrecisionCore TFP Printhead	
Printhead	3200 nozzles (800 nozzles x 4 channels x 1 head)	
Nozzle Configuration	2400 x 1200 dpi	
Maximum Resolution		
Print Speed*		
Production (2 pass)	For Fabric : Up to 62sec / 21m ² (600 x 1200dpi)	
Production (7 pass)	For Fabric & Rigid : Up to 208sec / 7.5m ² (1200 x 1200dpi)	
Production (12 pass)	For Fabric & Rigid : Up to 350sec / 4.5m ² (2400 x 1200dpi)	
Ink System		
Ink Type	Epson Genuine Dye-Sublimation Ink	
Colours	Cyan, Magenta, Yellow, Black Cyan, Fluorescent Pink, Fluorescent Yellow, Black	
Ink Capacity	140ml	
Ink Case	Ink Bottle	
Paper Handling		
Paper Path	Friction Feed	
Maximum Roll Diameter / Weight	Max. 110mm/3kg	
Paper Width (Roll)	Roll Paper: 210 mm to 610 mm Cutsheet: 210mm to 610 mm ASF: A4 to A3	
Paper Thickness	Roll Paper: 0.05mm~0.21mm Cutsheet: 0.12mm~0.27mm ASF: 0.12mm~0.27mm	
	4.3 inch Touch Screen	
Control Panel		
Connectivity		
Printer Interfaces	Super-Speed USB, 100BASE-TX / 1000BASE-T, Wi-Fi Direct	
Printer Languages	ESC/P Raster, HP-GL/2HP RTL	
Memory	1GB	
Power and Operating Requirements		
Power Requirements	AC 100 to 240V 50/60Hz	
Rated Current	1.4A	
Power Consumptions	Operating: Approx. 22W Ready: Approx. 8W Sleep: Approx. 1.6W Power Off (Stand by): Approx. 0.2W	
Temperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C	
Humidity	Operating: 20 - 80% (no condensation), Storage: 5 - 85% (no condensation)	
Utility Software		
Utility Software (Bundled in CD)	Windows: Install Navi - Printer Driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - Epson Software Updater - EPSON Manuals - Manual Launcher Mac: Setup Navi Windows only: DVD (Epson Edge Print Bundle SKU only), Epson Communication Driver	
Utility Software (Web delivery)	Windows: Install Navi, Web Installer, Firmware Updater, Epson Net Setup Manager, Epson Device Admin, LFP Accounting Tool Mac: Web Installer, Install Navi, Printer Driver, EpsonNet Config, Epson Software Updater, Uninstaller, EPSON Manuals. Firmware Updater	
Printer Dimensions		
Storage Dimensions (W x H x D)	970mm x 245mm x 577mm	
Printing Dimensions (W x H x D)	970mm x 245mm x 811mm	
Weight	29kg	
What's In The Box	Printer, Initial Ink, AC Power Cable, Setup Guide, Software CD-ROM, Maintenance Box (x2)	
Options	Optional Stand - 24", Roll Feed Spindle - 24"	
Consumables	Ink, Replacement Printer Cutter Blade, Replacement Ink Maintenance Tank	
Warranty	2 years	

*Based on internal testing

^Only for SC-F531

~ Only for SC-F530

SC-F530

Dimension & Weight

Weight: 29kg



SC-F531

Dimension & Weight

Weight: 29kg



Ink Compatibility

• Black	C13T49P100
• Cyan	C13T49P200
• Magenta	C13T49P300
• Yellow	C13T49P400
• Fluorescent Yellow [^]	C13T49FA00
• Fluorescent Pink [^]	C13T49FB00

Supplies & Optional Accessories

DS Transfer General Purpose 24 inch Roll	C13S400080
DS Transfer General Purpose 17 inch Roll	C13S400079
Stand (24")	C12C933151
Roll Feed Spindle (24")	C12C935701
Maintenance Box	C13S210057
Auto Cutter Spare Blade	C13S210055



© 2021 PT Epson Indonesia. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Partner's Stamp

Information correct at time of printing
Printed August 2021

1-500-766 0812-12-37766 **HOTLINE CALL CENTER**
(NATIONAL AREA)

PT Epson Indonesia
Epson Sales & Service
(Showroom)
Epson Service Center

Cibis Tower 9, 3rd Floor, CIBIS Business Park, Jalan TB Simatupang No.2, Jakarta 12560 Tel: (021) 808-66-766 Fax: (021) 808-66-799
ESS Bandung, ESS Batam, ESS Bogor, ESS Jakarta (Citandak), ESS Jakarta (Mangga Dua), ESS Jakarta (Sudirman), ESS Makassar, ESS Manado, ESS Palu
ESS Purwokerto, ESS Semarang, ESS Surabaya (Gubeng), ESS Surabaya (Barat), ESS Tangerang
ESC Ambon, ESC Banjarmasin, ESC Cikarang, ESC Cirebon, ESC Denpasar, ESC Jember, ESC Madiun, ESC Medan, ESC Palembang, ESC Pekanbaru
ESC Pontianak, ESC Samarinda, ESC Serang, ESC Yogyakarta

Epson Indonesia @EpsonIndonesia @EpsonIndonesia Epson Indonesia Epson Indonesia

For more information, visit <https://www.epson.co.id/textile-printing>