LARGE FORMAT PRINTERS
SURECOLOR SC-P7530 & SC-P9530

EPSON

LARGER THAN LIFE
PHOTO PRINTS
THAT COME ALIVE.

## Impeccable Photo Quality, Unparalleled Colour Accuracy.

Add a touch of extraordinary performance to your photo printing with the Epson SureColor™ 24-inch SC-P7530 and 44-inch SC-P9530 large format photo printers. Unparalleled wide colour gamut print quality with the UltraChrome PRO12 ink perfectly paired with Epson's PrecisionCore® MicroTFP® printhead, to deliver high quality prints at outstanding speeds. Expect nothing short of impeccable in the quality and accuracy of your photo prints.

SC-P7530

SC-P9530

IT'S IN THE DETAILS.

With Epson UltraChrome™ ink, the SureColor P-series printers redefine consistent, quality printing.

Outstanding Colour Quality
Wide colour gamut with the UltraChrome PRO12 and increased black density with Black Enhance Overcoat.

Exceptional Productivity
With dedicated Matte Black and Photo Black ink channels, print jobs can be continuous.

Trusted Reliability
The printers are designed to be dust-proof with an easy access hatch for printhead cleaning to ensure minimised downtime.

PRECISIONCORE

ULTRACHROME PRO12 INK

SPECIFICATIONS
SureColor SC-P7530 & SC-P9530

EPSON

MODEL NUMBER	SC-P7530	SC-P9530
Printer Width	24"	44"
Printing Technology		
Printing Method	PrecisionCore Inkjet Technology, Variable-Sized Droplet Technology	
Printhead	MicroTFP Printhead	
Nozzle Configuration	9600 nozzles (800 nozzles x 12 channels x 1 head)	
Maximum Resolution	2400 x 1200 dpi	
Minimum Ink Droplet Volume	3.5pl	
Print Speed	97 sec (Level 1)122 sec (Default) Premium Glossy	219 sec (Level 1)285 sec (Default) Premium Glossy
	Photo Paper 170gsm A1 size/ ISO Bike	Photo Paper 170gsm B0 size/ ISO Bike
Ink System		
Ink Type	UltraChrome PRO12 Pigment Ink	
Colours	Cyan, Vivid Magenta, Yellow, Light Cyan, Vivid Light Magenta, Orange, Green, Violet, Photo Black,	
	Matte Black, Gray, Light Gray	
Ink Capacity	350ml, 700ml	
Paper Handling		
Paper Path	Friction Feed	
Maximum Roll Diameter / Weight	2" roll core media: Max. 103 mm/6 kg,	2" roll core media: Max. 103 mm/10kg,
	3" roll core media: Max. 150 mm/6 Kg	3" roll core media: Max. 150 mm/10Kg
Paper Width (Roll)	Roll Paper: 254 mm to 620 mm,	Roll Paper: 254 mm to 1118 mm,
	Cutsheet: 210 mm to 620 mm	Cutsheet: 210 mm to 1118 mm
Paper Thickness	Roll : 0.08 mm to 0.5 mm, Cutsheet : 0.08 mm to 1.5 mm	
Control Panel	4.3 inch touch screen	4.3 inch Optical Touch Colour LCD
Connectivity		
Printer Interface	Super-Speed USB, 100BASE-TX /1000BASE-T	USB Interface (Hi-Speed USB/USB),
		1000BASE-T/100BASE-TX
Printer Language	ESC/P raster	
Memory	2GB	
Power and Operating Requirements		
Power Requirements	AC 100 to 240V 50/60Hz	
Rated Current	3.4-1.6A	
	Operating: Approx. 85W	Operating: Approx. 110W
	Ready: Approx. 32W	Ready: Approx. 32W
	Sleep: Approx. 3.4W	Sleep: Approx. 3.4W
Power Consumption	Power Off (Stand by): Approx. 0.3W	Power Off (Stand by): Approx. 0.3W
Temperature	Operating: 10°C to 35°C, Storage/Packing: -20°C to 60°C, Unpacking: -20°C to 40°C	
Humidity	Operating: 20 - 80% (no condensation), Storage: 5 - 85% (no condensation)	
Acoustic Noise Level		
Sound Pressure Level <db(A)>	Operating: Approx. 49.5dB(A), Sleep: Approx. 31.5dB(A)	
Sound Power Level <B(A)>	Operating: Approx. 7.5B(A)	
Utility Software		
Utility Software (Bundled in CD)	Windows Install Navi - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE -	
	Epson Software Updater - EPSON manuals - Manual Luncher - Epson Control DashboardMac	
	Setup Navi EpsonNet Config SE Epson Software Updater	
Utility Software (Web delivery)	Windows Install Navi, Web Installer, Firmware Updater, PS Driver, HDI Driver, XPS Driver, Epson	
	Media Installer, EpsonNet Setup Manager, Epson Device Admin, Epson Edge Dashboard, Epson	
	Edge Print, Epson Print Layout, LFP Accounting tool, Adobe ICC	
	Profiles, Mac Web Installer, Install Navi - Printer driver - EpsonNet Config - Epson Software	
	Updater - Uninstaller - Epson Manuals, Epson Media Installer, Firmware Updater, Linux, Printer driver	
Printer Dimensions		
Storage Dimensions (W x H x D)	1,401mm x 1,218mm x 667mm	1,909mm x 1,218mm x 667mm
Printing Dimensions (W x H x D)	1,401mm x 1,218mm x 2,211mm	1,909mm x 1,218mm x 2,211mm
Weight	121.7kg	153.8kg
What's in the box	Printer, Printer Stand, Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-ROM, Maintenance Box.	
Options	SpectroProofer, SpectroPhotoMeter, ILS30EP, Auto Take Up Reel Unit, Hard Disk Unit, Adobe	
	PostScript 3 Expansion Unit, Roll Media Adapter	
Consumables	Ink Cartridge , Maintenance Box, Auto Cutter Spare Blade, Borderless Replacement Pad Kit	

SC-P7530
Dimension & Weight
Weight: 121.7kg

1,218mm
2,211mm
1,401mm

SC-P9530
Dimension & Weight
Weight: 153.8kg

1,218mm
2,211mm
1909mm

Supplies & Optional Accessories

SC-P7530	C11CH12402
SC-P9530	C11CH13402
SC-P7530/9530 PK IC (700ml)	C13T44N100
SC-P7530/9530 CY IC (700ml)	C13T44N200
SC-P7530/9530 VM IC (700ml)	C13T44N300
SC-P7530/9530 YL IC (700ml)	C13T44N400
SC-P7530/9530 LC IC (700ml)	C13T44N500
SC-P7530/9530 VL IC (700ml)	C13T44N600
SC-P7530/9530 LB IC (700ml)	C13T44N700
SC-P7530/P9530 MK IC (700ml)	C13T44N800
SC-P7530/9530 LI IC (700ml)	C13T44N900
SC-P7530/9530 OR IC (700ml)	C13T44NA00
SC-P7530/9530 GR IC (700ml)	C13T44NB00
SC-P7530/9530 VI IC (700ml)	C13T44ND00
SC-P7530/9530 PK IC (350ml)	C13T44V100
SC-P7530/9530 CY IC (350ml)	C13T44V200
SC-P7530/9530 VM IC (350ml)	C13T44V300
SC-P7530/9530 YL IC (350ml)	C13T44V400
SC-P7530/9530 LC IC (350ml)	C13T44V500
SC-P7530/9530 VL IC (350ml)	C13T44V600
SC-P7530/9530 LB IC (350ml)	C13T44V700
SC-P7530/9530 MK IC (350ml)	C13T44V800
SC-P7530/9530 LL IC (350ml)	C13T44V900
SC-P7530/9530 OR IC (350ml)	C13T44VA00
SC-P7530/9530 GR IC (350ml)	C13T44VB00
SC-P7530/9530 VI IC (350ml)	C13T44VD00

Partner's Stamp

Information correct at time of printing
Printed February 2020