# LARGE FORMAT PHOTO PRINTER SURECOLOR SC-P8530D



# AMPLIFY YOUR IDEAS WITH TOP CLASS PRINT QUALITY.

## Transform your ideas into striking true-to-life prints with Epson's P-series printer.

Nothing beats seeing life injected into your ideas, turning them into picturesque prints in vivid and vibrant colours with top-class accuracy. Equipped with the Epson's proprietary PrecisionCore MicroTFP printheads, the Epson SureColor SC-P8530D photographic printer take pride in their precise and reliable print productivity, along with the colour-accurate reproduction with Epson genuine UltraChrome PRO 6 inks. With high installation flexibility and seamless printing workflow, increase your print efficiency today!



Highest Standards in Print The additional grey ink in the UltraChrome Pro 6 inks offers smooth and natural colour gradation in every print.

## Installation Flexibility

Flat top design allows for easy placement of printer in challenging and narrow spaces, giving businesses more options in installation.

EPSON



## **Boosted Efficiency**

Improved print speeds and continuous automatic printing with dual rollers help ensure high productivity with minimal downtime.

## **SPECIFICATIONS**

MODEL NUMBER	SC-P8530D	Dimensions and	Weigl
SKU Number	C11CJ50402	SC 095200	
Printing Technology		SC-P8530D Weight: Approx. 1	155 ka
Printing Method Print Head	PrecisionCore Inkjet Technology, Variable-Sized Droplet Technology PrecisionCore MicroTFP Printhead	neight. Approx.	roo ng
Nozzle Configuration	9,600 Nozzles		
Black	Pk:1,600, Mk:1,600	Page	
Colour	C:1,600, M:1,600, Y:1,600, Gray:1,600	Manual	-1
Maximum Resolution	2,400 x 1,200 dpi		
Minimum Ink Droplet Volume	3.5pl		
Printing Specifications			
Print Speed	B0 size Premium Glossy Photo Paper 170gsm:		
	152 sec (Speed), 281 sec (Quality), 614 sec (Max Quality)	1,848mm	<b>*</b>
	Plain Paper: 35 sec (Draft), 46 sec (Speed), 258 sec (High Quality)		
	Poster – B0 size Epson Premium Glossy Photo Paper 170gsm 1200dpi x 1200dpi: Standard(sRGB)/Quality: 281 sec		
Margin Roll Paper	Right: Min. 3mm <sup>*1</sup> / Left : Min. 0mm <sup>*1</sup>		
Cut Sheet	Top: Min. 3mm <sup>-1</sup> / Bottom: Min. 1mm <sup>-1</sup>		
Ink System		WHAT'S IN THE	вох
Ink Type	Pigment Ink	Printer	
Ink Brand Name	UltraChrome Pro 6 Ink	<ul><li>Initial ink cartridge</li><li>AC power cable</li></ul>	e (110m
Colour	Cyan, Magenta, Yellow, Gray, Photo Black, Matte Black	<ul> <li>AC power cable</li> <li>Setup guide</li> </ul>	
Ink Capacity	350, 700 ml	<ul> <li>Software CD-ROM</li> </ul>	
Ink Case	Ink Cartridge	Maintenance box	
Paper Handling			
Paper Path	Roll (Double Roll), Cut Sheet (Manual Feed), Poster Board (Manual Feed) Friction Feed	OPTIONS	
Paper Feed Method Maximum Roll Diameter	Max. 170 mm <sup>°2</sup>	Roll Feed Spindle (4	
Maximum Roll Weight	12.5kg	Production Stacker SSD Unit (C12C936	
Paper Width (Roll)	254 – 1,118 mm	33D 0111 (0120830	071)
Paper Width (Cut Sheet)	203 – 1,118 mm		
Paper Thickness (Roll)	0.07 – 0.8 mm		
Paper Thickness (Manual)	Cut Sheet: 0.07 – 0.8 mm / Poster Board: 0.8 – 1.5 mm	Ink Cartridge CYAN 35	50ml
Maximum Printable Length	91 m <sup>-3</sup>		50ml
Borderless Sizes	254mm (10"), 300mm (11.8"), 330mm (13"), 356mm (14"), 406mm (16"), 432mm		50ml
	(17"), 500mm (19"), 508mm (20"), 515mm (20.3"), 594mm (23"), 610mm (24"),		50ml 50ml
	700mm (27.5"), 728mm (28.6"), 841mm (33"), 914mm (36"), 1030mm (40.5"),		50ml
	1188mm (44")		)0ml
Roll Paper Remaining Connectivity	The remaining amount is managed by the barcode printed on roll paper		)0ml
Interface	SuperSpeed USB <sup>11</sup> , 100BASE-TX /1000BASE-T/IEEE802.11b/g/n/ac		)0ml )0ml
Printer Language	ESC/P raster, HP-GL/2*, HP RTL*, Adobe PostScript 3, Adobe PDF 1.7		)0ml
USB Direct Print	Yes		)0ml
Memory	4GB	Maintenance Tank	
HDD (Optional)	SSD 960GB	Borderless Maintenar Printer Cutter Blade	псе во;
Operating System		Cleaning Stick	
PC System Requirement	Windows 10, 8.1, 8, 7, Windows Vista, Windows XP (32bit/64bit)		
	Windows Server 2019/2016/2012 R2/2012/2008/2003 R2/2003 SP2 or later		
Mac System Requirement	Mac OS X 10.6.8 or later, Mac OS 11 or later	00000 <b>F</b>	
Utility Software	Windows Drieter driver, EnconNet Octure, EnconNet Driet, EnconNet Occific	©2022 Epson Singapore F Reproduction in part or in	
Bundled in CD	Windows - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - EPSON manuals - Manual Launcher - LFP Print Plug-in for Office - PS	permission from Epson, is	strictly p
	SE - EFSON manuals - Manual Launcher - EFF Finit Plug-in for Onice - FS Driver - PS Folder	EPSON and EXCEED YOU trademarks of Seiko Epsor	
Web Delivery	Windows - Epson Media Installer - EpsonNet SetupManager - Epson Device	All other product names a	
	Admin - Epson Edge Dashboard - Epson Print Layout - Epson Print Automate -	used herein are for identific	cation pu
	Epson Edge Print (Option) - Epson Print Admin (Option) - Order Controller (Option)	are the trademarks or regist respective owners.	stered tra
	Mac - Printer driver - EpsonNet Config SE - EPSON manuals - Epson Media	Epson disclaims any and a	all rights i
	Installer - Epson Edge Dashboard - Epson Print Layout - PS DriveriOS/Android -	Projected images shown h The actual product design	nerein are
	Epson Smart Panel	Specifications are subject	to chang
Electrical Specifications		may vary between countrie Epson offices for more info	
Voltage	AC 100 – 240V, 50/60Hz	Apple, iPad and iPhone an	
Rated Current	AC 100V 3.4AAC 100-240V 3.4-1.6A	registered in the U.S. and	other cou
Power Consumption	Operating: Approx. 70W, Ready: Approx. 32W,	a service mark of Apple In Android is a trademark of	
Environmental Conditions	Sleep: Approx. 2.0W, Standby: Approx. 0.3W	Android is a trademark of	aooyie Ir
Temperature	Operating: 10°C to 35°C / Storage: -20°C to 40°C		
Humidity	Operating: 10 C to 35 C / Storage: -20 C to 40 C Operating: 20% to 80% (no condensation), Storage: 5% to 85% (no condensation)	Dealer's Stamp	
Dimensions & Weight			
Dimension (W $\times$ H $\times$ D)	1,848 x 975 x <mark>829</mark> mm		
Weight	Approx. 155 kg		

#### sions and Weight

## 530D t: Approx. 155 kg



## 'S IN THE BOX

- ink cartridge (110ml)
- power cable p guide ware CD-ROM

- tenance box

#### DNS

ed Spindle (44") (C12C936171) tion Stacker (44") (C12C937131) it (C12C936671)

CONSUMABLE			
350ml	C13T48Y200		
350ml	C13T48YE00		
350ml	C13T48Y800		
350ml	C13T48Y300		
350ml	C13T48Y100		
350ml	C13T48Y400		
700ml	C13T48R200		
700ml	C13T48RE00		
700ml	C13T48R800		
700ml	C13T48R300		
700ml	C13T48R100		
700ml	C13T48R400		
Maintenance Tank			
Borderless Maintenance Box			
Printer Cutter Blade			
Cleaning Stick			
	350ml 350ml 350ml 350ml 350ml 350ml 700ml 700ml 700ml 700ml 700ml 700ml 700ml 700ml 700ml		

oson Singapore Pte Ltd. All Rights Reserved. tion in part or in whole, without the written n from Epson, is strictly prohibited. nd EXCEED YOUR VISION are registered of Seiko Epson Corporation.

in are for identification purposes only and demarks or registered trademarks of their owners.

claims any and all rights in those marks. images shown herein are simulations. I product design and contents may vary, ions are subject to change without notice and between countries. Please check with local ces for more information.

d and iPhone are trademarks of Apple Inc., in the U.S. and other countries. App Store is mark of Apple Inc.

a trademark of Google Inc.

within the outside diameter range. <sup>3</sup> Printable length is limited depending on restrictions of operating systems or applications.

#### Find out more at www.epson.com.sg/p-series

📑 EpsonSingapore 💿 EpsonSingapore 🕨 EpsonSoutheastAsia in Epson Singapore

Epson Singapore Pte Ltd Epson Customer Care Center

438B Alexandra Road, Block B Alexandra Technopark, #04-01/04, Singapore 119968. Tel: (65) 6586-5500 100G Pasir Panjang Road, #01-09 Interlocal Centre, Singapore 118523. Epson Helpdesk: 800 120 5564. Please refer to www.epson.com.sg/contact for opening hours.