#### SPECIFICATIONS

MODEL NUMBER	SC-T3130 / SC-T3130N	SC-T3130X	SC-T5130	Dime		
Printer Width	24"		36"	Dime		
Printing Technology						
Print Head	PrecisionCore TFP Printhead			SC-T		
Nozzle Configuration	3,200 nozzles (800 nozzles x 4 channels x 1 head)					
Maximum Resolution	2,400 x 1,200 dpi					
Minimum Ink Droplet Volume	4.0 pl	3.5 pl	4.0 pl			
Line Accuracy	±0.1% or ±0.26 mm					
Print Speed	CAD (A1): 34 seconds		CAD (A1): 31 seconds			
nk System						
nk Type	UltraChrome XD2 Pigment Ink	Black: Pigment, Colour: Dye	UltraChrome XD2 Pigment Ink			
Colours	Cyan, Magenta, Yellow, Black					
Paper Handling						
Maximum Roll Diameter / Weight	2" core, Max 110 mm/3kg	2" core, Max 119 mm/4.2kg	2" core, Max 110 mm/5kg	1		
Paper Width	Roll: 329 mm - 610 mm	Roll: 297 mm - 610 mm	Roll: 329 mm - 914 mm			
	Cutsheet: 210 mm - 610 mm		Cutsheet: 210 mm - 914 mm	1.00		
Side Margin	3mm					
Media Thickness	Roll: 0.05 mm to 0.21 mm. AS	SF/Cutsheet: 0.12 mm to 0.27 mm	)			
Auto-Sheet Feeder	A4 to A3					
Paper Capacity for ASF	50 sheets plain paper / 5 sheets special media					
Connectivity						
Interface	USB 3.0. Ethernet (100BASE-	TX/1000BASE-T), Wi-Fi (IEEE802.	11b/a/n)	Weigl		
Wi-Fi Direct	Wi-Fi Direct (Simple AP)					
Control Panel	4.3" Touch Screen					
Printer Languages	ESC/P raster, HP-GL/2HP RTL					
Scanner Integration	Epson WorkForce DS-530					
	Epson WorkForce DS-650					
	Epson WorkForce DS-60000					
Memory	IGB					
Operating System Requirements	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019,					
operating system nequirements	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019, Mac OS X 10.6.8 or later					
Electrical Specifications				Weig		
Rated Voltage / Frequency / Current	AC 100 to 240V, 50/60Hz, 1.4	14				
Power Consumptions	Operating: Approx. 28W	Operating: Approx. 22W	Operating: Approx. 28W			
	Ready: Approx. 8W	Ready: Approx. 8W	Ready: Approx. 8W	1.17		
	Sleep: Approx. 1.6W	Sleep: Approx. 1.6W	Sleep: Approx. 1.6W			
	Power Off (Stand by):	Power Off (Stand by):	Power Off (Stand by):			
	Approx. 0.2W	Approx. 0.2W	Approx. 0.2W			
Environmental Conditions		Appiox. 0.200				
Temperature	Operating: 10°C to 35°C, Stor	rage: -20°C to 40°C		SC-T		
Humidity		rage: -20 C to 40 C densation), Storage: 5 - 85% (No C	Condensation	Weigh		
Humiaity Sound Pressure			Jondensation)			
	Operating: Approx. 49dB(A), Sleep: Approx. 32dB(A)					
Sound Power	Operating: Approx. 7.5B(A)					
	070 x 010 x 600	070 × 000 × 577 ++++	1 1 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0	1		
Dimension With Stand ( $W \times H \times D$ )	970 x 913 x 696 mm	970 x 928 x 577 mm	1,268 x 913 x 696 mm			
Dimension Without Stand ( $W \times H \times D$ )		970 x 245 x 577 mm	1,268 x 230 x 505 mm			
Weight With Stand	38 kg	40 kg	46 kg			
Weight Without Stand	27 kg	29 kg	33 kg			
What's In The Box	Printer, Printer Stand *1, Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-Rom,					
	Maintenenace Box					
Warranty	3-years Warranty	1-year Warranty	3-years Warranty			

\*1 No stand included for SC-T3130N model.

#### **SPECIFICATIONS**

\*2 Addressable.

\*3 For scanner data processing.
\*4 PDF available only for files scanned by integrated scanner.
\*5 No stand included for SC-T3130M model.

913mm

3mr

nsions and Weight

MODEL NUMBER	SC-T3130M	SC-T51
Printer Width	24"	36"
Printing Technology		
Print Head	PrecisionCore TFP Printhead	
Nozzle Configuration	3,200 nozzles (800 nozzles x 4 channels x 1 hear	d)
Maximum Resolution	2,400 x 1,200 dpi	
Minimum Ink Droplet Volume	4.0 pl	3.7 pl
Line Accuracy	±0.1% or ±0.26 mm	
Minimum Line Width	0.07mm <sup>*1</sup> (0.02mm <sup>*2</sup> )	
Print Speed	CAD (A1): 34 seconds	CAD (A1
Ink System		
Ink Type	UltraChrome XD2 Pigment Ink	
Colours	Cyan, Magenta, Yellow, Black	
Paper Handling		
Maximum Roll Diameter / Weight	2" core, Max 110 mm/3kg	2" core,
Paper Width	Roll: 329 mm - 610 mm	Roll: 297
	Cutsheet: 210 mm - 610 mm	Cutsheet
Side Margin	<u>3mm</u>	
Media Thickness	Roll: 0.05 mm to 0.21 mm, ASF/Cutsheet: 0.12 r	nm to 0.27
Auto-Sheet Feeder	A4 to A3	
Paper Capacity for ASF	50 sheets plain paper / 5 sheets special media	
Scanning		
Sensor	CIS	
Light Source	RGB LED	
Optical Resolution	600 dpi	
Scan Speed (200 dpi)	1.5 ips (Colour) / 4.5 ips (Mono)	
Minimum Document Size	148 mm x 148 mm	
Maximum Document Size	609.6 mm x 2,720 mm	914.4 m
Scan Formats	JPEG, PDF (Single Page), PDF (Multi Page), PDF,	
Scan to Destination	Scan to Network Folder, Scan to FTP Server, Sc	an to Email
Сору		
Copy Speed	77 sec (Colour) / 60 sec (Mono)	
Scaling	25 to 400%	
Maximum Copies	99	
Connectivity		
Interface	USB 3.0, Ethernet (100BASE-TX/1000BASE-T), Wi-Fi Direct (Simple AP)	VVI-FI (IEEE)
Wi-Fi Direct		
Control Panel		
Printer Languages	ESC/P raster, HP-GL/2HP RTL	
Memory	1GB + 8GB *3	
USB Direct Print	PDF *4, TIFF, JPEG Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, V	Vindou o Co
Operating System Requirements	Mac OS X 10.6.8 or later	vindows Se
Electrical Specifications		
Rated Voltage / Frequency / Current	AC 100 to 240V, 50/60Hz, 1.4A	
Power Consumptions	Operating: Approx. 24W	Operatin
Power Consumptions	Ready: Approx. 11W	
	Sleep: Approx. 2.0W	Ready: A
	Power Off (Stand by): Approx. 0.2W	Power C
Environmental Conditions	Fower On (Stand by). Approx. 0.200	FOWERC
Temperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C	<b>`</b>
Humidity		
Humiaity Sound Pressure	Operating: 20 - 80% (No Condensation), Storage Operating: Approx. 47dB(A)	Operatin
Sound Pressure Sound Power	Operating: Approx. 470B(A) Operating: Approx. 6.6B(A)	- Operaum
Printer Dimensions		
Dimension With Stand (W x H x D)	970 x 974 x 696 mm	1,268 x 9
		N/A
Dimension Without Stand (W x H x D) Weight With Stand	970 x 292 x 505 mm 44.4 kg	54.8 kg
Weight With Stand	44.4 kg 33.4 kg	04.8 Kg
Weight Without Stand What's In The Box	33.4 kg Printer, Printer Stand *5, Initial Ink Cartridge, AC F	
What's III The Box	Maintenenace Box	ower Gabl
Warranty	1-year Warranty	
manrality	r-year waitanty	

Partner's Stamp

Information correct at time of printing Printed June 2021

1268mm

© 2021 Epson Singapore Pte Ltd. All Rights Reserved Reproduction in part or in whole, without the written

and EXCEED YOUR VISION are registered trademarks

of Seiko Epson Corporation. All other product names

lentification purposes only and are the trademarks

or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks.

with local Epson offices for more information.


Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check

and other company names used herein are for

ssion from Epson, is strictly prohibited. EPSON







292mm 505mm 970mm

SC-T5130M Weight: 54.8kg



ti). TIFF can to Memory Device

2003 / 2008 / 2012 / 2016 / 2019,

Approx. 26W prox. 12W orox. 2.0W Stand by): Approx. 0.2W

Condensation Approx. 50dB(A)

5 x 696 mm

Setup Guide, Software CD-Rom,

\*1 ISO/IEC 24790, Single weight matte paper, CAD/Line Drawing, Max Quality, High Speed=Off, Finest Detail=On.

© 2021 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information. 

Partner's Stamp

Information correct at time of printing Printed June 2021

# GO BIG ON Possibilities **AND PRECISION.**



#### Distinctive Quality Meets Endless Possibilities For Your Creative Ideas.

Take your ideas to a bigger scale with greater performance and precision with the Epson SureColor T-series printers. With PrecisionCore printhead technology and UltraChrome XD2 ink<sup>+2</sup> to bring about fast printing speeds, enjoy a seamless work process and top-class accuracy in every print. Showcase your ideas and plans in a big way right down to the finest detail.

GO BIG on the details and find out more from our printing experts.



# IT'S IN THE DETAILS.

#### **Detailed Accuracy**

PrecisionCore printhead technology produces impressive accuracy and sharpness at outstanding speeds.


#### **Reliable Efficiency** In-built functions such as Continuous Ink Supply System<sup>\*3</sup> and seamless scan to print

ensure high productivity.

\*1 SC-T3130X stand is optional and is not included in the initial packaging. \*2 For SC-T3130/T3130M/T5130/T5130M only. \*3 For SC-T3130X only.

PRECISIONCORE

Small Footprint Minimally designed to fit effortlessly into tight working spaces.




For accuracy right down to the finest details, the Epson SureColor T-series printers fulfils all your business needs. Using core technologies such as PrecisionCore printheads and UltraChrome XD2 ink, prints are delivered at an outstanding speed with impressive accuracy and clarity. Let your ideas impress your audience with prints that are consistently fast, precise and reliable.



# Compact, User-friendly Design

# PrecisionCore Printhead Technology

Equipped with the next-generation PrecisionCore printhead technology as well as Variable Size Dot Technology, piezo elements are used to mechanically eject ink from the SureColor T-series' PrecisionCore Micro TFP printhead, allow the ink droplets to be controlled to the finesse of 3.5 picolitres, producing incredibly precise line detail, sharp text and photographic-quality graphics. T-series' industry-leading output quality and accuracy will provide a reliable and productive long-term operation.



PRECISIONCORE

### Impressive Print Speeds


The PrecisionCore printhead technology enables remarkable print speeds that will print A1 printouts in 31 seconds\*.

\*Print speed is based on the SC-T5130.



### Nozzle Verification Technology

Print without interruptions with the advanced built-in Nozzle Verification Technology (NVT). This technology monitors nozzle health and adjusts print quality automatically without interruption, even during printing.



zzle is indicated by an irregular residual vibration (pressure change) in the vibration pattern, the printer automaticall adjusts the print quality

#### **Control At Your Fingertips**

A 4.3 inch touch panel on the T-series gives you the convenience of an easy setup and a PC-less operation that just makes things extra efficient.



# **Trusted Productivity**

#### Ink Tank System

The SC-T3130X increases cost savings as it brings on a seamless workflow, eliminating the need for ink replacements that will delay print jobs. With an efficiently designed ink tank and system, ink refills during print jobs can be easily and effortlessly done, without compromising on efficiency.



### Wireless Connectivity

The T-series is integrated with Wi-Fi and Wi-Fi Direct, making it convenient to print right from smart devices anywhere in the office. The Wi-Fi Direct function acts as an access point, allowing devices to connect directly to

the printer without a router. Additionally, the T-series printers come equipped to allow direct wireless printing from any Apple devices through Apple AirPrint\*, without the need for any additional drivers.



\*Apple AirPrint is a trademark of Apple Inc

# Small Footprint

Sleek and minimally designed, the T-series is of a comfortable size that fits into tight work spaces effortlessly. At just 970 x 245 x 577mm without the stand, the SC-T3130X has one of the smallest footprint in its class.

# Seamless Scan To Print

**Epson Cloud Solution PORT** 

Scan and enlarge your printouts in just four easy steps without needing to connect to a computer. Using compatible Epson scanners\* for the SC-T3130/T3130N/T3130X/T5130, you can seamlessly scan and print directly from the T-series printers.



#### \*Recommended scanners: WorkForce DS-530. DS-6500. DS-60000.

Epson Cloud Solution PORT is a cloud-based solution for Epson end users. This software

provides users with the status of the connected printer and alerts for troubleshooting if

required. The Production Monitor allows users to visualise printer operational status,

track usage and print job cost, conveniently from their PC or smart devices.



	Size	SC-T3130/SC-T5130/ SC-T3130M/SC-T5130M	SC-T3130X	Options	SC-T3130	SC-T3130X	SC-T5130	SC-T3130M	SC-T5130M
Cartridge	50ml	C13T40A100		Roll Feed Spindle (24")					
Cartridge	26ml	C13T40A200		C12C933211		•		•	
nk Cartridge	26ml	C13T40A300		Roll Feed Spindle (36")					
Cartridge	26ml	C13T40A400		C12C933131			•		•
Cartridge	80ml	C13T40B100		Printer Stand (24")					
Cartridge	50ml	C13T40B200		C12C933151		•		•	
nk Cartridge	50ml	C13T40B300		Printer Stand (34")					
Cartridge	50ml	C13T40B400		C12C933091			•		
Bottle	140ml	-	C13T49K100	Document Carrier Sheet (A1)					
Bottle	140ml		C13T49K200	C12C936101					
nk Bottle	140ml		C13T49K300	Document Carrier Sheet (A0)					
Bottle	140ml		C13T49K400	C12C936461					

### Maintenance Box

Black Ir

É | Yellow I

Consuma Mode Black Ink Cvan Inl

Auto Cutter Spare Blade

C13S210057 C13S210055

