

LARGE FORMAT PRINTER SURECOLOR™ SC-P10070/P20070

EPSON
EXCEED YOUR VISION



SPEARHEAD PRINTING EXCELLENCE WITH SUPERIOR QUALITY AND SWIFT SPEED.

One good printing experience is all it takes to set new standards. The Epson SureColor™ SC-P10070 and SC-P20070 are professional production printers designed for the best results. Advanced PrecisionCore™ MicroTFP printhead technology yields high speeds of up to 17.5 m²/h*, with accurate dot placement for stand-out visuals. To top it off, the Epson UltraChrome™ PRO nine-colour pigment ink system develops vibrant prints with lasting durability and the high-precision media feeding system ensures smooth, reliable operations.



SC-P10070



SC-P20070



2.64"
Printhead



Up to
64" Wide**



Versatile
Media
Handling



Up to
1.5mm
Thick



Ethernet



IT'S IN THE DETAILS.

With Epson UltraChrome™ ink, the SureColor P-series printers redefine consistent, reliable printing.

Swift Speeds For Maximum Output

New PrecisionCore MicroTFP printhead utilises 8000 nozzles, for class-leading print speeds of up to 17.5 m²/h*.

Affordable Prints With Peace of Mind

The UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Cost-effective 700 ml ink cartridges ensure low printing costs.

Precision Media Feeding System

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.



EPSON ULTRACHROME
PRO INK

*Based on 6-pass printing for high quality production, on photo media.

**Up to 64" wide for SC-P20070, 44" for SC-P10070.

SPECIFICATIONS

SURECOLOR™ SC-P10070/P20070



Model Number	SC-P10070	SC-P20070
Printer Width	44"	64"
Printing Technology	PrecisionCore™ MicroTFP Printhead	
Printhead	Nozzle Verification System	
Printing Method	Black colour ink : 4,000 nozzles (PK, MK, DGY, GY, LGY 800 nozzles each colour)	
Nozzle Configuration	Colour ink : 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)	
Print Direction	Bi-directional printing, uni-directional printing	
	Auto Head Alignment technology	
Print Quality		
Maximum Resolution	2400x1200 dpi	
Minimum Ink Droplet Volume	3.5pl	
Performance*1		
Draft Mode	600 x 600dpi, 1.9 minutes	
Normal Mode	1200 x 1200dpi, 3.0 minutes	
Fine Mode	2400 x 1200dpi, 5.6 minutes	
Ink System		
Ink Type	Epson UltraChrome™ PRO Ink	
Colours	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan, Vivid Light Magenta	
Ink Capacity	700ml/110ml (Bundled)	
Printer Software on CD-ROM		
Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / MacOSX10.6.8 or later Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later 2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later (Certification/Logo : Windows Server 2008/2008R2)	
Paper Handling		
Paper Feed Method	Friction Feed	
Roll Dimensions	170mm	
Paper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44") Cut sheet : 210mm (A4)- 1118mm (44") 0.08-1.50mm	
Borderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 1030mm(B0), 1118mm(44in/B0+)	
	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.), 1372mm(54), 1524(60in.)	
Roll Paper Remaining	The remaining amount is managed by the barcode print on Roll paper.	
Control Panel		
Colour & Size	2.7" Colour LCD	
Number of Dots	960 x 240 pix.	
Connectivity		
Standard	Hi-Speed USB	
Ethernet	1000BASE-T (Recommended) / 100BASE-TX	
Control Code	ESC/P raster	
Memory		
Main	1GB	1.5GB
Software		
PC Software	User's Guide(EN) Network Guide(EN) , LFP RemotePanel 2, Epson Color Calibration Utility, EpsonNet Setup, EpsonNet Config, EpsonNet Print (Windows only)	
Printer Web Function	'Remote Manager' HDD utility - Control of HDD functions	
Software from Web Download	LFP Accounting Tool (Job monitoring, consumable cost tracking), HDD Utility software (Web download)	
Electrical Specifications		
Voltage	AC100-240V 50/60Hz	
Rated Current	5A	
Power Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interface is 1000BASE-T; Power off (Stand-by): Less than 0.5W	
Recommended Operating		
Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C	
Humidity	Operating: 20% - 80% (no condensation); Storage: 5% - 85% (no condensation)	
Acoustic Noise Level		
Sound Pressure Level	Approx 50.5dB (A)	Approx 51.1dB (A) less than
Sound Power Level	Approx 65.3dB (A)	Approx 67dB (A) less than
System Requirement	Windows XP/Vista/7/8/8.1 (32/64bit) or later CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB Macintosh Mac OS X10.6.8 or later CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB	

Dimensions & Weight

SC-P10070

Weight: 126kg



SC-P20070

Weight: 171kg



*1 Figures represent print times only for Epson test sample image (A1 size) as shown, produced on Premium Photo paper.



A1:588x735mm

Ink Cartridge Compatibility

700 ml Ink Cartridges

● Photo Black	C13T809100
● Cyan	C13T809200
● Magenta	C13T809300
● Yellow	C13T809400
● Light Cyan	C13T809500
● Vivid Light Magenta	C13T809600
● Dark Grey	C13T809700
● Matte Black	C13T809800
● Grey	C13T809900
● Light Grey	C13T809000

Supplies & Optional Accessories

Auto Cutter Spare Blade	C13S210040
Cleaning Stick	C13S090013
Maintenance Box	C13T619300
Auto Take-up Reel Unit	C12C932201
Roll Adapter	C12C932231
Adobe® PostScript® 3™	
Expansion Unit	C12C891131
Hard Disk Unit	C12C848031



©2018 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing
Printed November 2018

Sales Enquiries
800 120 5564

[f](#) EpsonSEA
 [@EpsonSEA](#)
[@EpsonSEA](#)
[YouTube](#) EpsonSoutheastAsia
 [in](#) Epson Southeast Asia

To find out more, visit www.epson.com.sg/largeformat or call 800 120 5564

Epson Singapore Pte Ltd 1 Harbourfront Place, #03-02 HarbourFront Tower One, Singapore 098633. Tel: (65) 6586-5500 Fax: (65) 6271-9755

Epson Customer Care Centre 108, Pasir Panjang Road, #04-08 Golden Agri Plaza, Singapore 118535. Epson Helpdesk: 800-120-5564. Operating hours: Monday – Friday, 9am – 6pm, Saturday, 9am – 1pm. Closed on Sunday and Public Holiday.