



## Efficient printing and unrivalled textile print quality, now with orange and violet inks.

Epson new powerhouses, SureColor F6430/F6430H, are setting fresh benchmarks in textile printers with their reliable and superior print quality. Offering a high-performance solution for small to mid-sized textile production companies, these 44" digital dye sublimation printers are equipped with an integrated ink system and the all-new PrecisionCore MicroTFP Printhead. With the addition of orange and violet inks, the SC-F6430H raises the bar with its 6-colour printing, delivering fluorescent brightness and unique colours for specific printing needs.









## Reliable & High Productivity

Equipped with the all-new 1.33-inch PrecisionCore MicroTFP printhead, printing speeds are improved by approximately 20%\*.

## **Integrated Ink System**

Minimise downtime with the improved 1.6L ink capacity along with easy and user-friendly machine operation and maintenance. Ink life after installation has been improved up to one year from just 25 days.

## **Improved Colour Options**

Expand business opportunities with SC-F6430H's improved colour set options which are fluorescent yellow and fluorescent pink, light cyan and light magenta, and orange and violet.

MODEL NUMBER	SC-F6430	SC-F6430H	PRINTER DIMENSION
PRINT			SC-F6430/F6430H
Technology 1 Technology 2	PrecisionCore Inkjet Technology Variable-Sized Droplet Technology	Without Take Up Reel	
Printhead	PrecisionCore MicroTFP Printhe		
Nozzle Configuration	The number of nozzles:	The number of nozzles:	
HOLLIG Commigulation	3,200 nozzles	2,400 nozzles	Co.
	CMYHDK:	CMYHDKLcLm: 2,400 nozzles (400 x 6 colours)	1,128 mm
	3,200 nozzles	CMYHDKFpFy: 2,400 nozzles (400 x 6 colours)	
	(800 x 4 colours)	CMYHDKOrV: 2,400 nozzles (400 x 6 colours)	
Maximum Resolution Minimum Ink Droplet Volume	600 x 1,200 dpi 3.6pl		745 mm
Maximum Print Speed	3.6pi 78.3 m²/h	38.8 m²/h	1,608 mm
Margin (Roll Paper)	3~25 mm (Right/Left) / 5~35 mi		
INK			With Take Up Reel
Ink Types	Dye Sublimation Transfer Ink		
Ink Brand Name	UltraChrome DS Ink	UltraChrome DS 6 Ink	2000 E
Colours	Cyan, Magenta, Yellow, High De	ensity Black	1,128 mm
	N/A	Light Cyan, Light Magenta,	
		Fluorescent Yellow, Fluorescent Pink,	55
Ink Capacity	1.6L	Orange, Violet	
Ink Capacity  Ink Case	Ink Supply Unit		1,608 mm
MEDIA HANDLING	The Gappin Office		1,000 11111
Paper Path	Roll (Single Roll)		
Paper Feed Method	Friction Feed		UltraChrome DS Inks
Paper Width (Roll)	254 mm to 1,118 mm (10" to 4	4")	Cyan C13T53Q200 Magenta C13T53Q300
Paper Thickness (Roll)	Up to 0.5 mm		Yellow C13T53Q400
CONTROL PANEL	100 L T 700 L		High Density Black C13T53Q900
Colour/Size CONNECTIVITY	4.3" Colour LCD Touch Panel		
Interfaces	Super Speed USB, 100BASE-TX/1000BASE-T		UltraChrome DS 6 Inks Light Cyan C13T53Q500
Printer Language	ESC/P raster		Light Magenta C13T53Q600
Memory	1 GB		Fluorescent Pink C13T53Q800
ENVIRONMENT			Fluorescent Yellow C13T53Q700
CHARACTERISTICS			Orange C13T53QA00 Violet C13T53QD00
Temperature (°C)	Operating: 10 °C − 35 °C		Violet C13133QD00
	Storage: -20 °C - 40 °C		Options & Consumables
Humidity	Operating: 20 – 80% (No Condensation)		Auto Take-up Reel Unit C12C934671
<b>DIMENSIONS</b> Printer (W x D x H)	With Take Up Reel: 1,608 x 916 mm x 1,128 mm Without Take Up Reel: 1,608 x 745 mm x 1,128 mm		Roll Adapter C12C934701  Maintenance Kit C13S210063
Filliter (W X D X H)			Head Maintenance Kit C13S400145
WEIGHT	Without take op fleet. 1,000 x	743 11111 X 1,120 111111	Waste Ink Bottle C13T724000
With Take Up Reel:	Approx. 133 kg	Approx. 140 kg	Auto Cutter Spare Blade C13S902006
Without Take Up Reel:	Approx. 120 kg	Approx. 127 kg	*Bundled for SC-F6430H.
ELECTRICAL SPECIFICATION	DN		
Voltage	AC 220 - 240V (withstand volta	ge AC 400V)	
Frequency	50/60 Hz		
Power Consumption	Operating: Approx. 80W		©2022 Epson Singapore Pte Ltd. All Rights Reserved Reproduction in part or in whole, without the written
	Ready: Approx. 36W Sleep: Approx. 19W		permission from Epson, is strictly prohibited.
	Power Off (Standby): Approx. 0.	3///	EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.
ACOUSTIC NOISE LEVEL	1 Ower On (Standby). Approx. 0.	377	All other product names and other company names
Sound Pressure Level - db(A)	53.5 db		used herein are for identification purposes only and
Sound Power Level - B(A)	7.0 B		are the trademarks or registered trademarks of their respective owners.
UTILITY SOFTWARE			Epson disclaims any and all rights in those marks.
Bundled in CD	Epson Software Updater, Epson Net Print, Epson Net Config SE		Projected images shown herein are simulations.
Web Delivery	Epson Edge Print Pro, Epson Edge Colour, Epson Device Admin		The actual product design and contents may vary.  Specifications are subject to change without notice ar
CERTIFICATIONS			may vary between countries. Please check with local
Safety	USA and Canada (NRTL Certified), EU (Low Voltage Directive),		Epson offices for more information.
	Custom Union (Russia, Belarus, Kazakhstan) (EAC),		
	Morocco, Ukraine, India, Argentina (S-mark), Mexico (NOM), UK (UKCA),		Dealer's Stamp
WHAT'S IN THE BOY	Germany (GS), Singapore, Cambodia  Main unit, Stand, Waste ink bottle, Roll adapter, Epson Edge Print Pro DVD,		
WHAT'S IN THE BOX	Software CD, Paper manual and instructions, Warranty sheet, AC cable,		
		o reel unit (standard bundle only for F6430H)	
	maintenance tools, Auto take-u	5 1951 drift (otal laar a ballale only for 1 0 1001)	
			Information correct at time of printing. Printed December 2022







