

Designed specifically for embedded use, the sleek EU-m30 kiosk thermal receipt printer offers innovative kiosk friendly features for easy integration into various self-checkout and self-ordering kiosks.

Discover how the EU-m30 raises the level of service, maximise uptime and improve self-service kiosk performance, accommodating the needs of businesses today.

Remember, it's in the details. epson.com.sq/pos















Reliable Performance

This compact printer features a print speed of up to 250mm/s, with auto-cutter life of 1.5 million cuts for greater efficiency and reliability.

Optimised for Self-Service Environments

Enjoy seamless switch to multiple languages with added Unicode support. Being UL and TÜV certified makes it easier for import and export worldwide.

Maximise System Uptime

The EU-m30 comes equipped with a mounting kit for easy kiosk integration and serviceability. Illuminated LED indicators help with speedy error resolutions in the field.

Optimised For The Self-Service Environment

Ease of Importation/Exportation

With the universally recognised UL and TÜV certification, kiosk vendors can be rest assured that the printer is guaranteed to be a reliable, quality product. There is no further need to spend additional time and money to apply for these certifications.



Multiple Language Support

Print multiple languages in a single receipt without the need to change printer settings with EU-m30's added Unicode support. Kiosk vendors can enjoy greater inventory cost savings, as they are not required to purchase additional printers to support the printing of multiple languages.



Flexible Performance

Business owners can take advantage of the flexible performance of the EU-m30. With its USB and serial interface for seamless integration, this innovative kiosk printer can easily be applied to a kiosk with touchscreen monitor setup, or even a kiosk with tablet setup using a USB converter.






Maximise System Uptime


Detect Error Status Early

Illuminated LED indicators bring attention to error status for swift resolutions in the field, minimising terminal downtime.



Secured Installation

Compact and kiosk friendly, the EU-m30 comes with a mounting kit, providing effortless kiosk integration and serviceability. The mounting brackets ensure secure position of the printer upon installation, without worry of paper misalignment or paper jams.




Prevent Paper Jams

The bezel acts as a paper exit guide, improving paper path alignment, which helps prevent paper jams in a kiosk environment. In addition, the bezel accessory holds the paper in place, making it easier for receipt retrieval.



Mischief Prevention Feature

Bundled with an additional lever cover, paper feed and power switch covers to protect your equipment from the possibility of user tampering and accidental contact. Restricted front cover access and button covers further prevent unauthorised access to the printer.



SPECIFICATIONS EU-m30 **Model Number** Print Technology Print Method Thermal line printing **Print Speed** Up to 250 mm/s **Print Font** ANK Font A: 12 × 24 (Default); ANK Font B: 10 × 24; ANK Font C: 9 x17; Font Kanji Font A: 24 x 24 Character Set 95 Alphanumeric, 18 International, 128 x 43 Graphic UPC-A, UPC-E, JAN8 / EAN8, JAN13 / EAN13, Code39, Code93, Code128, ITF, CODABAR (NW-7), GS1-128, GS1 DataBar Bar Code PDF417, QR Code, Maxi Code, Data Matrix, Aztec, 2D Symbol Two-dimensional GS1 DataBar, Composite Symbology ANK + Thai/Viet + Simplified Chinese + Traditional Chinese + Korean Supported Language + Japanese (Unicode support1) Interface USB + Serial 45 bytes or 4 KB Receive Data Buffer Dot / Line 576 dots Dot / Inch 203 x 203 dpi Paper Dimension (mm) Roll Paper 79.5 ± 0.5 (Width) × 83 (Diameter) Roll Paper 57.5 ± 0.5 (Width) × 83 (Diameter) Power Supply Voltage DC + 24 V \pm 5 % Power Consumption (Operating) 24.2W 5 - 45 °C (41 - 113 °F) Operating Temperature Humidity 10 - 90 % RH **Power Supply** External power supply PS-180 Reliability Printer Mechanism Life 17 Million Lines Auto Cutter Life 1.5 Million Cuts MTBF 360.000 Hours **MCBF** 65 Million Lines Colour Epson Black (EBCK), Epson Ultra White (ENB9) General Information LED Indicators Blue LED = On / Power Orange LED = Error and/or Paper Out Sensor Paper End, Paper Near End Advanced Paper Reduction Built-in Feature Printer Driver Windows Advanced Printer Driver OPOS, OPOS.NET JavaPOS SDK for Android Utility Tool TM Utility (Android) EU-m30 Utility (Windows)

EU-m30



EU-m30 with Bezel

Weight: 1.3kg (Approx.)



(Bezel option sold separately)

What's In The Box

- Epson EU-m30 Printer
- Thermal Roll Paper (Starter Roll for Testing)
- · Power Switch and Power/Feed Switch Covers
- Roll Paper Guides for 58mm Width Paper
- Small Cover Open Lever including 1 Spare Screw
- Equipment Mounting Brackets x 2
- Product Fixing Brackets including 2 Screws + 1 Spare
- External Power Supply PS-180
- Setup Guide

Options

Paper Exit Bezel - OT-BU30

© 2022 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing Printed February 2022





¹ Unicode Support applicable for languages listed above.



Epson Monitoring Tool

Epson Deployment Tool











For more information, visit https://www.epson.co.id/pos

Weight: 1.3kg (Approx.)