


## SPECIFICATIONS

MODEL NUMBER	TM-m30II	TM-m30II-NT	TM-m30II-H
<b>Print Technology</b>	Thermal Line Printing		
<b>Print Font</b>	ANK Font A: 12 x 24 (Default); ANK Font B: 10 x 24; ANK Font C: 9 x 17; Kanji Font: 24 x 24 Font Character Set and Barcode Standards Bar code: UPC-A, UPC-E, JAN8 / EAN 8, JAN13 / EAN13, Code39, Code93, Code128, ITF, CODABAR (NW-7), GS1-128, GS1 DataBar 2D Symbol: PDF417, QR code, Maxi Code, Data Matrix, Aztec, Two-dimensional GS1 DataBar, Composite Symbology		
<b>Supported Language</b>	ANK + Thai/Viet + Simplified Chinese (Unicode support <sup>*1</sup> )	ANK + Thai/Viet + Simplified Chinese + Traditional Chinese + Korean + Japanese (Unicode support <sup>*1</sup> )	
<b>Interface</b>	USB + Ethernet USB + Ethernet + Bluetooth 3.0 EDR	USB + Ethernet + USB Lightning	USB + Ethernet + Bluetooth 3.0 EDR + USB Lightning
<b>Additional Interface Port for Peripheral</b>	1 x USB Type A	1 x USB Type A	3 x USB Type A
<b>Receive Data Buffer</b>	45 bytes or 4 KB		
<b>Print Speed</b>	250 mm/s		
<b>Dot / Line</b>	576 dots		
<b>Dot / Inch</b>	203 x 203 dpi		
<b>Paper</b>	Roll Paper: 79.5 ± 0.5 (W) x Dia. 83 57.5 ± 0.5 (W) x Dia. 83		
<b>Power</b>	DC + 24 V ± 7 % Power Consumption (Operating) 32.4 W   32.8 W Operating Temperature 5 - 45° C (41 - 113° F) Humidity 10 - 90% RH Power Supply External power supply (Model: Adapter-C1)   External power supply (Model: PS-180)		
<b>Reliability</b>	Printer Mechanism Life 17 million lines Auto Cutter Life 1.5 million cuts   2.2 million cuts MTBF 360,000 hours MCBF 65 million lines Colour Epson Black (EBCK), Epson Ultra White (ENB9) Overall Dimensions (W X D X H) 127 x 127 x 135 mm Mass (Approx.) 1.3 Kg		
<b>General Information</b>	LED Indicators Blue LED - Power, Interfaces (LAN, Wi-Fi, Bluetooth) Orange LED - Error and/or Paper Out		
<b>Sensor</b>	Paper End, Cover Open	Paper End, Paper Near End, Cover Open	Paper End, Cover Open
<b>Built-in Feature</b>	Advanced Paper Reduction 180 degree rotation, backfeed guide,	Advanced Paper Reduction, 180 degree rotation, backfeed guide, Network tethering function <sup>*2</sup> , Server Direct Print + Status Notification	
<b>Printer Driver</b>	Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux), TM Virtual Port Driver, CUPS Driver (Linux), Mac Driver		
<b>Utility Tool</b>	TM Utility (iOS, Android), TM-m30II Utility (Windows Desktop), EpsonNet Config (Win, Mac), TM Bluetooth Connector, Deployment Tool, Monitoring Tool, TM-Print Assistant (iOS, Android)		
<b>Easy Setting</b>	Easy pairing with NFC, QR Code	Easy pairing with NFC, QR Code, iBeacon <sup>*3</sup> , USB-Lightning Sync and Charge	
<b>Peripheral Supported</b>	Cash Drawer, OT-WL06 Wi-Fi Dongle, DM-D30 customer display, Barcode Scanner <sup>*4</sup> , USB-Hub <sup>*5</sup> .		
<b>What's in the Box</b>	Roll paper x 1 roll (for checking the initial movement of the printer), Setup guide, Power switch cover, External power supply, Spacer for 58 mm		

<sup>\*1</sup> Unicode support is only for languages listed above.  
<sup>\*2</sup> Only works for iOS devices.  
<sup>\*3</sup> Third party iBeacon dongle is requires.  
<sup>\*4</sup> Third party barcode scanner is requires.  
<sup>\*5</sup> TM-m30II std only.

### Dimensions & Weight

Weight: Approx. 1.3 Kg



### Options & Consumables

Wireless LAN Dongle	OT-WL06
Customer Display Unit	DM-D30
Wall Hanging Unit	OT-WH30
External Buzzer	OT-BZ20

### Legend

dpi dots per 25.4 mm (dots per inch)

©2021 PT Epson Indonesia. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.  
 Printed February 2021

## TABLET POINT-OF-SALE PRINTER TM-m30II/m30II-NT/m30II-H

**EPSON**  
EXCEED YOUR VISION


# VERSATILE TABLET POS SOLUTION WITH ENHANCED CONNECTIVITY.



### Space-friendly receipt printer with configuration and connection flexibility

Accommodating the needs of growing businesses, the Epson TM-m30II POS thermal receipt printer features enhanced connectivity, supporting USB, Ethernet, Bluetooth® and wireless connectivity options. Works ideally as a fuss-free Tablet POS setup with sync and charge function<sup>1</sup>, the sleek and compact 3-inch receipt printer frees up valuable counter space and provides multiple USB-A ports<sup>2</sup> for POS peripherals.

Remember, **it's in the details.** [epson.co.id/pos](https://www.epson.co.id/pos)



### Improved Productivity

The compact printer comes with an improved print speed of up to 250mm/s and an enhanced printer mechanism, print-head, and cutter life.

### Better Connectivity

Enjoy multiple interface options including the sync and charge function<sup>1</sup>, and do more with the additional USB-A ports<sup>2</sup>, which can now support more POS peripherals.

### Efficient & User-friendly

Achieve more with advanced built-in features such as connectivity indicators, rotation printing, which is ideal for printing in kitchen, and paper back-feed, which gives more savings on paper usage.

**1-500-766 0812-12-37766**  
HOTLINE CALL CENTER (NATIONAL AREA)

Epson Indonesia @EpsonIndonesia @EpsonIndonesia Epson Indonesia Epson Indonesia

For more information, visit <https://www.epson.co.id/pos>

<sup>1</sup> Sync and charge function is only applicable to TM-m30II-NT and TM-m30II-H.  
<sup>2</sup> Additional USB-A ports for peripherals is only applicable to TM-m30II-H.



## TABLET POINT-OF-SALE PRINTER TM-m30II/m30II-NT/m30II-H

### HASSLE-FREE TABLET POS SETUP\*

\* For selected models.

Running without complicated cables and set-up, the TM-m30II POS thermal receipt printer pairs easily with peripherals such as scanners and customer display. Designed with transactional efficiency in mind, it supports multiple languages and network tethering without additional fuss.

## COMPACT ALL-PURPOSE MPOS RECEIPT PRINTER

### Improved speed and product reliability

With print speeds of up to 250mm/s, the durable TM-m30II POS thermal receipt printer gets up to 25% boost in speed as compared to its predecessor, the TM-m30, making it a reliable and trusty companion for your business.

### Print more with less

With the character height reduction function, your business can now enjoy paper savings up to 49%\* as compared to the conventional models with the TM-m30II.

Item	TM-m30	TM-m30II	TM-m30II-H TM-m30II-NT
Printer mechanism life	15 mil lines	17 mil lines	17 mil lines
Print head life	100 Km	150 Km	150 Km
Auto cutter life	1.5 mil cuts	1.5 mil cuts	2.2 mil cuts
Mean cycles between failures (MCFB)	60 mil lines	65 mil lines	65 mil lines



\* Backward paper feeding is applied together  
\* Tested with the pattern defined by Seiko Epson / Actual reduction ratio depends on printing patterns  
\* Applicable for alphanumeric text printing only.


### Easy sync and charge For TM-m30II-NT and TM-m30II-H only

No longer do you have to worry about your tablet's battery status while connected to the TM-m30II. The same cable used in transferring your data securely for printing will be charging the tablet at the same time, reducing use of extra cables and saving precious table space.



### Network-tethering For TM-m30II-NT and TM-m30II-H only


Serving as an access point, the TM-m30II enables network connection, using a USB lightning cable, to an external tablet, eliminating unstable Wi-Fi signals.



\*Operating conditions:  
iOS 10.1 or later; iPadOS 13 or later;  
Printer firmware Ver.03.03A ESC/POS or later; Ver.03.03B ESC/POS or later  
[TM-m30II-NT also supports this feature.]

### Supports more peripherals with additional USB-A Ports For TM-m30II-H only


With three additional USB-A ports, you can now connect the Epson TM-m30II to external POS peripherals such as scanners, cash drawers, kitchen buzzers and more, allowing it to do more for your business.



\*Bluetooth is disabled when USB-A is used for tablet data transfer.

### Multi-languages support For TM-m30II-NT and TM-m30II-H only

With additional Unicode support<sup>^</sup>, users can now print multiple languages on one receipt without taking extra steps to change printing settings or switch between printers.



<sup>^</sup>Unicode support is only for languages listed in the specifications sheet.

## USER-FRIENDLY OPERATION


### Ideal for order slip printing in kitchen

With 180° rotation printing function and the front paper loading setting, reading the order slip in the kitchen is made easy without tearing off the paper. Now you can manage and print more order slips with the narrow top margin, uncut center function.



### New status indicator

Checking the status of Bluetooth, Ethernet, and Wi-Fi connections are made simple with the new status indicator on the compact printer.




## GO CLOUD WITH EPSON TM-m30II SERIES

For TM-m30IINT and TM-m30IIH only

### Server direct print

The Epson TM-m30II is able to pull data directly from the server, printing receipts and order slips with additional hassle with the server direct print function.



### Remote maintenance

Your TM-m30II printer is able to update its status directly to the server, allowing you to remotely check and maintain the printer with the Status Notification function.