



Take performance wherever you go with the Epson TM-P80 printer. Featuring fast print speeds of up to 100mm/s and Near Field Communication (NFC) pairing with multiple smart devices, you can be assured of fast and high-quality printing on-the-go. The TM-P80 offers up to 33 hours\* of operational battery life, which ensures uninterrupted service to your customers. Integrating seamlessly with a wide variety of platforms such as iOS, Android™, and Windows operating systems over Wi-Fi or Bluetooth technology, you can count on the TM-P80 to deliver an impeccable quality service experiences.













**ENGINEERED FOR BUSINESS** 

## **Compact and High Performance**

Discover superior print speed, flexible connectivity, and a rugged design with a drop rating of 1.2m that fits in the palm of your hand.

## **Lasting Productivity**

Unrivalled operational battery life, which lasts up to 33 hours\*, provides you with lasting productivity on-the-go.

## **Multi-platform Integration**

Epson ePOS-Print technology allows seamless integration with different platforms, over Wi-Fi or Bluetooth technology.







# **SPECIFICATIONS**

# TM-P80



MODEL NUMBER	TM-P80	- Dimensions & Weight
Print Technology		•
Printing Method	Thermal line printing	TM-P80 Weight: Approx. 630 g
Print Font		Weight Approx. 600 g
Font	48 cpl mode: Font A: 12 × 24 48 cpl (Default); Font B: 9 × 17 64 cpl	
	42 cpl mode: Font A: 13 × 24 42 cpl; Font B: 9 × 17 60 cpl	NOSTER
Character Size (mm)	Font A: 1.5 x 3.0 mm; Font B: 1.12 x 3.0 mm	1
Character Set	95 Alphanumeric, 18 International, 128 x 43 Graphic	69 mm
	Bar code: UPC-A, UPC-E, JAN8/EAN8, JAN13/EAN13, ITF (Interleaved 2 of 5), Codabar (NW-7),	
	Code 39, Code 93, Code 128, GS1-128 (UCC/EAN-128), GS1 DataBar Omnidirectional, GS1 DataBar	
	Truncated, GS1 DataBar Limited, GS1 DataBar Expanded	
	2D Symbol: PDF417, Datamatrix, QR Code, Maxi Code, Composite Symbology, Aztec Code	
Interface	802.11 b/g/n (2.4 GHz) and 802.11 a/n (5 GHz) or Bluetooth 3.0 (EDR supported)	110 mm
Data Buffer	4096 bytes	-
Print Speed Max.	100 mm/sec (Receipt Version)	-
Dot / Line	48 cpl mode: 576 dots (72 mm), 42 cpl mode: 546 dots (68.25 mm)	- Legend
Dot / Inch	203.2 dpi	dpi dots per 25.4 mm (dots per inch)
Paper		cpl characters per 25.4 mm (characters per inch
Dimensions (mm)	Roll paper: 59.5 ± 0.5 (W) × Dia. 51	
Power	Custom Lithium-Ion Battery Pack, AC Adapter (Option)	-
Power Saving	Auto Power-off Function, Wi-Fi Power-saving Function	-
Charging	AC Adapter (2.5 hours to Full Charge)	-
Battery Life*	14 hours (Wi-Fi)   25 hours (Wi-Fi (Energy saving)   33 hours (Bluetooth))	-
Operating Temperature	0 to 45 ° C (32 to 113 ° F) Bluetooth Model; 0 to 40 ° C (32 to 104 ° F) Wi-Fi Model	-
Humidity	10 – 90 % RH	-
Drop Rating	4 feet	-
Reliability		-
Printer Mechanism Life	10 million lines	
Auto Cutter Life**	500,000 cuts	-
MTBF	120,000 hours	-
MCBF	16,000,000 lines	=
Colour	Epson Black (EBCK)	-
Overall Dimensions (W x D x H)	$110 \times 140 \times 69$ mm (Belt clip included)	-
Mass (Approx.)	Wi-Fi Model: Approximately 640 g	* P80 battery life can vary significantly depending on usage.  *Available in Auto Cutter Model.
	Bluetooth Model: Approximately 630 g	
	(Battery and Belt Clip included; Roll Paper excluded)	
Options	Single Charger (OT-SB60II), Battery pack (OT-BY60II), AC Adapter (PS-11)	<ul> <li>© 2016 Epson Singapore Pte Ltd. All Rights Reserved.</li> <li>Reproduction in part or in whole, without the written</li> </ul>
Standard Accessories ROM	Roll paper x 1 roll (for checking the initial movement of the printer), CD-ROM (Drivers, Utility software,	permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names
	Manuals), Setup guide, Battery, Belt Clip, Paper Spacer for 76 mm	
General Information		and other company names used herein are for
Supported Operating Systems	Mobile iOS, Android and Windows (Security Level WEP, WPA, WPA2-Personal/Enterprise)	identification purposes only and are the trademarks
ROM	64 MB	<ul> <li>or registered trademarks of their respective owners.</li> <li>Epson disclaims any and all rights in those marks.</li> </ul>
NV Area	User NV 1 KB, NV Graphics 384 KB	Print samples shown are simulations only. Specifications
Audible Alert	Programmable Buzzer	<ul> <li>and product availability are subject to change without notice and may vary between countries. Please check</li> </ul>
Sensors	Paper End, Cover Open, BM Sensor	with local Epson offices for more information.
<del>-</del>	Battery Charge Level, Power Status, Error Condition	- A. J. 'B. J. J. B
LED Indicators		Apple, iPad and iPhone are trademarks of Apple Inc.,
LED Indicators Software	TM-P80 Utility, EpsonNet Config. EpsonNet Simple Viewer. TM-P80 Remote Configuration Tool	
LED Indicators Software	TM-P80 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P80 Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page	registered in the U.S. and other countries. App Store is a service mark of Apple Inc.
	TM-P80 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P80 Remote Configuration Tool,  TM Bluetooth Connector, Built-In Configuration Page  Easy connection for Bluetooth – NFC, Easy connection for Wi-Fi – NFC, Easy connection for Bluetooth –	registered in the U.S. and other countries. App Store is a

Information correct as at May 2016